[illegible]


- NOTES**
-
- 1- COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 2- STRAINER TO BE MIN. DISTANCE FROM COMPRESSOR INLET NOZZLE.
 - 3- STRAINER TO BE REMOVABLE WITHOUT BREAKING PIPING ALIGNMENT.
 - 4- NON SLAM TYPE SUITABLE FOR COMPRESSOR SERVICE.
 - 5- LOCATE AS CLOSE TO C-2102A OUTLET FLANGE AS POSSIBLE.
 - 6- CONTROL OF COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 7- COMPRESSOR VENDOR TO CONFIRM REQUIREMENT FOR HOT GAS BY-PASS.
 - 8- SHALL BE PROVIDED BY COMPRESSOR VENDOR.
 - 9- PULSATION DAMPERS ARE REQUIRED ON DISCHARGE OF EACH STAGE.
 - 10- REDUNDANT SERIAL LINK SHALL BE CONSIDERED BETWEEN UCP AND DCS. QUANTITIES OF SIGNALS WILL BE FINALIZED LATER.

LEGEND

V : PROVIDE BY COMPRESSOR VENDOR

REFERENCE DRAWING	DRG. No.
Process Flow Diagram	EK-GCS-PEDCO-120-PR-PF-0001
Symbol & Legend For PFD and P&ID	EK-GCS-PEDCO-120-PR-PI-0001

KEY PLAN

[illegible]


- NOTES**
- 1- COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 2- STRAINER TO BE MIN. DISTANCE FROM COMPRESSOR INLET NOZZLE.
 - 3- STRAINER TO BE REMOVABLE WITHOUT BREAKING PIPING ALIGNMENT.
 - 4- NON SLAM TYPE SUITABLE FOR COMPRESSOR SERVICE.
 - 5- LOCATE AS CLOSE TO C-1029B OUTLET FLANGE AS POSSIBLE.
 - 6- CONTROL OF COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 7- COMPRESSOR VENDOR TO CONFIRM REQUIREMENT FOR HOT GAS BY-PASS.
 - 8- SHALL BE PROVIDED BY COMPRESSOR VENDOR.
 - 9- PULSATION DAMPERS ARE REQUIRED ON DISCHARGE OF EACH STAGE.
 - 10- REDUNDANT SERIAL LINK SHALL BE CONSIDERED BETWEEN UCP AND DCS. QUANTITIES OF SIGNALS WILL BE FINALIZED LATER.

LEGEND

V : PROVIDE BY COMPRESSOR VENDOR

REFERENCE DRAWING	DRG. No.
Process Flow Diagram	EK-GCS-PEDCO-120-PR-PF-0001
Symbol & Legend For PFD and P&ID	EK-GCS-PEDCO-120-PR-PI-0001

KEY PLAN

[illegible]

- NOTES**
- 1- COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 2- STRAINER TO BE MIN. DISTANCE FROM COMPRESSOR INLET NOZZLE.
 - 3- STRAINER TO BE REMOVABLE WITHOUT BREAKING PIPING ALIGNMENT.
 - 4- NON SLAM TYPE SUITABLE FOR COMPRESSOR SERVICE.
 - 5- LOCATE AS CLOSE TO C-2102C OUTLET FLANGE AS POSSIBLE.
 - 6- CONTROL OF COMPRESSOR PACKAGE WILL BE FINALIZED BY VENDOR.
 - 7- COMPRESSOR VENDOR TO CONFIRM REQUIREMENT FOR HOT GAS BY-PASS.
 - 8- SHALL BE PROVIDED BY COMPRESSOR VENDOR.
 - 9- PULSATION DAMPERS ARE REQUIRED ON DISCHARGE OF EACH STAGE.
 - 10- REDUNDANT SERIAL LINK SHALL BE CONSIDERED BETWEEN UCP AND DCS. QUANTITIES OF SIGNALS WILL BE FINALIZED LATER.

LEGEND

V : PROVIDE BY COMPRESSOR VENDOR

REFERENCE DRAWING	DRG. No.
Process Flow Diagram	BK-GCS-PEDCO-120-PR-PF-0001
Symbol & Legend For PFD and P&ID	BK-GCS-PEDCO-120-PR-PI-0001

KEY PLAN