

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN
PACKAGES

پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سر يال	نسخه			
BK	GCS	PEDCO	120	PR	SP	0002	D02			

شماره صفحه: 1 از 16

طرح نگهداشت و افزایش تولید ۲۷ مخزن

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES

نگهداشت و افزایش تولید میدان نفتی بینک

01		OLIENT Des Neuroles 505	_			
Rev.	Date	Purpose of Issue/Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval
D00	DEC.2021	IFC	M.Aryafar	M.Fakharian	M.Mehrshad	
D01	MAR.2022	IFA	M.Aryafar	M.Fakharian	M.Mehrshad	
D02	AUG.2022	IFA	M.Aryafar	M.Fakharian	M.Mehrshad	

Class: 2 CLIENT Doc. Number: F0Z-708736

Status:

IDC: Inter-Discipline Check
IFC: Issued For Comment
IFA: Issued For Approval
AFD: Approved For Design
AFC: Approved For Construction
AFP: Approved For Purchase
AFQ: Approved For Quotation
IFI: Issued For Information
AB-R: As-Built for CLIENT Review

AB-A: As-Built -Approved



053 - 073 - 9184

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN

PACKAGES

صادر کننده پروژه بسته کاری رشته تسهيلات نوع مدرك سريال BK GCS PEDCO PR SP 0002 D02 120

شماره صفحه: 2 از 16

REVISION RECORD SHEET

	_	1			
PAGE	D00	D01	D02	D03	D04
1	Х				
2	X				
3 4	X				
5	X	Χ			
6	Χ	X			
7	X	X			
<u>8</u> 9	X	Χ			
10	x	X			
11	Χ	X			
12	X	X X X			
13	X	X			
14 15	X	X			
16		X			
17					
18				ļ	
19 20	1			<u> </u>	
20 21	1				
22					
23					
24					
25					
26 27					
28					
29					
30					
31 32					
33					
34					
35					
36					
37 38					
39					
40					
41					
42	1			-	
43 44					
45					
46			•		
47					
48	1			 	
49 50					
51					
52	1				
53					
54 55					
56					
57					
58					
59				ļ	
60 61	1				
62					
63					
64					

PAGE	D00	D01	D02	D03	D04
66					
67 68					
69					
70					
71					
72					
73 74					
75					
76					
77					
78 79					
80					
81					
82					
83					
84 85					
86					
87					
88					
89 90					
90 91					
92					
93					
94					
95 96					
97					
98					
99					
100					
101 102					
103					
104					
105					
106 107					
107					
109					
110					
111					
112 113					
114					
115					
116					
117 118			1		
118					
120					
121					
122					
123 124			 		
124 125					
126					
127					
128					
129					
130		l	<u> </u>		<u> </u>



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 — 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN
PACKAGES

 HORRICAL

 بسته کاری
 پروژه

 نسخه
 سریال
 نوع مدر ک
 رشته
 تسهیلات
 صادر کننده
 بسته کاری
 پروژه


 BK
 GCS
 PEDCO
 120
 PR
 SP
 0002
 D02

شماره صفحه: 3 از 16

CONTENTS

SCOPE	
000: L	5
NORMATIVE REFERENCES	5
Local Codes and Standards	5
INSTRUMENT/PLANT AIR PACKAGE	6
BASIS OF DESIGN SCOPE OF ENGINEERING AND SUPPLY SERVICES DOCUMENT REQUIREMENT FROM VENDOR GUARANTEES DESIGN REVIEW RESPONSIBILITY OF VENDOR 1	8 0 0
NITROGEN PACKAGE1	2
BASIS OF DESIGN	4 5 5
	NORMATIVE REFERENCES LOCAL CODES AND STANDARDS INTERNATIONAL CODES AND STANDARDS THE PROJECT DOSUMENTS INSTRUMENT/PLANT AIR PACKAGE BASIS OF DESIGN SCOPE OF ENGINEERING AND SUPPLY SERVICES DOCUMENT REQUIREMENT FROM VENDOR GUARANTEES DESIGN REVIEW RESPONSIBILITY OF VENDOR 1 NITROGEN PACKAGE BASIS OF DESIGN 1 SCOPE OF SUPPLY DOCUMENT REQUIRED FROM VENDOR 1 DOCUMENT REQUIRED FROM VENDOR 1 DOCUMENT REQUIRED FROM VENDOR 1 DOCUMENT REQUIRED FROM VENDOR 1







شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES										
			I ACNAC	LO						
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سر يال	نسخه			
BK	GCS	PEDCO	120	PR	SP	0002	D02			

شماره صفحه: 4 از 16

1.0 INTRODUCTION

Binak oilfield in Bushehr province is a part of the southern oilfields of Iran, is located 20 km northwest of Genaveh city.

With the aim of increasing production of oil from Binak oilfield, an EPC/EPD Project has been defined by NIOC/NISOC and awarded to Petro Iran Development Company (PEDCO). Also PEDCO (as General Contractor) has assigned the EPC-packages of the Project to "Hirgan Energy - Design and Inspection" JV.

As a part of the Project, a New Gas Compressor Station (adjacent to existing Binak GCS) shall be constructed to gather of 15 MMSCFD (approx.) associated gases and compress & transfer them to Siahmakan GIS.

GENERAL DEFINITION

The following terms shall be used in this document.

CLIENT: National Iranian South Oilfields Company (NISOC)

PROJECT: Binak Oilfield Development – Surface Facilities; New

Gas Compressor Station

EPD/EPC CONTRACTOR (GC): Petro Iran Development Company (PEDCO)

EPC CONTRACTOR: Joint Venture of : Hirgan Energy – Design & Inspection

(D&I) Companies

VENDOR: The firm or person who will fabricate the equipment or

material.

EXECUTOR: Executor is the party which carries out all or part of

construction and/or commissioning for the project.

THIRD PARTY INSPECTOR (TPI): The firm appointed by EPD/EPC CONTRACTOR (GC)

and approved by CLIENT (in writing) for the inspection

of goods.

SHALL: Is used where a provision is mandatory.

SHOULD: Is used where a provision is advisory only.

WILL: Is normally used in connection with the action by

CLIENT rather than by an EPC/EPD CONTRACTOR,

supplier or VENDOR.

MAY: Is used where a provision is completely discretionary.



نگهداشت و افزایش تولید میدان نفتی بینک

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

PACKAGES									
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه		

BK GCS PEDCO 120 PR 0002 D02 شماره صفحه: 5 از 16

2.0 **SCOPE**

This specification outlines the minimum process requirements for design of Associated Instrument/Plant Air and Nitrogen packages in Binak Plant.

NORMATIVE REFERENCES 3.0

3.1 **LOCAL CODES AND STANDARDS**

Engineering Standard for Process Design of Dryers • IPS-E-PR-905

Engineering Standard for Process Design of Compressed IPS-E-PR-330

Air Systems

3.2 **INTERNATIONAL CODES AND STANDARDS**

American Society for Testing Materials Relevant Parts ASTM

Engineering Standard for Process Design of Compressed API 610

Air Systems

Petroleum and Natural Gas Industries. Materials for use in • ISO 15156

H2S Containing Environments in Oil and Gas Production

3.3 THE PROJECT DOSUMENTS

 BK-GNRAL-PEDCO-000-PR-DB-0001 Process Basis Of Design

 BK-GNRAL-PEDCO-000-PR-DC-0001 Process Design Criteria

• BK-GCS-PEDCO-120-PR-UF-0001 Utility Flow Diagrams (UFD)

P&IDs BK-GCS-PEDCO-120-PR-PI-0002~0025



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES							
				4		H.	12

 نسخه
 سریال
 نوع مدر ک
 رشته
 تسهیلات
 صادر کننده
 بسته کاری
 پروژه

 BK
 GCS
 PEDCO
 120
 PR
 SP
 0002
 D02

شماره صفحه: 6 از 16

4.0 INSTRUMENT/PLANT AIR PACKAGE

4.1 BASIS OF DESIGN

4.1.1 General

The Instrument dryer package will produce dry air for instruments air consumption.

The compressed air will feed the related plant air header and two dryer's bed, one are in operation and one in regeneration. One set dryer's shall be considered as stand-by mode.

The package as minimum will include, air inlet filters, air compressors (two identical 100% in parallel- one on duty and one stand by ready to start), air dryers (mole sieve adsorption), air dryer pre/after filters (two identical 100% in parallel - one on duty and one stand by ready to start). Beds are used such that as the one bed becomes water saturated the other one bed is brought into operation and the saturated one is under regeneration procedure. The dry air will continuously feed the air distribution header at specified following condition.

It should be noted that start-up of spare compressor should not exceed 5 minutes after receiving start-up signal. The auxiliary systems shall be kept in continuous operation to minimize the change overtime.

No instrument air available at black start-up. Dedicated provisions have to be taken for the black start of compressor packages.

4.1.2 Design Basis

4.1.2.1 Operating Case and Design Capacity

The final design capacity of package (including regeneration of dryer's beds) shall be finalized by vendor, to fulfill the stable operation of plant under any of the following situations:

- Normal operation (steady state): The total air demand for instrument (excluding regeneration rate of dryers) will be 91.8 Nm³/hr for instrument air.
- Maximum demand: In which the total air demand (excluding regeneration rate of dryers) will become 119 Nm³/hr. (30% Overdesign has been consider on maximum instrument air consumptions of valves).
- For Regeneration of air dryers 20% of normal consumption has been considered which is equal to 20 Nm³/hr (To be finalized with vendor).
- Total maximum Demand for dryer package: 143.2 Nm³/hr
- 30 Nm³/hr will be considered as total consumption of wet plant air
- Total maximum Demand for air compressors: 173 Nm³/hr (Dry basis with sucked air condition which is mentioned at Design Basis/BEDD condition)



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

PACKAGES										
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه			
BK	GCS	PEDCO	120	PR	SP	0002	D02			

شماره صفحه: 7 از 16

It should be noted that the instrument air consumption for this package shall be excluded from the total instrument air flow rate.

4.1.2.2 Design and Operating Condition

The air supply to the package will have the specifications outlined in Design Basis of Project.

4.1.2.3 Product Requirement



The produced dry air shall have following condition and quality at B.L:

Table No. 4.1: Operating Conditions at Producer's Battery limit

System	Ten	nperatur	e (°C)	Pres	ssure (ba	ar g)
	Min	Norm.	Max	Min	Norm.	Max
Instrument Air	-	60	65	-	9	-
Plant Air	-	60	65	-	4.5	-

Table No. 4.2: Operating Conditions at User's Battery limit

System	Temperature (°C)			(°C) Pressure (bar g)		
	Min	Norm.	Max	Min	Norm.	Max
Instrument Air	-	60	65	4.5	-	8
Plant Air	-	60	65	4.5	-	9

Table No. 4.3: Mechanical Design Conditions

System	Temperature (°C)	Pressure (bar g)		
Instrument Air	85	12.5		
Plant Air	85	12.5		

^{*)} Compressor vendor shall advise max oil concentration in gas at design flow rate.

4.1.2.4 Package Control System

Package control system is "Package type C" (Refer to Project Specifications for Instrumentation of Package Units) which is fully controlled by a Package Control Cabinet (UCP) located either on



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN							
	PACKAGES						
نسخه سربال نوع مدرک رشته تسهیلات صادرکننده بسته کاری یروژه							

 نسخه
 سریال
 نوع مدر ک
 رشته
 تسهیلات
 صادر کننده
 بسته کاری
 پروژه

 BK
 GCS
 PEDCO
 120
 PR
 SP
 0002
 D02

شماره صفحه: 8 از 16

the skid package itself or remotely in the control building. UCP shall be connected to the PCS, ESD, for required monitoring, control functions and shutdowns as per P&ID.

Air System Packages to be installed in safe location.

4.1.3 SITE CONDITION

For site condition, refer to "Design Basis or BEDD of Project".

4.1.4 AVAILABLE UTILITIES

The available utilities for the packages and their conditions are listed in Design Basis. Further to the design basis followings shall be deemed in design:

- Air cooling to be utilized.
- Steam/Cooling water is not available.

4.1.5 Specific Design Requirements

The air production unit shall be complete self-contained unit requiring only utility supplies with the following design considerations:

- The produced dried air shall be analyzed for humidity.
- Interconnecting piping and valving shall be designed for continuous operation.

4.2 SCOPE OF ENGINEERING AND SUPPLY SERVICES

The VENDOR is responsible for all engineering, design, fabrication, assembly, testing, delivery, and documentation of the complete integrated package.

The equipment shall be delivered to site as complete as possible. The minimum amount of disassembly shall be performed to minimize reassembly on site.

The scope of supply includes but is not limited to the following equipment:

1. AIR COMPRESSOR

The major items of equipment furnished by the Supplier for air compressor packages shall include, but not be limited to the following:

- Inlet filter (auto cleaning type)
- Inlet silencer
- Inlet IGV
- Inter-stage air cooler



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN
PACKAGES

پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	
BK	GCS	PEDCO	120	PR	SP	0002	D02	

شماره صفحه: 9 از 16

- Inter-stage water separator and water trap
- After cooler(Air cooler)
- Outlet water separator(at downstream of after cooler) with water trap
- Compressor auxiliary equipment
- Blow off silencer
- Outlet FT for surge control
- PSV at discharge of each compressor
- All required instrumentations for safe operation of compressors
- All piping interconnections
- Relevant equipment for compressor control and safety.
- PT,TT & FT on common discharge header of compressors for load sharing and load management
- PDT for inlet Air Filters
- LT for water separators
- PT& TT for inlet and out let of each stage of compressor
- First filling of consumables such as lube oil and ... is in vendor scope of supply
- All transmitters shall transferred to DCS for operator monitoring purpose
- Package running status /common alarms/faults to be transferred to DCS
- Anti-surge controller for each compressor shall be considered.
- Spare compressor shall be provided.

2. AIR DRYER PACKAGES

The major items of equipment furnished by the Supplier for air dryer packages shall include, but not be limited to the following:

- Air dryers beds (mole sieve adsorption type) (for each package one bed in adsorption and one bed in regeneration mode)
- Silencer for air regeneration discharge line
- All required instrumentations for safe operation of compressors
- All piping interconnections
- Manual globe valve and FT for regeneration line
- Dual-pre-filters & dual-after-filters(Cartridge Element) with spares filters
- Dew point meter at discharge of each air dryers(at downstream of after filters)
- PSV for each beds
- All required sequencing valves for adsorption and regeneration of beds
- All transmitters shall transferred to DCS for operator monitoring purpose(if any)
- The life time of Air dryer's adsorbent shall be minimum 3 years
- Water trap for dual filters
- PDT for inlet and outlet filters and Air Dryer beds
- First filling of mole sieves are in vendor scope of supply All transmitters shall transferred to



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES							
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه
BK	GCS	PEDCO	120	PR	SP	0002	D02

شماره صفحه: 10 از 16

DCS for operator monitoring purpose

- Package running status /common alarms/faults to be transferred to DCS
- Automatic starting of standby Dryer in case of shutdown of running air dryer to be considered.

The instrument air at the outlet of the dryer package shall conform to the following specifications:

• Outlet dew point : -20 °C @9 barg

• Filtration degree: 99% solid particle> 5 micron (Based on ISA-S7.0.01-1996)

• Max oil content: oil free

• Drier allowable Pressure drop: 0.5 bar

3. OTHER SPECIFICATION

Each dryer shall have separate and independent LCP.

4.3 DOCUMENT REQUIREMENT FROM VENDOR

- Process description
- Utility Flow Diagram
- Heat and Material Balance for all operating and design cases
- Equipment Datasheet
- Utility Consumption List
- Equipment List
- Instrument Datasheet
- Operating and Maintenance Manual
- Alarm and Trip Set Point List
- Piping and Instrumentation Diagram
- Control Philosophy and Complex Loop Description
- Performance Curves
- Start-up and shutdown procedure

4.4 GUARANTEES

The VENDOR shall guarantee:

- Air Compressor Design Capacity and delivery pressure at wet air receiver inlet flange
- Air Dryer Design Capacity and delivery pressure at Air dryer outlet common header.
- Air Dryer regeneration rate
- Maximum outlet air temperature
- Maximum Utility consumption at design capacity
- Maximum Impurity content of the produced air



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

PACKAGES									
پروژه	نسخه سریال نوع مدرک رشته تسهیلات صادر کننده بسته کاری پروژه								
BK GCS PEDCO 120 PR SP 0002 D02									

شماره صفحه: 11 از 16

- Maximum pressure drop (1 Bar) for air dryer package with dirty pre& after filters
- Sound pressure level (SPL)(maximum 85 dB at 1 meter distance)
- Air dryer outlet dew point at design capacity
- Maximum particle size (3 micrometers) at air dryer outlet
- The life Time for air dryers and carbon mole sieve bed shall not less than 3 years

4.5 DESIGN REVIEW RESPONSIBILITY OF VENDOR

VENDOR shall have Attendance at design (including design for constructability), coordination. VENDOR shall have overall responsibility for the proper design and safety of the equipment supplied. Any items required as a result of the HAZOP actions are to be fully implemented by VENDOR.

VENDOR shall ensure the relevant personnel are available during the course of the HAZOP sessions. Client/Consultant may ask vendor to participate to further reviews such as Constructability and Maintainability for the equipment to be supplied.

The VENDOR shall include in the package cost, the cost of him and his instruments/ controls SUB-VENDOR(S) participation in the HAZOP & HAZID Study which will be conducted by the client/Consultant.



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUT	Y SPECIFIC	CATION FOR	NSTRUI PACKAG		LANT AIR 8	NITROG	EN
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سر يال	نسخه

120

شماره صفحه: 12 از 16

5.0 NITROGEN PACKAGE

5.1 BASIS OF DESIGN

BK

5.1.1 General

The nitrogen package will produce gaseous nitrogen only. The nitrogen production should be based on pressure swing adsorption system, in which the nitrogen content of air will be separated from oxygen by using adsorption beds.

PR

SP

0002

D02

The compressed wet air will feed nitrogen generation section.

GCS

PEDCO

Water vapor and oxygen will be adsorbed in two individual beds, in which parallel beds are used such that as the one bed becomes oxygen/water saturated the other one bed is brought into operation and the saturated one is under regeneration procedure.

The gaseous nitrogen continuously feeds the nitrogen distribution header under pressure control.

The produced nitrogen is used as:

- Purging of system and equipment at start up and shutdown.
- Blanketing gas in storage tanks, vessels, etc.
- Buffer gas for dry seals of reciprocating compressors.
- Mechanical seal system of pumps (if any)

5.1.2 Design Basis

The nitrogen production package shall operate under any of the following situations:

- Normal operation as seal and buffer gas for compressors and blanket gas for storage tanks.
- Purging activities.

The normal demand of nitrogen consisted of continuous and intermittent consumption is 39.5 Nm³/hr and maximum nitrogen demand will be 43 Nm³/hr, which has been considered as design capacity of nitrogen generation package (10% over design on normal demand including regeneration rate).

Vendor shall provide the maximum turndown flexibility that can be offered without any additional cost.



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES							
نسخه سریال نوع مدرک رشته تسهیلات صادرکننده بسته کاری پروژه							نسخه
BK	GCS	PEDCO	120	PR	SP	0002	D02

شماره صفحه: 13 از 16

The nitrogen at the outlet of this package shall conform to the nitrogen specification of compressor vendor but as a minimum is as the following specifications:

Nitrogen content: 98% vol maxOxygen content: 2% vol max

Carbon dioxide content: 1 ppm vol maxCarbon monoxide content: 10 ppm vol max

Water content: 1 ppm vol max

· Oil content: oil free

5.1.2.1 Design and Operating Condition



The air supply to the package will have the specifications outlined in "PROCESS BASIS OF DESIGN".

5.1.2.2 Product Requirement

The produced nitrogen shall have following condition and quality:

Table No. 5.1: Operating Conditions at Producer's Battery limit

System Temperature (°C) Pressure (bar			Temperature (°C)			ar g)
	Min	Norm.	Max	Min	Norm.	Max
Nitrogen	-	60	-	-	8	-

Table No. 5.2: Operating Conditions at User's Battery limit

System	Temperature (°C)			Pres	ssure (ba	arg)
	Min	Norm.	Max	Min	Norm.	Max
Nitrogen	-	60	-	-	7.5	-

Table No. 5.3: Mechanical Design Conditions

System	Temperature (°C)	Pressure (bar g)
Nitrogen	85	12.5



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES									
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه		
BK	GCS	PEDCO	120	PR	SP	0002	D02		

شماره صفحه: 14 از 16

5.1.2.3 Package Control System

Package control system is "Package type C"(Refer to Project Specifications for Instrumentation of Package Units) which is fully controlled by a Package control cabinet (UCP) located either on the skid package itself or remotely in the control building. UCP shall be connected to the PCS, ESD, for required monitoring, control functions and shutdowns as per P&ID.

Nitrogen System Packages to be installed in safe location.

5.1.3 Site Condition



For site condition, refer to "PROCESS BASIS OF DESIGN".

5.1.4 Available Utilities

The available utilities for the packages and their conditions are listed in Design Basis.

Further to the design basis followings shall be deemed in design:

- Air cooling to be utilized.
- Steam/Cooling water is not available.

5.1.5 Specific Design Requirements

The Nitrogen production package shall be complete self-contained unit requiring only utility supplies with the following design considerations:

- The package shall operate in a safe and reliable condition at plant turndown.
- The produced nitrogen shall be analyzed for humidity and oxygen content.
- Interconnecting piping and valving designed for continuous operation.
- Instrumentation for all control, alarm and safety functions.

5.2 SCOPE OF SUPPLY

The VENDOR is responsible for all engineering, design, fabrication, assembly, testing, delivery, and documentation of the complete integrated package.

The equipment shall be delivered to site as complete as possible. The minimum amount of disassembly shall be performed to minimize reassembly on site.

The scope of supply includes but is not limited to the following equipment:

- 1) Air K.O. drum
- 2) Air compressors
- 3) Air cooler



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

DUTY SPECIFICATION FOR INSTRUMENT/PLANT AIR & NITROGEN PACKAGES

TAGRAGES								
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	
BK	GCS	PEDCO	120	PR	SP	0002	D02	

شماره صفحه: 15 از 16

- 4) Inlet silencer
- 5) Outlet water separator
- 6) Chiller for cooling of inlet wet air(if required)
- 7) Silencer for air regeneration discharge line
- 8) Dual-pre-filters & dual-after-filters(Cartridge Element)
- 9) N₂ Generator
- 10) Dual Particulate Filters(Cartridge Element) (if required)
- 11) O₂ analyzer at discharge of air N₂ Generator(at downstream of particulate filters)
- 12) H₂O analyzer at discharge of air N₂ Generator(at downstream of particulate filters)
- 13) PDI for Filters and beds
- 14) UV(on-off valve) for temperature control, TT, check valve for Nitrogen Gaseous discharge line.
- 15) All required TSV,PSV and on/off valves for gaseous nitrogen lines for safe operation

5.3 DOCUMENT REQUIRED FROM VENDOR

- Process description
- Utility Flow Diagram
- Heat and Material Balance for all operating and design cases
- Equipment Datasheet
- Utility Consumption List
- Equipment List
- Instrument Datasheet
- Operating and Maintenance Manual
- Alarm and Trip Set Point List
- Piping and Instrumentation Diagram
- Control Philosophy and Complex Loop Description
- Performance Curves
- Start-up and shutdown procedure

5.4 GUARANTEES

The vendor shall guarantee:

- The production capacity
- The nitrogen purity and impurities.
- Pressure and Temperature of nitrogen at battery limit.
- The maximum pressure drop across the package.
- Utility consumption at design capacity.
- The life Time for adsorption beds shall not less than 3 years
- Noise limit level as per project specification(Maximum allowable noise level produced by each individual unit in operation shall be less than 85 dB at 1 meter from the involved equipment.)



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

PACKAGES									
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سر يال	نسخه		
BK	GCS	PEDCO	120	DD	SD.	0002	DUS		

شماره صفحه: 16 از 16

5.5 DESIGN REVIEW RESPONSIBILITY OF VENDOR

VENDOR shall have Attendance at design (including design for constructability), coordination. VENDOR shall have overall responsibility for the proper design and safety of the equipment supplied. Any items required as a result of the HAZOP actions are to be fully implemented by VENDOR.

VENDOR shall ensure the relevant personnel are available during the course of the HAZOP sessions. Client/Consultant may ask vendor to participate to further reviews such as Constructability and Maintainability for the equipment to be supplied.

The VENDOR shall include in the package cost, the cost of him and his instruments/ controls SUB-VENDOR(S) participation in the HAZOP & HAZID Study which will be conducted by the client/Consultant.