



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

شماره پیمان:

053-073-9184

CALCULATION NOTE FOR PSV SIZING

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D03	0004	CN	PR	120	PEDCO	GCS	BK

شماره صفحه: 1 از 14

طرح نگهداشت و افزایش تولید 27 مخزن

CALCULATION NOTE FOR PSV SIZING

نگهداشت و افزایش تولید میدان نفتی بینک

D03	OCT.2022	IFA	M.Aryafar	M.Fakharian	M.Mehrshad	
D02	APR.2022	IFA	M.Aryafar	M.Fakharian	M.Mehrshad	
D01	JAN.2022	IFA	M.Aryafar	M.Fakharian	M.Mehrshad	
D00	SEP.2021	IFC	M.Aryafar	M.Fakharian	Sh.Ghalikar	
Rev.	Date	Purpose of Issue/Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

Class: 2

CLIENT Doc. Number: F0Z-708742

Status:

IDC: Inter-Discipline Check
IFC: Issued For Comment
IFA: Issued For Approval
AFD: Approved For Design
AFC: Approved For Construction
AFP: Approved For Purchase
AFQ: Approved For Quotation
IFI: Issued For Information
AB-R: As-Built for CLIENT Review
AB-A: As-Built -Approved



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053-073-9184

CALCULATION NOTE FOR PSV SIZING

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D03	0004	CN	PR	120	PEDCO	GCS	BK

شماره صفحه: 2 از 14

REVISION RECORD SHEET

PAGE	D00	D01	D02	D03	D04
1	X	X	X	X	
2	X	X	X	X	
3	X				
4	X				
5	X	X	X		
6	X	X	X		
7	X	X	X		
8	X	X			
9	X		X		
10	X				
11	X				
12	X		X	X	
13	X		X	X	
14	X		X	X	
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					
65					

PAGE	D00	D01	D02	D03	D04
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
122					
123					
124					
125					
126					
127					
128					
129					
130					

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 – 073 – 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>پروژه</th><th>بسته کاری</th><th>صادر کننده</th><th>تسهیلات</th><th>رشته</th><th>نوع مدرک</th><th>سریال</th><th>نسخه</th></tr><tr><td>BK</td><td>GCS</td><td>PEDCO</td><td>120</td><td>PR</td><td>CN</td><td>0004</td><td>D03</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	BK	GCS	PEDCO	120	PR	CN	0004	D03	شماره صفحه : 3 از 14
CALCULATION NOTE FOR PSV SIZING																										
پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه																			
BK	GCS	PEDCO	120	PR	CN	0004	D03																			

CONTENTS

1.0	INTRODUCTION	4
2.0	SCOPE	5
3.0	NORMATIVE REFERENCES.....	5
3.1	LOCAL CODES AND STANDARDS.....	5
3.2	INTERNATIONAL CODES AND STANDARDS.....	5
3.3	THE PROJECT DOCUMENTS.....	5
3.4	ENVIRONMENTAL DATA	5
4.0	PSV SIZING.....	5
4.1	FIRE; EXTERNAL FIRE ON THE UNWETTED SURFACE OF VESSEL.....	6
4.2	FIRE; EXTERNAL FIRE ON THE WETTED SURFACE OF VESSEL	7
4.3	BLOCKED OUTLET	9
5.0	RELIEF LOAD SUMMARY TABLE	11
	ATTACHMENT: SOFTWARE REPORT	14

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 – 073 – 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>پروژه</th><th>بسته کاری</th><th>صادر کننده</th><th>تسهیلات</th><th>رشته</th><th>نوع مدرک</th><th>سریال</th><th>نسخه</th></tr><tr><td>BK</td><td>GCS</td><td>PEDCO</td><td>120</td><td>PR</td><td>CN</td><td>0004</td><td>D03</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	BK	GCS	PEDCO	120	PR	CN	0004	D03	شماره صفحه : 4 از 14
CALCULATION NOTE FOR PSV SIZING																										
پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه																			
BK	GCS	PEDCO	120	PR	CN	0004	D03																			

1.0 INTRODUCTION

Binak oilfield in Bushehr province is a part of the southern oilfields of Iran, is located 20 km northwest of Genaveh city .

With the aim of increasing production of oil from Binak oilfield, an EPC/EPD Project has been defined by NIOC/NISOC and awarded to Petro Iran Development Company (PEDCO). Also PEDCO (as General Contractor) has assigned the EPC-packages of the Project to "Hirgan Energy - Design and Inspection" JV.

As a part of the Project, a New Gas Compressor Station (adjacent to existing Binak GCS) shall be constructed to gather of 15 MMSCFD (approx.) associated gases and compress & transfer them to Siahmakan GIS.

GENERAL DEFINITION

The following terms shall be used in this document.

CLIENT:	National Iranian South Oilfields Company (NISOC)
PROJECT:	Binak Oilfield Development – Surface Facilities; New Gas Compressor Station
EPD/EPC CONTRACTOR (GC):	Petro Iran Development Company (PEDCO)
EPC CONTRACTOR:	Joint Venture of : Hirgan Energy – Design & Inspection (D&I) Companies
VENDOR:	The firm or person who will fabricate the equipment or material.
EXECUTOR:	Executor is the party which carries out all or part of construction and/or commissioning for the project.
THIRD PARTY INSPECTOR (TPI):	The firm appointed by EPD/EPC CONTRACTOR (GC) and approved by CLIENT (in writing) for the inspection of goods.
SHALL:	Is used where a provision is mandatory.
SHOULD:	Is used where a provision is advisory only.
WILL:	Is normally used in connection with the action by CLIENT rather than by an EPC/EPD CONTRACTOR, supplier or VENDOR.
MAY:	Is used where a provision is completely discretionary.

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک								
شماره پیمان: 053 – 073 – 9184	CALCULATION NOTE FOR PSV SIZING								شماره صفحه : 5 از 14
	پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	
	BK	GCS	PEDCO	120	PR	CN	0004	D03	

2.0 SCOPE

The scope of this document is to provide sizing calculation of Pressure Safety Valves's of BINAK New GCS unit.

3.0 NORMATIVE REFERENCES

3.1 LOCAL CODES AND STANDARDS

- IPS-E-PR-450 Process Design Of Pressure Relieving systems inclusive safety relief valves
- IPS-E-PR-460 Process Design Of Flare And Blowdown Systems

3.2 INTERNATIONAL CODES AND STANDARDS

- API-STD-520 Sizing, Selection and Installation of Pressure Relieving Devices in Refineries, Part 1-Sizing and Selection
- API-STD-521 Pressure Relieving and Depressuring Systems
- API-STD-526 Flanged Steel Pressure Relief Valves

3.3 THE PROJECT DOCUMENTS

- BK-GNRAL-PEDCO-000-PR-DB-0001 Process Basis of Design
- BK-GNRAL-PEDCO-000-PR-DC-0001 Process Design Criteria
- BK-GCS-PEDCO-120-PR-PF-0001 Process Flow Diagram (PFD)
- BK-GCS-PEDCO-120-PR-PI-0002~25 Piping & Instrumentation Diagram

3.4 ENVIRONMENTAL DATA

Refer to "Process Basis of Design; Doc. No. BK-GNRAL-PEDCO-000-PR-DB-0001".

4.0 PSV SIZING

Following two over pressure scenarios are recognized for Kashan gas compressor station, which PSV's are considered to protect relevant equipments & pipings against pressure increasing.

- FIRE (UNWETTED)
- FIRE (WETTED)
- BLOCKED OUTLET

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 - 073 - 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>پروژه</th><th>بسته کاری</th><th>صادرکننده</th><th>تسهیلات</th><th>رشته</th><th>نوع مدرک</th><th>سریال</th><th>نسخه</th></tr><tr><td>BK</td><td>GCS</td><td>PEDCO</td><td>120</td><td>PR</td><td>CN</td><td>0004</td><td>D03</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	BK	GCS	PEDCO	120	PR	CN	0004	D03	شماره صفحه : 6 از 14
CALCULATION NOTE FOR PSV SIZING																										
پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه																			
BK	GCS	PEDCO	120	PR	CN	0004	D03																			

4.1 FIRE; EXTERNAL FIRE ON THE UNWETTED SURFACE OF VESSEL

According to API 521 2007, The discharge areas for pressure-relief devices on vessels containing super-critical fluids, gases or vapors exposed to open fires can be estimated using Equation 1.

$$A = \frac{F' \cdot A'}{\sqrt{P_1}} \quad (1)$$

Where

A is the effective discharge area of the valve, expressed in SI units (square inches);

A' is the exposed surface area of the vessel, expressed in SI units (square feet);

P1 is the upstream relieving absolute pressure, expressed in SI units (psi);

NOTE: p1 is the set pressure plus the allowable overpressure plus the atmospheric pressure.

F' can be determined using Equation (2). If calculated using Equation (2) and the result is less than 0,01, then use a recommended minimum value of F' =0,01. If insufficient information is available to use Equation (2), then use F' =0,045.

$$F' = \frac{0,1406}{C \cdot K_D} \left[\frac{(T_w - T_1)^{1,25}}{T_1^{0,6506}} \right] \quad (2)$$

Where

KD is the coefficient of discharge (obtainable from the valve manufacturer);

NOTE: A KD value of 0.975 is typically used for preliminary sizing of pressure-relief valves (see API RP 520-1 or ISO 4126).

Tw is the recommended maximum wall temperature of vessel material

T1 is the gas absolute temperature, at the upstream relieving pressure, determined from Equation (4), expressed in °R.

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053-073-9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>پروژه</th><th>بسته کاری</th><th>صادرکننده</th><th>تسهیلات</th><th>رشته</th><th>نوع مدرک</th><th>سریال</th><th>نسخه</th></tr><tr><td>BK</td><td>GCS</td><td>PEDCO</td><td>120</td><td>PR</td><td>CN</td><td>0004</td><td>D03</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	BK	GCS	PEDCO	120	PR	CN	0004	D03	شماره صفحه : 7 از 14
CALCULATION NOTE FOR PSV SIZING																										
پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه																			
BK	GCS	PEDCO	120	PR	CN	0004	D03																			

C is given by Equation (3):

$$C = 520 \sqrt{k \left(\frac{2}{k+1} \right)^{\frac{k+1}{k-1}}} \quad (3)$$

Where

k is the specific heat ratio (Cp/Cv) of gas or vapor at relieving conditions;

$$T_1 = \frac{p_1}{p_n} \cdot T_n \quad (4)$$

where

p_n is the normal operating gas absolute pressure, expressed in SI units (psi);

T_n is the normal operating gas absolute temperature, expressed in SI units (°R).

The recommended maximum vessel wall temperature, T_w, for the usual carbon steel plate materials is 593 °C (1 100 °F).

The relief load, q_{m, relief}, expressed in pounds per hour, can be calculated from equation (5)

$$q_{m, relief} = 0,1406 \sqrt{M \cdot p_1} \left[\frac{A' (T_w - T_1)^{1,25}}{T_1^{1,1506}} \right] \quad (5)$$

Where M is the relative molecular mass of the gas.

4.2 FIRE; EXTERNAL FIRE ON THE WETTED SURFACE OF VESSEL

The amount of heat absorbed by a vessel exposed to an open fire is markedly affected by the type of fuel feeding the fire, the degree to which the vessel is enveloped by the flames (a function of vessel size and shape), and fireproofing measures.

Adequate drainage is necessary to control the spread of major spills from one area to another and to control surface drainage and refinery waste water. This can be accomplished by the

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 – 073 – 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>پروژه</th><th>بسته کاری</th><th>صادرکننده</th><th>تسهیلات</th><th>رشته</th><th>نوع مدرک</th><th>سریال</th><th>نسخه</th></tr><tr><td>BK</td><td>GCS</td><td>PEDCO</td><td>120</td><td>PR</td><td>CN</td><td>0004</td><td>D03</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	BK	GCS	PEDCO	120	PR	CN	0004	D03	شماره صفحه : 8 از 14
CALCULATION NOTE FOR PSV SIZING																										
پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه																			
BK	GCS	PEDCO	120	PR	CN	0004	D03																			

strategic use of sewers and trenches with adequate capacity and/or by using the natural slope of the land.

Where adequate drainage and firefighting equipment do not exist, Equation 6 should be used

$$Q = 34,500FA^{0.82} \quad (6)$$

Qtotal: heat absorption (input) to the wetted surface (BTU/hr)

F: Environment factor. (Values for various types of installation are shown in Table 5 API 521)

A: Total wetted surface, in square feet (see 3.15.1.1 and Table 4 API 521.)

W required flow through the device from Equations (vessel containing liquid): (7)

$$W = Q \text{ (BTU/hr)} \div \text{Latent Heat of Vaporisation (BTU/lb)}$$

According to API 521 2007, The discharge areas for pressure-relief devices on vessels containing super-critical fluids, gases or vapours exposed to open fires can be estimated using Equation 8.

$$C = 520 \sqrt{k \left(\frac{2}{k+1} \right)} A = \frac{W}{CK_d P_L K_b K_c} \sqrt{\frac{TZ}{M}} \quad (8)$$

Where

A required effective discharge area of the device, in²

W required flow through the device from Equations (7), lb/hr.

C coefficient determined from Equations (3).

Kd effective coefficient of discharge. For preliminary sizing, use the following values:

0.975 When a pressure relief valve is installed with or without a rupture disk in combination,

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک								
شماره پیمان: 053 – 073 – 9184	CALCULATION NOTE FOR PSV SIZING								شماره صفحه: 9 از 14
	پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	
	BK	GCS	PEDCO	120	PR	CN	0004	D03	

0.62 When a pressure relief valve is not installed and sizing is for a rupture disk

P1 upstream relieving pressure, psia. This is the set pressure plus the allowable overpressure plus atmospheric pressure.

Kb capacity correction factor due to back pressure. The back pressure correction factor applies to balanced bellows valves only. For conventional and pilot operated valves, use a value for Kb equal to 1.0

Kc combination correction factor for installations with a rupture disk upstream of the pressure relief valve

1.0 When a rupture disk is not installed,

0.9 When a rupture disk is installed in combination with a pressure relief valve and the combination does not have a published value.

T relieving temperature of the inlet gas or vapour, R (°F + 460)

Z compressibility factor

M molecular weight of the gas or vapour at inlet relieving conditions.

4.3 BLOCKED OUTLET

The absolute pressure ratio of the pressure at the nozzle exit at sonic velocity (P_{cf}) to the inlet pressure (P₁) is called the critical pressure ratio. P_{cf} is known as critical flow pressure and can be estimated using the following equation (API 520):

$$\frac{P_{cf}}{P_1} = \left[\frac{2}{K+1} \right]^{K/(K-1)} \quad (9)$$

Where:

P_{cf}= critical flow nozzle pressure in psia

P₁=upstream relieving pressure in psia

K= ratio of specific heats

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک								
شماره پیمان: 053 - 073 - 9184	CALCULATION NOTE FOR PSV SIZING							شماره صفحه : 10 از 14	
	پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال		نسخه
	BK	GCS	PEDCO	120	PR	CN	0004		D03

If the pressure downstream of the nozzle is less than or equal to the critical flow pressure P_{cf} , then critical flow will occur and following procedure will be used to determine the required effective discharge area of the device.

According to API-520 2007, Pressure relief devices in gas or vapor service that operate at closed outlet conditions are sized using Equations (10). This equations is used to calculate the effective discharge area, A , required to achieve a required flow rate through a pressure relief device. A pressure relief valve that has an effective discharge area equal to or greater than the calculated value of A is then chosen for the application from API-526.

$$A = \frac{W}{CK_d P_1 K_b K_c} \sqrt{\frac{TZ}{M}} \quad (10)$$

Where

A required effective discharge area of the device, in²

W required flow through the device, lb/hr.

C coefficient determined from Equations (3).

K_d effective coefficient of discharge. For preliminary sizing, use the following values:

0.975 When a pressure relief valve is installed with or without a rupture disk in combination,

0.62 When a pressure relief valve is not installed and sizing is for a rupture disk

P_1 upstream relieving pressure, psia. This is the set pressure plus the allowable overpressure plus atmospheric pressure.

K_b capacity correction factor due to back pressure. The back pressure correction factor applies to balanced bellows valves only. For conventional and pilot operated valves, use a value for K_b equal to 1.0

K_c combination correction factor for installations with a rupture disk upstream of the pressure relief valve

1.0 When a rupture disk is not installed,

0.9 When a rupture disk is installed in combination with a pressure relief valve and the combination does not have a published value.

T relieving temperature of the inlet gas or vapour, R ($^{\circ}\text{F} + 460$)

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 – 073 – 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>نسخه</th><th>سریال</th><th>نوع مدرک</th><th>رشته</th><th>تسهیلات</th><th>صادرکننده</th><th>بسته کاری</th><th>پروژه</th></tr><tr><td>D03</td><td>0004</td><td>CN</td><td>PR</td><td>120</td><td>PEDCO</td><td>GCS</td><td>BK</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه	D03	0004	CN	PR	120	PEDCO	GCS	BK	شماره صفحه : 11 از 14
CALCULATION NOTE FOR PSV SIZING																										
نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه																			
D03	0004	CN	PR	120	PEDCO	GCS	BK																			

Z compressibility factor

M molecular weight of the gas or vapor at inlet relieving conditions.

PSV SIZING CALCULATION REPORT

software

The software using for sizing Pressure safety valve is valve star. Pressure safety valve sizing report have been reported as following attachment.

5.0 RELIEF LOAD SUMMARY TABLE



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض
احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

CALCULATION NOTE FOR PSV SIZING

پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه
BK	GCS	PEDCO	120	PR	CN	0004	D03

شماره صفحه : 12 از 14

D03 PSV No.	PSV- 2111/2112	PSV- 2113/2114	PSV-2121A/B/C	PSV- 2122,2123A/B/C	PSV-2131 A/B/C
Service	V-2104	V-2105	V-2101 A/B/C	C-2101A/B/C	V-2102A/B/C
Fire	YES	-	YES	-	YES
Other	-	Blocked Outlet	-	Blocked Outlet	-
Fluid & State	HC	HC	HC	HC	HC
Operating Pressure (Bara)	5.3	5.1	4.9	19.0	18.1
Normal Temperature (°C)	31.86	36.92	36.78	124.8	60
Relief Temperature (°C)	284	280	350.7	204	208.3
P set, Barg	9.00	9.00	9.00	22.00	22.00
Required massflow (kg/hr)	27770.9	17833.11	342.89	8664.00	982.27
Specific Heat Ratio (Cp/Cv)	1.223	1.246	1.245	1.225	1.278
Molecular Weight (kg/Kmol)	37.85	24.52	20.5	24.52	24.52
Compressibility Factor	0.945	0.974	0.975	0.964	0.936
Total Back Pressure (Barg)	3.3	2.4	3.0	1.3	3.2
Allowable Over Pressure (%)	21	10	21	10	21
Calculated Discharge Area	3458.068	3024.427	53.556	591.135	59.62
Required Discharge Area (mm ²)	4358	3769.279	120.246	719.546	127.757
Orifice Designation	P	P	D	J	D
Body size	4" × 6"	4" × 6"	1" × 2"	2" × 3"	1" × 2"
Capacity exceed %	14.6	33.3	28.0	41.46	20.49
P&ID Number	BK-GCS-PEDCO-120-PR-PI-0004 (3/1)	BK-GCS-PEDCO-120-PR-PI-0005 (1/1)	BK-GCS-PEDCO-120-PR-PI-0006 (1~3)	BK-GCS-PEDCO-120-PR-PI-0007 (3~1)	BK-GCS-PEDCO-120-PR-PI-0009



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض
احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

053 - 073 - 9184

CALCULATION NOTE FOR PSV SIZING

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D03	0004	CN	PR	120	PEDCO	GCS	BK

شماره صفحه : 13 از 14

PSV No.	PSV-2132,2133A/B/C	PSV-2141/2142	PSV-2201 A/B	PSV-2211 A/B	PSV-2271 A/B	PSV-2239
Service	C-2102A/B/C	V-2103	V-2203	V-2204	V-2205	V-2107
Fire	-	YES	YES	YES	YES	YES
Other	Blocked Outlet	-	-	-	-	-
Fluid & State	HC	HC	Air	N2	HC	TEG
Operating Pressure (Barg)	54.80	53.9	8.0	8.0	4.9	0.1
Normal Temperature (°C)	142.3	60	65	60	36.78	AMB
Relief Temperature (°C)	233	286	323.4	323.4	350.7	335.9
P set, Barg	62.0	62.0	12.5	12.5	9.0	3.5
Required massflow (kg/hr)	8,664	17,763.1	1,071.8	500.39	174.5	2098.014
Specific Heat Ratio (Cp/Cv)	1.278	1.461	1.416	1.4	1.245	1.083
Molecular Weight (kg/Kmol)	24.52	18.96	28.95	28.00	20.05	88.11
Compressibility Factor	0.923	0.823	0.99	1.00	0.975	0.646
Total Back Pressure (Barg)	1.2	2.1	0.5	0.5	3.2	0
Allowable Over Pressure (%)	10	21	21	21	21	21
Calculated Discharge Area	213.771	430	113.24	54.241	27.258	350.982
Required Discharge Area (mm ²)	260.208	523.298	137.85	116.23	61.787	427.226
Orifice Designation	G	H	E	D	D	H
Body size	1 1/2" × 3"	2" × 3"	1" × 2"	1" × 2"	1" × 2"	1 1/2" × 3"
Capacity exceed %	52.80	20.2	11.67	32.44	149	47.23
P&ID Number	BK-GCS-PEDCO-120-PR-PI-0010 (1~3)	BK-GCS-PEDCO-120-PR-PI-0012 (1/1)	BK-GCS-PEDCO-120-PR-PI-0015 (2/2)	BK-GCS-PEDCO-120-PR-PI-0016 (1/1)	BK-GCS-PEDCO-120-PR-PI-0022	BK-GCS-PEDCO-120-PR-PI-0025

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک																									
شماره پیمان: 053 – 073 – 9184	<table><tr><th colspan="8">CALCULATION NOTE FOR PSV SIZING</th></tr><tr><th>نسخه</th><th>سریال</th><th>نوع مدرک</th><th>رشته</th><th>تسهیلات</th><th>صادر کننده</th><th>بسته کاری</th><th>پروژه</th></tr><tr><td>D03</td><td>0004</td><td>CN</td><td>PR</td><td>120</td><td>PEDCO</td><td>GCS</td><td>BK</td></tr></table>	CALCULATION NOTE FOR PSV SIZING								نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادر کننده	بسته کاری	پروژه	D03	0004	CN	PR	120	PEDCO	GCS	BK	شماره صفحه : 14 از 14
CALCULATION NOTE FOR PSV SIZING																										
نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادر کننده	بسته کاری	پروژه																			
D03	0004	CN	PR	120	PEDCO	GCS	BK																			



ATTACHMENT: SOFTWARE REPORT