

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض







احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER

شماره پیمان:	پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه
3A1P - 7Y - 70·	BK	GCS	PEDCO	120	ME	DT	8000	D02

شماره صفحه: ۱ از ۸

طرح نگهداشت و افزایش تولید ۲۷ مخزن

MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER

نگهداشت و افزایش تولید میدان نفتی بینک

D02	JUN.2023	IFA	H.Adineh	M.Fakharian	A.M.Mohseni	
D01	SEP. 2022	IFA	H.Adineh	M.Fakharian	M.Mehrshad	
D00	NOV.2021	IFC	H.Adineh	M.Fakharian	M.Mehrshad	
Rev.	Date	Purpose of Issue / Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

Class: 1 CLIENT Doc. Number: F0Z-708839

status: IDC: Inter-Discipline Check

IFC: Issued For Comment
IFA: Issued For Approval
AFD: Approved For Design
AFC: Approved For Construction
AFP: Approved For Purchase
AFQ: Approved For Quotation

AB-R: As-Built for CLIENT Review

AB-A: As-Built -Approved

IFI: Issued For Information



۱۸۶ – ۲۲۰ – ۱۸۶

شماره پیمان:

پروژه

BK

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک







شماره صفحه: ۲ از ۸

D04

REVISION RECORD SHEET

				RE	VISION RE	CORD	SHEET				
Page	D00	D01	D02	D03	D04		Page	D00	D01	D02	D03
1	Х	Х	Х			1	65				
2	X	X	X			1	66				
3	X	X	,,			1	67				
4	X	X				1	68				
5	X	X	Х			1 🗁	69			1	
6	X	X	X			1	70				
7	X	X				1 🗁	71			1	
8	X	X				1	72				
9						1	73				
10						1	74				
11						1	75				
12						1	76				
13						1	77				
14							78				
15						1	79				
16						1	80				
17						1	81				
18							82				
19							83				
20							84				
21							85				
22							86				
23							87				
24							88				
25							89				
26							90				
27							91				
28							92				
29							93				
30							94				
31						l L	95				
32						↓ L	96				
33						ŀ L	97				
34						↓ L	98 99				
35						↓	99				
36						↓ L	100				
37						↓	101				
38						ŀ L	102				
39						ŀ L	103				
40						↓ L	104				
41						∤ 	105				
42						ł ⊨	106				
43						↓ 	107				
44	-		1	1	1	∤	108				
45			1	1	1	∤	109				ļ
46	 		1	1	1	∤	110				
47 48	-	1	+	 	 	∤	111 112			1	
48	1		+	 	+	+ ├	112				1
50	-		1	 	 	∤ 	113 114				
5U E1	1		+	 	+	+ ├	114				1
51 52	-		 	 	 	+ ├─	116				-
52	-		1	 	 	∤ 	117				
53 54	-		1	 	 	∤ 	117				
54	-		1	 	 	∤ 	110				
55 56		1	1	 	 	∤ 	119				
56 57		1	1	 	 	∤ 	120				
57	-	1	+	 	 	∤	121			1	
58	 		1	1	1	∤	122				
59 60			1	1	1	∤	123				ļ
60			1	1	1	∤	124				ļ
61	-		1	1	1	∤	125				
62	-		1	1	1	∤	126				ļ
63	-		1	1	1	∤ 	127				
64						1 L	128]		<u> </u>



نگهداشت و افزایش تولید میدان نفتی بینک

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک





MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER

	شماره پیمان:	پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدر ک	سريال	نسخه
۱۸٤ – ۲۲۰ – ۲۵۰		BK	GCS	PEDCO	120	ME	DT	8000	D02

شماره صفحه: ۳ از ۸

General Notes

Rev

- 1. The Asterisk * denotes information and/or confirmation required from VENDOR.
- Deleted
- 3. VENDOR shall include for the services of a independent verification body for mechanical design, stage inspection, testing and stamping of the equipment (if possible).
- 4. Painting and coating (internal & external) shall be as per project 'Specification for Painting', Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0006. and Specification For Lining Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0007 respectively.
- 5. Flanges shall comply with ASME B16.5. Nozzle bolt holes shall straddle the natural centrelines for horizontal nozzles. VENDOR to confirm maximum allowable nozzle loads and moments (RF: Raised Face, WN: Welding Neck)
- 6. All reinforcement pads shall have 1/4" (6mm) tell-tale hole and 1/8" (3mm) vent hole as per Standard Detail Drawing For Pressure Vessels and Heat Exchangers', Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001".
- 7. Manways shall be supplied complete with blind flange, external grab handles, internal grab handle and ladder rungs, nuts, bolting, gasket and proof load test davits. Davits shall be proof load tested on the vessels to 1.5 x Safe Working Load (SWL) and shall be marked accordingly.
- 8. All external bolts and nuts shall be hot dip galvanized. Internal bolts and nuts shall be stainless steel.
- 9. Loads at support base, Shall be calculated and determined by vendor.
- 10. Access Ladder & Platform to be considered.
- 11. Deleted
- 12. All material, corrosion allowance and their suitability for the process fluid at design pressure and temperature to be confirmed by vendor.
- 13. The vendor shall be responsible for mechanical strength of the equipment based on mentioned condition in data sheets.
- 14. All nozzle locations and orientations to be finalized later.
- 15. Instrumentation items are excluded from vendor's scope of supply.
- 16. Any changes in material of construction, location & orientation of the nozzles shall be confirmed by client.
- 17. All materials shall be new and unused.
- 18. Fabrication tolerances for vessel shall be in accordance with requirement of ASME code.
- 19. Location and number of lifting lugs on vessels shall be specificed on VENDOR drawing.
- 20. All items shall be clearly match marked against vessel drawings to facilitate erection.
- 21. Deleted
- 22. Vendor shall supply details of all welding connections and give general specification of used materials.
- 23. For equipment requiring PWHT, final inspection and acceptance by the CLIENT or its nominated representative shall only be undertaken against NDE after PWHT. All weldings shall be made before vessel heat treatment (if any).
- 24. Equipment packaging, preparation for shipment and delivery shall be in accordance with the project Minimum Requirements for Marking, Packing, Shipment & Storage' Document No. IPS-G-GN-210.
- 25. Specified accessories and attachments shall be supplied by vendor.
- 26. Gasket shall be spiral wound type, graphite filled with inner ring and outer ring S.S.316
- 27. Deleted
- 28. Deleted
- 29. Two M12 earthing bosses shall be provided on vessel support. Material of Earthing Bosses shall be S.S. 316



نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض



NISOC

۱۸۶ – ۲۷۰ – ۹۱۸۶

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

خه سریال نوع مدر ک رشته تسهیلات صادر کننده بسته کاری پروژه	MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER									
حه سریال انوع مدر ک رسته نسهیادت اصادر دننده استه کاری پروره	نس									

GCS PEDCO 120 ME DT 0008 D02

شماره صفحه: 2 از ۸

General Notes (Cont'd)

Rev

- 30. For standard detail of Earth lug execution refer to the Project "Standard Detail Drawing For Pressure Vessels and Heat Exchangers Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001".
- 31. Elliptical heads shall be Ultrasonic Tested for LAMINATION after forming.

BK

شماره پیمان:

- 32. The projection of equipment's nozzles should be considered as per 'Standard Detail Drawing For Pressure Vessels and Heat Exchangers',

 Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001". Projection of Horizontal & Vertical nozzles is from tengent line and centerline respectively.
- 33. The elevation of equipment's nozzels should be specified as follows:
 - I. For vertical vessels : from bottom T.L.
 - II. For horizontal vessels : from Left T.L.
- 34. Nozzles and flanges shall be suitably supported and reinforced based on nozzle loads provided in project Specification for Pressure Vessels, Document No. BK-GNRAL-PEDCO-000-ME-SP-0001.
- 35. Prior to sealing the vessel for shipping and storage, the inside surface of the equipment shall be 100% visually inspected. Internal surfaces shall be clean and thoroughly dried. The CLIENT or its nominated representative shall witness the cleanliness of internal surfaces. Flange faces shall be protected by wooden or plastic dummy flanges.
- 36. Minimum requirement for pre-commissioning, commissioning, start up and two years operation and spare parts shall be in accordance with document E&C-QC-SP-1.
- 37 Lifting Lugs / trunnions shall be provided to facilitate a single point lift. If a single point lift cannot be achieved without the use of a lifting beam, then VENDOR shall provide a suitable, certified, lifting beam.
- 38. Design pressure specified is at top of vessels. VENDOR design shell include static head for vessels flooded with specific gravity of the handled liquid.
- 39. VENDOR is to maximize shop fabrication based on the following transportation limits:
 - Maximum weight: 96 tonnes
 - Maximum load per axle: 12 tonnes
 - Maximum length: 50.0 m
 - Maximum width: 5.0 m
 - Maximum height: 5.2 m

For items with dimensions and weights greater than the road capacity specified above, VENDOR may be required to split the package into several components.

- 40. All external attachments directly welded to the pressure part shall be the same material as vessel grade.
- 41. The Vendor shall be fully responsible for the complete mechanical design, preparing calculation book and supply of the vessel.
- 42. All dimensions shown are in mm unless otherwise indicated. All nozzle sizes are in inch.



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض



احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER

نسخه سربال نوع مدرک رشته تسهیلات صادرکننده بسته کاری پروژه شماره پیمان: • ۱۵۳ - ۱۹۱۸ BK GCS PEDCO 120 ME DT 0008 D02

شماره صفحه: ٥ از ٨

Mechanical Data Sheets For Instrument Air Receiver (V-2203) / sheet 1 of 4

ev		DATA S	HEET			Rev		
1		ument Air Receiver		_				
2			Quantity : 1	Set				
3		ure Vessel	Danium Data					
4		Process	Design Data Corrosive / Erosive					
5	Contents Operating Temp. (°C)	65	Liquid Flow (kg/	/h)				
6	Operating Temp. (°C) Operating Press. (barg)	<u>65</u> 8	Vap. Molec. Weight (kg/ki					
8	Gas Flow (kg/h)	8	Liquid Sp. Gravity	11101)				
9	, , ,		Service:		N/A			
10		Mechanica	I Design Data D02		IV/A			
	Design Temp. (°C)	85	Vessel Orientation	Vertical				
	Design Press. (barg)	12.5	LLL	(mm)		D		
	Test Press. (barg)	Per Code & Spec Requirements	Nor. Liquid Vol.	(m ³)		0		
	Internal Vacuum (barg)	-	In. Dia. Of Boots	(mm)				
	In. Dia. of Shell (mm)	1500	Boot Length	(mm)				
	Tan/Tan Dim. (mm)	5000	Boot Head Type	(,	N/A			
17		2:1 elliptical	Corr. Allowance	(mm)				
	Shell Wall Thk. (mm)	*	Joint Efficiency	,/	0.7 (Skirt)/0.85 (Shell) / 1 (Head)			
10	Head Wall Thk. (mm)	* (After forming)	Ambient Temp.	(°C)		Ì		
	Seismic Design	Class D, Code: ASCE 7-10	MDMT	(°C)				
	Wind Design	Speed: 120 Km/hr (Max.), Code: ASCE 7-10	Insulation Required	(0)	-			
22			terials					
	Code	ASME II / ASTM	Nozzle Necks:					
	Shell / Heads	A 516 Gr. 70	Pipes		A 106 Gr.B			
	Heads	A 516 Gr. 70	Plates		A 516 Gr.70			
	Lining / Cladding	Epoxy Coating	Forgings		A 105			
	Skirt (Top / Bottom)	A 516 Gr. 70 / A 283 Gr. C	Flanges		A 105			
	Platform Gratings	Hot Dip Galvanized C.S.	Fittings		A 234 Gr. WPB			
	Gaskets	Note 26	External Bolts		A 193 Gr. B7 (Note 8)			
	Lifting Lugs	A 516 Gr.70 / A 283 Gr. C	External Nuts		A 194 Gr.2H (Note 8)			
31	Reinforcing Pads	A 516 Gr.70	Internal Bolts / Nuts		S.S.			
32		C.S.	Name Plate		S.S. 316			
33	3	REFERENCE STAND	ARDS & DOCUMENTS					
34	Mechanical Design Code		ASME Sec VIII Div 1, IPS-G-ME-150					
	Specification for Pressure	/essels	BK-GNRAL-PEDCO-000-ME-SP-0001					
	Process Basis of Design		BK-GNRAL-PEDCO-000-PR-DB-0001					
	Piping & Instrument Diagra	m (P&ID)	BK-GCS-PEDCO-120-PR-PI-0015					
38	Specification for Painting				-000-PI-SP-0006			
39	Specification for Insulation		BK-GNRAL-PEDCO-000-PI-SP-0019					
40	Specification For Material F	Requirements in Sour service	BK-GNRAL-PEDCO-000-PI-SP-0008					
41								
42			pection Requirements					
43		TPI & Client						
44		In Accordance with BS EN 10204:2004,						
	Hydro Test Medium	Water	Hydro Test Procedure	Ye	s;Per Code & Spec. Requirements			
46		1 1	PT		100%			
47		100 % on Lifting Lug Fillet Welds	UT	Ye	s;Per Code & Spec. Requirements			
48		100 % On T-Joints and Head Join						
		Spot On Shell Longitudinal and	Circumferential Joints Butt-Welds	5,				
49		100 % On Nozzle Neck to Flange	& Fabricated Nozzle Neck Longiti					
50			PT Report		s;Per Code & Spec. Requirements	l		
50 51	RT Report	Yes; Per Code & Spec. Requir.		***	Yes;Per Code & Spec. Requirements			
50 51 52	RT Report MT Report	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir.	UT Report		<u> </u>			
50 51 52 53	RT Report MT Report Fabrication Quality Contro	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer)		Yes	X X			
50 51 52 53 54	RT Report MT Report Fabrication Quality Contro Welding Procedure Review	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer)	UT Report	Yes Yes				
50 51 52 53 54 55	RT Report MT Report Fabrication Quality Contro Welding Procedure Review	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer) v / Approval	UT Report Specification for Painting Doc. No.	Yes Yes BK-GN	IRAL-PEDCO-000-PI-SP-0006			
50 51 52 53 54 55 56	RT Report MT Report Fabrication Quality Contro Welding Procedure Review Surface Preparation & Coa	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer) v / Approval	UT Report	Yes Yes BK-GN	IRAL-PEDCO-000-PI-SP-0006			
50 51 52 53 54 55 56 57	RT Report MT Report Fabrication Quality Contro Welding Procedure Review Surface Preparation & Coa	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer) v / Approval	UT Report Specification for Painting Doc. No.	Yes Yes BK-GN	IRAL-PEDCO-000-PI-SP-0006			
50 51 52 53 54 55 56 57 58	RT Report MT Report Fabrication Quality Contro Welding Procedure Review Surface Preparation & Coa	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer) v / Approval	UT Report Specification for Painting Doc. No.	Yes Yes BK-GN	IRAL-PEDCO-000-PI-SP-0006			
50 51 52 53 54 55 56 57	RT Report MT Report Fabrication Quality Contro Welding Procedure Review Surface Preparation & Coa	Yes; Per Code & Spec. Requir. Yes; Per Code & Spec. Requir. Plan (With Offer) v / Approval	UT Report Specification for Painting Doc. No.	Yes Yes BK-GN	IRAL-PEDCO-000-PI-SP-0006			



NISOC

٤٨١٤ - ٣٧٠ - ٣٥٠

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER





شماره صفحه: ۲ از ۸

Mechanical Dat	ta Sheets For Instru	ment Air Receiver	(V-2203) / sheet 2 of 4

				ACCES				LIST & LC		BASE				
1	_				Acces			chments (/						
2	Supporting	g Saddles	.,			NO		Name Plate						YES
3	Access La		attorm			YES		Name Plate		001				YES
4	Insulation	Support				NO	-+:	Earthing Lu	g (Note	30)				YES YES
5 6	Insulation Insulation	Cover				NO NO		Tailing Lug Cathodic Pr	rotootion	(Coorifi	oial Anada	0)		NO NO
7	Fireproofin		+			NO		Anchor Bolt		(Sacrill	ciai Alloue	3)		NO
8	Lifting Luc		· ·			YES		Instrumenta						NO
9	Internal/ E		ine			YES		Skid	1110115					NO
10	Tamplate	.xterriai Ci	ips			YES		Support Clip	ne					YES
11	Boot					NO		Vortex Brea						NO
12	Davit for N	/lanhole				YES		Rung & Grip						NO
13	Internal Li		ainting)			YES		Heating Coi						NO
14 15 16 17						NI-			D02					
18		I	1		l		LIS	st (Note 1)			Dua: /m	nm) Reinf	oroomoni	. T
19 20	Mark	Qty.	Des	cription	Size	Pipe Thk.	Sch		Flange Rate.	Face	(Note 32			Remarks
20 21	Λ.	1	+	Inlet	2"	IIIK.	SCI	WN	#150	RF	965*) IIIK	. О.Б.	
22	A B	1		Outlet	2"			WN	#150	RF	See DWO	2		+
23	PSV	1		Safety Valve	2"			WN	#150	RF	965*	-	+	1
24	V	1		Vent	2"			WN	#150	RF	See DWO	7		+
25	M	1		ınhole	24"			WN	#150	RF	1170	*	*	Note 7
26	P	1		ire Gauge	2"			WN	#300	RF	965			
27	D	1		Prain	2"			WN	#150	RF	See DWO	\vec{j}		
28	L 1,2	2		l Gauge	2"			WN	#300	RF	965			
29		_						,,,,,						
30			1											1
31			1											
32														
33														
34														
35					1									
36														
37 38 39 40 41 42 43 44 45 46 47 48 49 50	Load Co		Emp Max. Shear @ Base (Kg)	oty Condition Max. Moment @ Base (Kg.m)	Wind an		Oper	ds at Base * rating Condit Max. Moment @ Base (Kg.m)		ht @	Max. Shear D Base (Kg)	Testing C Max. Noment @ Base (Kg.m)		Weight (Kg)
38 39 40 41 42 43 44 45 46 47 48 49 50 51	Load 1	уре	Max. Shear @ Base	Max. Moment @ Base	Weight	Max. Shea @ Base	Oper	Max. Moment @ Base	tion	ht @	Shear O Base	Max. Noment @ Base		
38 39 40 41 42 43 44 45 46 47 48 50 51 52	M. T.	уре	Max. Shear @ Base	Max. Moment @ Base	Weight	Max. Shea @ Base	Oper	Max. Moment @ Base	tion	ht @	Shear O Base	Max. Noment @ Base		
38 39 40 41 42 43 44 45 46 47 48 49 50	Load 1	Type D	Max. Shear @ Base	Max. Moment @ Base	Weight	Max. Shea @ Base	Oper	Max. Moment @ Base	tion	ht @	Shear O Base	Max. Noment @ Base		



نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض

تومه پروارا^ن **HIRGAN** ENERGY



NISOC

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک


MECHANICAL DATA	SHEETS FOR INSTRUMENT A	D DECEIVED

ماره پیمان:	پروژه ش	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدر ک	سر يال	نسخه
·0" - ·Y" - 9118	BK	GCS	PEDCO	120	ME	DT	8000	D02

شماره صفحه: ۱ از ۸

Mechanical Data Sheets For Instrument Air Receiver (V-2203) / sheet 3 of 4

Sketch



Nozzle Orientation will be finalized Later.



٤٨١٤ – ٧٧٠ – ٥١٨٤

شماره پیمان:

نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR INSTRUMENT AIR RECEIVER

 نسخه
 سریال
 نوع مدرک
 رشته
 تسهیلات
 صادرکننده
 بسته کاری
 پروژه

 BK
 GCS
 PEDCO
 120
 ME
 DT
 0008
 D02



شماره صفحه: ۱ از ۱

		Mechan	ical Data Sheets For Instrun	nent Air Receiver	(V-2203) / she	et 4 of 4				
			WE	IGHT					Re	
1 2 3 4		WEIGHT CONTR DATA SHEET SI UNIT *	OL		1/1					
5 6 7 8	Service : Type : No. trains :	Instrument Air Receive	r		Location : Bushehr (Binak Oilfield) Quotation No. : Serial No. :					
11	No. stages : Supplier : Manufacturer :									
12 13 14 15	Model : Note: Information t	o be completed by equip	oment vendor.							
16 17				weight (kg) *						
18 19 20	Fabrication	Erection	Operation	Hydrosta	atic Test	Remo	ovable internal	Ladder & Platform		
21		L								
22 23			WEIGHT AND C	F G DATA RE	QUIRED *					
24 25	CONDITION	WEIGHT ACCURACY %	WEI		Х		NTER OF GRAV	/ITY (mm)		
26 27	Dry	ACCURACT /		9/						
28			<u>'</u>					l		
29 30			S	KETCH						
32 33 34 35 36 37 38 39 40 41		Y	Pag PLAN	е			w			
42 43 44 45 46 47 48 49	1	H Z	ELEVATION				UNDERSIDE OF BASE	: <u> </u>		
50		-				-				
51 52				NOTES						
53 54 55 56	2) Any spreader b	to be load tested and ce eam to be load tested a plan for skid mounted e	ertified. nd certified.		۲.					
57 58 59 60										
61 62 63										