

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک						 		
	MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM								
شماره پیمان: ۰۵۳ - ۰۷۳ - ۹۱۸۴	پروژه BK	بسته کاری GCS	صادرکننده PEDCO	تسهیلات 120	رشته ME	نوع مدرک DT	سریال 0010	نسخه D02	شماره صفحه: ۱ از ۸

طرح نگهداشت و افزایش تولید ۲۷ مخزن

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM

نگهداشت و افزایش تولید میدان نفتی بینک

D02	JUN.2023	IFA	H.Adineh	M.Fakharian	A.M.Mohseni	
D01	SEP.2022	IFA	H.Adineh	M.Fakharian	M.Mehrshad	
D00	DEC.2021	IFC	H.Adineh	M.Fakharian	M.Mehrshad	
Rev.	Date	Purpose of Issue / Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

Class: 1

CLIENT Doc. Number: F0Z-708841

status:

IDC: Inter-Discipline Check

IFC: Issued For Comment

IFA: Issued For Approval

AFD: Approved For Design

AFC: Approved For Construction

AFP: Approved For Purchase

AFQ: Approved For Quotation

IFI: Issued For Information

AB-R: As-Built for CLIENT Review

AB-A: As-Built –Approved



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴



نسخه	سریال	نوع مدرک	رشته	تجهیزات	صادرکننده	بسته کاری	پروژه
D02	0010	DT	ME	120	PEDCO	GCS	BK

شماره صفحه: ۲ از ۸

REVISION RECORD SHEET

Page	D00	D01	D02	D03	D04
1	X	X	X		
2	X	X	X		
3	X	X			
4	X	X			
5	X	X	X		
6	X	X	X		
7	X	X	X		
8	X	X			
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					

Page	D00	D01	D02	D03	D04
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
122					
123					
124					
125					
126					
127					
128					

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض								
	احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM								
شماره پیمان:	پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه	شماره صفحه: ۸ از ۳
۰۵۳ - ۰۷۳ - ۹۱۸۴	BK	GCS	PEDCO	120	ME	DT	0010	D02	

General Notes	
Rev	
	<ol style="list-style-type: none"> The Asterisk * denotes information and/or confirmation required from VENDOR. The Vendor shall be fully responsible for the complete mechanical design and supply of the vessel. The vessel shall be supplied in accordance with project 'Specification for Pressure Vessels', Doc. No. BK-GNRL-PEDCO-000-ME-SP-0001. Nozzles and flanges shall be suitably supported and reinforced based on nozzle loads provided in project Specification for Pressure Vessels, Document No. BK-GNRL-PEDCO-000-ME-SP-0001. VENDOR shall include for the services of an independent verification body for mechanical design, stage inspection, testing and stamping of the equipment (if possible). Access Ladder & Platform to be considered . Painting and coating (internal & external) shall be as per project 'Specification for Painting', Doc. No. BK-GNRL-PEDCO-000-PI-SP-0006 and Specification for Lining (Internal Protection of Equipment by painting), Doc. No. BK-GNRL-PEDCO-000-PI-SP-0007. Flanges shall comply with ANSI B16.5. Nozzle bolt holes shall straddle the natural centerlines. VENDOR to confirm maximum allowable nozzle loads and moments. RF: Raised Face, WN: Welding Neck For equipment requiring PWHT, final inspection and acceptance by the CLIENT or its nominated representative shall only be undertaken against NDE after PWHT. All weldings shall be made before vessel heat treatment (if any). Manways shall be supplied complete with blind flange, external grab handles, internal grab handle and ladder rungs, nuts, bolting, gasket and proof load test davits. Davits shall be proof load tested on the vessels to 1.5 x Safe Working Load (SWL) and shall be marked accordingly. Loads at support base, Shall be calculated and determined by vendor. Location and number of lifting lugs on vessels shall be specified on VENDOR drawing. All external bolts and nuts shall be hot dip galvanized. Internal bolts and nuts shall be stainless steel. All material, corrosion allowance and their suitability for the process fluid at design pressure and temperature to be confirmed by vendor. The vendor shall be responsible for mechanical strength of the equipment based on mentioned condition in data sheets. All nozzle locations and orientations will be finalized later. Instrumentation items are excluded from vendor's scope of supply. Any changes in material of construction, location & orientation of the nozzles shall be confirmed by client. Structural surfaces of stainless steel internals shall be pickled & passivated. All dimensions shown are in mm unless otherwise indicated. All nozzle sizes are in inch. All materials shall be new and unused. Prior to sealing the vessel for shipping and storage, the inside surface of the equipment shall be 100% visually inspected. Internal surfaces shall be clean and thoroughly dried. The CLIENT or its nominated representative shall witness the cleanliness of internal surfaces. Flange faces shall be protected by wooden or plastic dummy flanges. Fabrication tolerances for vessel shall be in accordance with requirement of ASME code. All items shall be clearly match marked against vessel drawings to facilitate erection. The elevation of equipment's nozzels should be specified as follows : I. For vertical vessels : from bottom T.L. II. For horizontal vessels : from Left T.L. Vendor shall supply details of all welding connections and give general specification of used materials. Specified accessories and attachments shall be supplied by vendor. Gasket shall be spiral wound type, graphite filled with inner ring S.S.316 and outer ring C.S. deleted deleted Equipment packaging, preparation for shipment and delivery shall be in accordance with the project Packing, Marking, Transportation Procedure Doc. No. "BK-GNRL-PEDCO-000-QC-PR-0045".



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

پسته کاری

GCS

صادر کننده

PEDCO

تسهیلات

120

رشته

ME

نوع مدرک

DT

سریال

0010

نسخه

D02

شماره صفحه: ۸ از ۴

General Notes (Cont'd)

Rev

30. For standard detail of Earth lug execution refer to the Project "Standard Detail Drawing For Pressure Vessels and Heat Exchangers Doc. No. BK-GNRL-PEDCO-000-ME-DW-0001".
31. Elliptical heads shall be Ultrasonic Tested for lamination after forming.
32. The projection of equipment's nozzles should be considered as per 'Standard Detail Drawing For Pressure Vessels and Heat Exchangers', Doc. No. BK-GNRL-PEDCO-000-ME-DW-0001". Projection of Horizontal & Vertical nozzles is from tangent line and centerline respectively.
33. Deleted
34. All reinforcement pads shall have 1/4" (6mm) tell-tale hole and 1/8" (3mm) vent hole as per Standard Detail Drawing For Pressure Vessels and Heat Exchangers', Doc. No. BK-GNRL-PEDCO-000-ME-DW-0001".
35. Minimum requirement for pre-commissioning, commissioning, start up and two years operation spare parts shall be in accordance with document E&C-QC-SP-1.
36. Nozzle loads shall be in accordance with Specification for Pressure Vessels, Doc. No. BK-GNRL-PEDCO-ME-SP-0001.
37. The material shall be in compliance with NACE MR0175/ISO15156 and Specification for Material Requirements in Sour Service, Doc.No. BK-GNRL-PEDCO-000-PI-SP-0008.
38. Welded carbon and carbon manganese steels for vessel shall comply with the following :
Carbon content shall not exceed 0.23%.
Based on the ladel analysis, below equation shall be satisfied.
 $Ceq. = C + Mn/6 + (Cr + Mo + V)/5 + (Cu + Ni)/15 < 0.42 \%$
39. All carbon steel material shall be fully killed, fine grain treated and supplied in the normalized condition.
40. All nozzles must be vertical or horizontal and not perpendicular or parallel to vessel center line.
41. Lifting Lugs / trunnions shall be provided to facilitate a single point lift. If a single point lift cannot be achieved without the use of a lifting beam, then VENDOR shall provide a suitable, certified, lifting beam.
42. Design pressure specified is at top of vessels. VENDOR design shall include static head for vessels flooded with specific gravity of the handled liquid.
43. VENDOR is to maximize shop fabrication based on the following transportation limits:
- Maximum weight: 96 tonnes
 - Maximum load per axle: 12 tonnes
 - Maximum length: 50.0 m
 - Maximum width: 5.0 m
 - Maximum height: 5.2 m
- For items with dimensions and weights greater than the road capacity specified above, VENDOR may be required to split the package into several components.
44. All external attachments directly welded to the pressure part shall be the same material as vessel grade.



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM



شماره صفحه: ۵ از ۸

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D02	0010	DT	ME	120	PEDCO	GCS	BK

Mech. Data Sheet For Close Drain Drum (V-2202) / sheet 1 of 4

Rev	DATA SHEET	Rev
1	Description : <i>Close Drain Drum</i>	
2	Tag No. : <i>V-2202</i> Quantity : <i>1 Set</i>	
3	Type : <i>Pressure Vessel</i>	
4	Process Design Data	
5	Contents : <i>Hydro-Carbon (HC, H₂O)</i> Corrosive / Erosive : <i>Yes</i>	
6	Operating Temp. (°C) : <i>AMB</i> Liquid Flow (kg/h) : <i>-</i>	
7	Operating Press. (barg) : <i>0.5</i> Vap. Molec. Weight (kg/kmol) : <i>-</i>	
8	Gas Flow (kg/h) : <i>-</i> Liquid Sp. Gravity : <i>0.49-1.0</i>	
9	Liquid Viscosity (cP) : <i>-</i> Lethal: : <i>No</i>	
10	Mechanical Design Data D02	
11	Design Temp. (°C) : <i>85</i> Vessel Orientation : <i>Horizontal</i>	
12	Design Press. (barg) : <i>6</i> HHLL (mm) : <i>2300</i>	
13	Test Press. (barg) : <i>Per Code & Spec. Requirements</i> Nor. Liquid Vol. (m ³) : <i>-</i>	
14	Internal Vacuum (barg) : <i>F.V.</i> In. Dia. Of Boots (mm) : <i>N/A</i>	
15	In. Dia. of Shell (mm) : <i>2600</i> Boot Length (mm) : <i>N/A</i>	
16	Tan/Tan Dim. (mm) : <i>7800</i> Boot Head Type : <i>N.A</i>	
17	Vessel Head Type : <i>2:1 Elliptical (Note 31)</i> Corr. Allowance (mm) : <i>6</i>	
18	Shell Wall Thk. (mm) : <i>*</i> Joint Efficiency : <i>0.85 (Shell) / 1 (Head)</i>	
19	Head Wall Thk. (mm) : <i>(After Forming) *</i> Ambient Temp. (°C) : <i>-</i>	
20	Seismic Design : <i>Site Class: D, Code: ASCE 7-10</i> MDMT (°C) : <i>5</i>	
21	Wind Design : <i>Speed: 120 Km/hr (Max.), Code: ASCE 7-10</i> Insulation Required : <i>-</i>	
22	Materials	
23	Code : <i>ASME II / ASTM</i> Internal Welded Supports : <i>S.S.</i>	
24	Shell : <i>A 516 70N</i> Nozzle Necks : <i>A 106 Gr.B</i>	
25	Heads : <i>A 516 70N</i> Pipes : <i>A 106 Gr.B</i>	
26	Lining : <i>PI (Note 5)</i> Plates : <i>A 516 70N</i>	
27	Saddles : <i>A 283 Gr. C</i> Forgings : <i>A 105N</i>	
28	Wear Plate : <i>A 516 70N</i> Flanges : <i>A 105N</i>	
29	Stiffening Rings : <i>A 516 70N</i> Fittings : <i>A 234 Gr. WPB</i>	
30	Gaskets : <i>Note 26</i> Welded Internals : <i>S.S.</i>	
31	Lifting Lugs : <i>A 516 Gr.70 / A 283 Gr. C</i> External Bolts / Nuts (Note 11) : <i>A 193 Gr. B7 / A 194 Gr. 2H</i>	
32	Reinforcing Pads : <i>A 516 70N</i> Internal Bolts / Nuts (Note 11) : <i>S.S.</i>	
33	Ladder & Platform : <i>C.S.</i> Insulation : <i>-</i>	
34	Gratings : <i>Hot Dip Galvanized C.S.</i> Name Plate : <i>S.S. 316</i>	
35	External Welded Clips : <i>A 516 Gr.70N</i>	
36	REFERENCE STANDARDS & DOCUMENTS	
37	Mechanical Design Code : <i>ASME Sec VIII Div 1, IPS-G-ME-150</i>	
38	Specification for Pressure Vessels : <i>BK-GNRAL-PEDCO-000-ME-SP-0001</i>	
39	Process Basis of Design : <i>BK-GNRAL-PEDCO-000-PR-DB-0001</i>	
40	Piping & Instrument Diagram (P&ID) : <i>BK-GCS-PEDCO-120-PR-PI-0017</i>	
41	Specification for Painting : <i>BK-GNRAL-PEDCO-000-PI-SP-0006</i>	
42	Specification for Insulation : <i>BK-GNRAL-PEDCO-000-PI-SP-0019</i>	
43	Specification For Material Requirements in Sour service : <i>BK-GNRAL-PEDCO-000-PI-SP-0008 (Note 37)</i>	
44	Deleted	
45	Fabrication and Inspection Requirements	
46	Inspection Authority : <i>TPI & Client</i>	
47	Material Certification : <i>In Accordance with BS EN 10204:2004, Type 3.1, Minimum for Pressure Containing and Attachments</i>	
48	Hydro Test Medium : <i>Water</i> Hydro Test Procedure : <i>Yes; Per Code & Spec. Requirements</i>	
49	Post Weld Heat Treatment : <i>Yes</i> PT : <i>100%</i>	
50	MT : <i>100 % on Lifting Lug Fillet Welds</i> UT : <i>Yes; Per Code & Spec. Requirements</i>	
51	RT : <i>100 % On T-Joints and Head Joints Butt-Welds,</i>	
52	<i>Spot On Shell Longitudinal and Circumferential Joints Butt-Welds,</i>	
53	<i>100 % On Nozzle Neck to Flange & Fabricated Nozzle Neck Longitudinal Butt-Welds,</i>	
54	RT Report : <i>Yes; Per Code & Spec. Requir.</i> PT Report : <i>Yes; Per Code & Spec. Requirements</i>	
55	MT Report : <i>Yes; Per Code & Spec. Requir.</i> UT Report : <i>Yes; Per Code & Spec. Requirements</i>	
56	Fabrication Quality Control Plan (With Offer) : <i>Yes</i>	
57	Welding Procedure Review / Approval : <i>Yes</i>	
58	Surface Preparation & Coating : <i>Per Specification for Painting with Doc. No. "BK-GNRAL-PEDCO-PI-SP-0006"</i>	
59	<i>Specification for Linning Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0007</i>	
60		
61		
62		
63		
64		



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادرکننده

PEDCO

تسهیلات

120

رشته

ME

نوع مدرک

DT

سریال

0010

نسخه



D02

شماره صفحه: ۸ از ۷

Mechanical Data Sheets For Close Drain Drum (V-2202) / sheet 3 of 4

D02

Sketch



All Dimensions are in mm.
The close drain drum is located in pit.



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR CLOSE DRAIN DRUM



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تسهیلات

120

رشته

ME

نوع مدرک

DT

سریال

0010

نسخه

D02

شماره صفحه: ۸ از ۸

Mech. Data Sheet For Close Drain Drum (V-2202) / sheet 4 of 4

Rev.	WEIGHT						Rev.
1	WEIGHT CONTROL DATA SHEET SI UNIT *					1/1	
2							
3							
4							
5							
6	Service : <i>Close Drain Drum</i>					Location : <i>Bushehr (Binak Oilfield)</i>	
7	Type :					Quotation No. :	
8	No. trains :					Serial No. :	
9	No. stages :						
10	Supplier :						
11	Manufacturer :						
12	Model :						
13							
14	Note: Information to be completed by equipment vendor.						
15							
16	Total weight (kg) *						
17	Fabrication	Erection	Operation	Hydrostatic Test	Removable internal	Ladder & Platform	
18							
19							
20							
21							
22							
23	WEIGHT AND C OF G DATA REQUIRED *						
24	CONDITION	WEIGHT ACCURACY %	WEIGHT (kg)	CENTER OF GRAVITY (mm)			
25				X	Y	Z	
26	Dry						
27							
28							
29							
30	SKETCH						
31							
32							
33							
34							
35							
36							
37							
38							
39							
40							
41							
42							
43							
44							
45							
46							
47							
48							
49							
50							
51							
52	NOTES						
53	1) All lifting points to be load tested and certified.						
54	2) Any spreader beam to be load tested and certified.						
55	3) Lifting / rigging plan for skid mounted equipment to be provided by the Vendor.						
56							
57							
58							
59							
60							
61							
62							
63							