



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سرنال

0009

نسخه

D02

شماره صفحه: ۱ از ۳۳

طرح نگهداشت و افزایش تولید 27 مخزن

DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

نگهداشت و افزایش تولید میدان نفتی بینک

D02	SEP.2023	AFC	P.Hajisadeghi	M.Fakharian	A.M.Mohseni	
D01	OCT.2022	IFA	P.Hajisadeghi	M.Fakharian	M.Mehrshad	
D00	MAY.2022	IFC	P.Hajisadeghi	M.Fakharian	M.Mehrshad	
Rev.	Date	Purpose of Issue / Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

Class: 1

CLIENT Doc. Number: F9Z-708930

status:

IDC: Inter-Discipline Check

IFC: Issued For Comment

IFA: Issued For Approval

AFD: Approved For Design

AFC: Approved For Construction

AFP: Approved For PURCHASE (will be finalized later)

AFQ: Approved For Quotation

IFI: Issued For Information

AB-R: As-Built for CLIENT Review

AB-A: As-Built -Approved



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادرکننده

PEDCO

تسهیلات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲ از ۳۳

REVISION RECORD SHEET

Page	D00	D01	D02	D03	D04
1	X	X	X		
2	X	X	X		
3	X	X	X		
4	X	X	X		
5	X	X	X		
6	X	X	X		
7	X	X	X		
8	X	X	X		
9	X	X	X		
10	X	X	X		
11	X	X	X		
12	X	X	X		
13	X	X	X		
14	X	X	X		
15	X	X	X		
16	X	X	X		
17	X	X	X		
18	X	X	X		
19	X	X	X		
20	X	X	X		
21	X	X	X		
22	X	X	X		
23	X	X	X		
24	X	X	X		
25	X	X	X		
26	X	X	X		
27	X	X	X		
28	X	X	X		
29	X	X	X		
30	X	X	X		
31	X	X	X		
32	X	X	X		
33	X	X	X		
34	X	X			
35	X	X			
36	X	X			
37	X	X			
38		X			
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					

Page	D00	D01	D02	D03	D04
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
122					
123					
124					
125					
126					
127					
128					



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادرکننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۳ از ۳۳

REFERENCE DOCUMENTS :

D02

Specification For Instrumentation

Process Basis Of Design

Specification For Painting

Piping Material Specification

Specification For Pressure Safety Valves (PSV)

Instrument & Control System Design Criteria

Symbol & Legend For PFD and P&ID

P&ID - Gas Compression Inlet Gas Pipeline (Binak)

P&ID - Gas Compression Inlet Gas Pipeline (Golkhari)

P&ID - Slug Catcher System

P&ID - Gas Compression Inlet Knock Out Drum

P&ID - 1st Stage Gas Compression Suction Drums

P&ID - 1st Stage Gas Compression Compressors

P&ID - 1st Stage Gas Compression Air Coolers

P&ID - 2nd Stage Gas Compression Suction Drums

P&ID - 2nd Stage Gas Compression Compressors

P&ID - 2nd Stage Gas Compression Air Coolers

P&ID - 2nd Stage Gas Compression Discharge Drum

P&ID - Gas Compression Dehydration Package

P&ID - Lean Glycol Storage Tank

P&ID - Instrument & Plant Air System

P&ID - Nitrogen Generation System

P&ID - Close Drain System

P&ID - Corrosion Inhibitor Package

P&ID - Methanol Injection Package

P&ID - LP Flare System

P&ID - Oily Water Sewer

P&ID - Fuel Gas System

P&ID - Diesel Oil System

P&ID - Potable Water System

P&ID - Glycol Sump Drum

P&ID - Fire Water Network

P&ID - Total Flooding System For Extension of Existing Elect. Building

BK-GNRL-PEDCO-000-IN-SP-0001_D04

BK-GNRL-PEDCO-000-PR-DB-0001_D08

BK-GNRL-PEDCO-000-PI-SP-0006

BK-GCS-PEDCO-120-PI-SP-0001_D02

BK-GNRL-PEDCO-000-IN-SP-0007_D04

BK-GCS-PEDCO-120-IN-DC-0002_D01

BK-GCS-PEDCO-120-PR-PI-0001_D04

BK-GCS-PEDCO-120-PR-PI-0002_D06

BK-GCS-PEDCO-120-PR-PI-0003_D06

BK-GCS-PEDCO-120-PR-PI-0004_D06

BK-GCS-PEDCO-120-PR-PI-0005_D06

BK-GCS-PEDCO-120-PR-PI-0006_D06

BK-GCS-PEDCO-120-PR-PI-0007_D06

BK-GCS-PEDCO-120-PR-PI-0008_D06

BK-GCS-PEDCO-120-PR-PI-0009_D06

BK-GCS-PEDCO-120-PR-PI-0010_D05

BK-GCS-PEDCO-120-PR-PI-0011_D06

BK-GCS-PEDCO-120-PR-PI-0012_D06

BK-GCS-PEDCO-120-PR-PI-0013_D06

BK-GCS-PEDCO-120-PR-PI-0014_D06

BK-GCS-PEDCO-120-PR-PI-0015_D06

BK-GCS-PEDCO-120-PR-PI-0016_D06

BK-GCS-PEDCO-120-PR-PI-0017_D06

BK-GCS-PEDCO-120-PR-PI-0018_D06

BK-GCS-PEDCO-120-PR-PI-0019_D06

BK-GCS-PEDCO-120-PR-PI-0020_D06

BK-GCS-PEDCO-120-PR-PI-0021_D05

BK-GCS-PEDCO-120-PR-PI-0022_D06

BK-GCS-PEDCO-120-PR-PI-0023_D06

BK-GCS-PEDCO-120-PR-PI-0024_D06

BK-GCS-PEDCO-120-PR-PI-0025_D06

BK-GCS-PEDCO-120-SA-PI-0001_D04

BK-GCS-PEDCO-120-SA-PI-0002_D02



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

نسخه	سریال	نوع مدرک	رشته	تمهيلات	صادرکننده	بسته کاری	پروژه	شماره پیمان:
D02	0009	DT	IN	120	PEDCO	GCS	BK	۰۵۳ - ۰۷۳ - ۹۱۸۴

شماره صفحه: ۴ از ۳۳

GENERAL NOTES:

1- All valves shall be clearly and permanently marked. The name plate shall be corrosion resistant Stainless Steel and pinned to the valve body. Wired on labels are not acceptable. Following information shall be submitted on nameplate for approval.

- Tag number
- Manufacturer name, model and serial number
- Set Pressure
- Pressure rating
- Body size and material
- Measurement Range
- Liquid density
- Degree of protection & electrical construction
- Marking as per IEC Codes
- Well name

2- Calculation sheet using API RP-520 formula shall be provided by vendor for each safety/relief valve in accordance with process values.

3- All wetted part material shall be in accordance with ISO 15156-2 region 2 or NACE MR-01-75 as specified in data sheets for each tag . For these mentioned tags, both the compliance shall be provided.primary and secondary sides of valves shall meet NACE MR-01-75 requirements and certificate of

4- The safety/ relief valves shall comply with API RP 520, 521, 526 and 527 standards. All valves shall be supplied with ASME section VIII.

5- All valves shall be tested for leakage at the manufacturer's works in accordance with API 527. The procedures for these tests shall be submitted for approval.

6- Gasket material shall be suitable for the application.

7-The inlet/outlet sizes & rating and center to flange face dimensions for all valves shall be in accordance with API-526.

8- All the valves with the materials offered shall meet the set pressure and other design conditions for the orifice selected.

9-Vendor to advise all wetted parts materials include disc holder, stem guide, blowdown ring, ring pin, bushing and other internal components in contact with process fluid in bid stage

10 - Environmental condition for field instrumentation of Binak Oilfield shall be considered as per the followings:

Maximum ambient temperature: 50 (°C)
Minimum ambient temperature: 5 (°C)
Maximum steel surface exposed to sun: 85 (°C)
Maximum summer dry bulb: 50 (°C)
DB/RH for Summer HVAC Design: 41 °C / 61 %
DB for Winter HVAC Design: 6 °C

Relative Humidity:

- Maximum Design relative humidity (%): 100
- Minimum Design relative humidity (%): 0

11 - Material Test Certificate and calibration Certificate for all transmitters to be submitted by Vendor.

12- Body and other pressure parts subject to inlet pressure (primary pressure zone) shall be hydrostatically tested at a pressure of at least 1.5 times the design pressure of the parts

13- Safety relief valves shall be subject to a seat leakage test in accordance with API standard 527 as applicable, or as agreed upon by the manufacturer and the CLINET

14- Lifting lever shall be provided whenever the fluid to be relieved, is steam, air, or hot water (60°C and above)

15- Balanced bellows valves shall have open bonnet construction.

16- In valves with balancing bellow, the bonnet shall have a ½" threaded hole, NPT as per ANSI 1.20.1.

17- In bellows type, bonnet shall be vented separately from discharge.

18- Body color of Pressure & Safety Relief Valves shall be yellow. For more details referto the latest revision of Specification For Painting Doc No.

"BK-GNRAL-PEDCO-000-PI-SP-0006"



D02



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۵ از ۳۳

PRESSURE SAFETY VALVE

PRESSURE SAFETY VALVE						
GENERAL	1	Tag Number		PSV-2111		D02
	2	Service		GAS		
	3	Line No.	Vessel No.	GAS-111-0013-AN07-2"-PT	V-2104	
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm	BK-GCS-PEDCO-120-PR-PI-0004-D06 (1 of 2)	
	5	Discharge to		To LP FLARE HEADER		
	6	Protect Equipment		-		
	7	Area Clacification		Zone 2, IIB T4		
	8	NACE MR0175/ISO 15156 Compliance		YES		
BASIS	9	Nozzle (Full, Semi)		Full Nozzle		
	10	Design Type	Safety, Relief, Safety-Relief	Safety		
	Conventional, bellows, Pilot Op.		Bellows			
	12	Bonnet Type		Closed		
PROCESS CONDITIONS	13	Fluid	State	GAS	Singel Phase	
	14	Required Capacity		37247.20	kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	48.1 kg/kmol	1.659 kg/m3	
	16	Oper. Pressure	Set Pressure	5.3 /	9 bar-g	
	17	Oper. Temperature	RelievingTemp.	32 /	284 °C	
	18	Back Pressure	Constant	-	bar-g	
	19		Variable	3.4	bar-g	
	20		Total	3.4	bar-g	
	21	% Allowable Overpressure		21%		
	22	Over Pressure Factor		1.21		
	23	Compressibility Factor(Z)		0.95		
	24	Latent Heat of Vaporization (Kj/Kg)		431.6		
	25	Ratio of Specific Heats(Cp/Cv)		1.223		
	26	Density @ flowing temprature		12.837 kg/m3		
	27	Operating Viscosity		0.015 cP		
	28	Barometric Pressure		13.26 ~ 14.37 psia		
SELECTION	29	Design Code	Sizing Basis	API 520	-	
	30	Construction Code		API 520		
	31	Fire		YES		
	32	Basis of Selection		FIRE		
	33	Calculated Area	MM²	4134(VTC)		
	34	Required Area	MM²	8742 (VTC)		
	35	Orifice Designation		Q (VTC)		
CONNECTIONS	36	Size: Inlet	Outlet	6" in	8" in	
	37	Rating & Facing :In	Outlet	#300 FLANGED RF	#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)		
	39	Seat and Disc (Trim)		SS316+PTFE (VTC)		
	40	Nozzle		SS316 (VTC)		
	41	Guide and Rings		VTA		
	42	Spring		ASTM A216 GR. WCB (VTC)(Note2)		
	43	Bellows		SS316+PTFE (VTC)		
	44					
OPTIONS	45	Cap: Screwed or Bolted		Screwed		
	46	Lever: Plain or Packed		N/A		
	47	Test Gage		Yes		
	48	With Rupture Disc		No		
	49	Hydro Test		Required		
	50	Seat Leakage Test		Required		
	51	Compliance Standard		N/A		
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later		
	53	Model		Will Be Finalized Later		
	54	Serial No.		Will Be Finalized Later		

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۶ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2112				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0014-AN07-2"-PT		V-2104		
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm		BK-GCS-PEDCO-120-PR-PI-0004-D06 (1 of 2)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Bellows				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		37247.20		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	48.1 kg/kmol		1.659 kg/m3		
	16	Oper. Pressure	Set Pressure	5.3 /		9 bar-g		
	17	Oper. Temperature	RelievingTemp.	32 /		284 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	3.4		bar-g		
	20		Total	3.4		bar-g		
	21	% Allowable Overpressure		21%				
	22	Over Pressure Factor		1.21				
	23	Compressibility Factor(Z)		0.95				
	24	Latent Heat of Vaporization (KJ/Kg)		431.6				
	25	Ratio of Specific Heats(Cp/Cv)		1.223				
	26	Density @ flowing temprature		12.837 kg/m3				
	27	Operating Viscosity		0.015 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		YES				
	32	Basis of Selection		FIRE				
	33	Calculated Area	MM²	4134(VTC)				
	34	Required Area	MM²	8742 (VTC)				
	35	Orifice Designation		Q (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	6" in		8" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+PTFE (VTC)				
	40	Nozzle		SS316 (VTC)				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		SS316+PTFE (VTC)				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۷ از ۳۳

PRESSURE SAFETY VALVE

PRESSURE SAFETY VALVE						
GENERAL	1	Tag Number		PSV-2113		D02
	2	Service		GAS		
	3	Line No.	Vessel No.	GAS-111-0021-AN07-2"-PT		
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm	BK-GCS-PEDCO-120-PR-PI-0005_D06	
	5	Discharge to		To FLARE		
	6	Protect Equipment		-		
	7	Area Clacification		Zone 2, IIB T4		
	8	NACE MR0175/ISO 15156 Compliance		Yes		
BASIS	9	Nozzle (Full, Semi)		Full Nozzle		
	10	Design Type	Safety, Relief, Safety-Relief	Safety		
	11		Conventional, bellows, Pilot Op.	Bellows		
	12	Bonnet Type		Closed		
PROCESS CONDITIONS	13	Fluid	State	GAS	Singel Phase	
	14	Required Capacity		17833.1	kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol	0.846 kg/m3	
	16	Oper. Pressure	Set Pressure	5.1 /	9 bar-g	
	17	Oper. Temperature	RelievingTemp.	36.92 /	36.92 °C	
	18	Back Pressure	Constant	-	bar-g	
	19		Variable	1.2	bar-g	
	20		Total	1.2	bar-g	
	21	% Allowable Overpressure		10%		
	22	Over Pressure Factor		1.10		
	23	Compressibility Factor(Z)		0.954		
	24	Latent Heat of Vaporization (Kj/Kg)		1994.0		
	25	Ratio of Specific Heats(Cp/Cv)		1.246		
	26	Density @ flowing temprature		11.981 kg/m3		
	27	Operating Viscosity		0.012 cP		
	28	Barometric Pressure		13.26 ~ 14.37 psia		
SELECTION	29	Design Code	Sizing Basis	API 520	-	
	30	Construction Code		API 520		
	31	Fire		NO		
	32	Basis of Selection		Blocked Outlet		
	33	Calculated Area	MM²	2240.6 (VTC)		
	34	Required Area	MM²	3421 (VTC)		
	35	Orifice Designation		N (VTC)		
CONNECTIONS	36	Size: Inlet	Outlet	4" in	6" in	
	37	Rating & Facing :In	Outlet	#300 FLANGED RF	#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)		
	39	Seat and Disc		SS316+PTFE (VTC)		
	40	Nozzle		SS316 (VTC)		
	41	Guide and Rings		VTA		
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)		
	43	Bellows		SS316+PTFE (VTC)		
	44					
OPTIONS	45	Cap: Screwed or Bolted		Screwed		
	46	Lever: Plain or Packed		N/A		
	47	Test Gage		Yes		
	48	With Rupture Disc		No		
	49	Hydro Test		Required		
	50	Seat Leakage Test		Required		
	51	Compliance Standard		N/A		
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later		
	53	Model		Will Be Finalized Later		
	54	Serial No.		Will Be Finalized Later		

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۸ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2114				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0022-AN07-2"-PT		V-2105		
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm		BK-GCS-PEDCO-120-PR-PI-0005_D06		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		Yes				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Bellows				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		17833.1		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.846 kg/m3		
	16	Oper. Pressure	Set Pressure	5.1 / 9		bar-g		
	17	Oper. Temperature	RelievingTemp.	36.92 / 36.92		°C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	1.2		bar-g		
	20		Total	1.2		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.954				
	24	Latent Heat of Vaporization (KJ/Kg)		1994.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.246				
	26	Density @ flowing temprature		11.981 kg/m3				
	27	Operating Viscosity		0.012 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	2240.6 (VTC)				
	34	Required Area	MM²	3421 (VTC)				
	35	Orifice Designation		N (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	4" in		6" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+PTFE (VTC)				
	40	Nozzle		SS316 (VTC)				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		SS316+PTFE (VTC)				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۹ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2121A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0029A-AN07-2"-PT		V-2101A		
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm		BK-GCS-PEDCO-120-PR-PI-0006_D06 (1 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Bellows				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		2166.00		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.55 kg/kmol		0.847 kg/m3		
	16	Oper. Pressure	Set Pressure	4.9 / 9		bar-g		
	17	Oper. Temperature	RelievingTemp.	36.78 / 60		°C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.5		bar-g		
	20		Total	0.5		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.822				
	24	Latent Heat of Vaporization (KJ/Kg)		1827.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.457				
	26	Density @ flowing temprature		24.192 kg/m3				
27	Operating Viscosity		0.013 cP					
28	Barometric Pressure		13.26 ~ 14.37 psia					
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		YES				
	32	Basis of Selection		Control Valve Failiure				
	33	Calculated Area	MM²	107.25 (VTC)				
	34	Required Area	MM²	153.938 (VTC)				
	35	Orifice Designation		E (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1" in		2" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+PTFE (VTC)				
	40	Nozzle		SS316 (VTC)				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		SS316+PTFE (VTC)				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

بوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۰ از ۳۳

PRESSURE SAFETY VALVE

D02

GENERAL

1	Tag Number	PSV-2121B
2	Service	GAS
3	Line No.	Vessel No.
4	Pipe Class / C.A.	P&ID No.
5	Discharge to	AN07 / 6mm
6	Protect Equipment	To FLARE
7	Area Clacification	-
8	NACE MR0175/ISO 15156 Compliance	Zone 2, IIB T4
9	Nozzle (Full, Semi)	YES

BASIS

10	Design Type	Safety, Relief, Safety-Relief
11	Conventional, bellows, Pilot Op.	Safety
12	Bonnet Type	Bellows
13	Fluid	Closed

PROCESS CONDITIONS

14	Required Capacity	GAS
15	Molecular Mass	2166.00
16	Oper. Pressure	kg/h
17	Oper. Temperature	24.55
18	Back Pressure	kg/mol
19	Total	0.847
20	% Allowable Overpressure	10%
21	Over Pressure Factor	1.10
22	Compressibility Factor(Z)	0.822
23	Latent Heat of Vaporization (Kj/Kg)	1827.0
24	Ratio of Specific Heats(Cp/Cv)	1.457
25	Density @ flowing temprature	24.192
26	Operating Viscosity	0.013
27	Barometric Pressure	13.26 ~ 14.37

SELECTION

28	Design Code	API 520
29	Construction Code	API 520
30	Fire	YES
31	Basis of Selection	Control Valve Failure
32	Calculated Area	107.25 (VTC)
33	Required Area	153.938 (VTC)
34	Orifice Designation	E (VTC)

CONNECTIONS

35	Size: Inlet	Outlet
36	Rating & Facing :In	Outlet

MATERIALS (VTC)

37	Body and Bonnet	ASTM A216 GR. WCB (VTC)
38	Seat and Disc	SS316+PTFE (VTC)
39	Nozzle	SS316 (VTC)
40	Guide and Rings	SS316 (VTC)
41	Spring	ASTM A216 GR. WCB (VTC) (Note2)
42	Bellows	SS316+PTFE (VTC)

OPTIONS

43	Cap: Screwed or Bolted	Screwed
44	Lever: Plain or Packed	N/A
45	Test Gage	Yes
46	With Rupture Disc	No
47	Hydro Test	Required
48	Seat Leakage Test	Required
49	Compliance Standard	N/A

PURCHASE (will be finalized later)

50	Manufacturer	Will Be Finalized Later
51	Model	Will Be Finalized Later
52	Serial No.	Will Be Finalized Later

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

بوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۱ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2121C				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0029C-AN07-2"-PT		V-2101C		
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm		BK-GCS-PEDCO-120-PR-PI-0006_D06 (3 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Bellows				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		2166.00		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.55	kg/kmol	0.847	kg/m3	
	16	Oper. Pressure	Set Pressure	4.9	/	9	bar-g	
	17	Oper. Temperature	Relieving Temp.	36.78	/	60	°C	
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.5		bar-g		
	20		Total	0.5		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.822				
	24	Latent Heat of Vaporization (Kj/Kg)		1827.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.457				
	26	Density @ flowing temprature		24.192	kg/m3			
	27	Operating Viscosity		0.013	cP			
	28	Barometric Pressure		13.26 ~ 14.37	psia			
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		YES				
	32	Basis of Selection		Control Valve Faiilure				
	33	Calculated Area	MM²	107.25 (VTC)				
	34	Required Area	MM²	153.938 (VTC)				
	35	Orifice Designation		E (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1" in		2" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+PTFE (VTC)				
	40	Nozzle		SS316 (VTC)				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		SS316+PTFE (VTC)				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۲ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2122A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0032A-CN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0007_D06 (1 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		8664.0		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	19 / 22		bar-g		
	17	Oper. Temperature	RelievingTemp.	124.8 / 124.8		°C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.9		bar-g		
	20		Total	0.9		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.964				
	24	Latent Heat of Vaporization (KJ/Kg)		693.3				
	25	Ratio of Specific Heats(Cp/Cv)		1.225				
	26	Density @ flowing temprature		19.56 kg/m3				
	27	Operating Viscosity		0.015 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	539.85 (VTC)				
	34	Required Area	MM²	1017(VTC)				
	35	Orifice Designation		J (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۳ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2122B				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0032B-CN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0007_D06 (2 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		8664.0		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	19 /		22 bar-g		
	17	Oper. Temperature	RelievingTemp.	124.8 /		124.8 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.9		bar-g		
	20		Total	0.9		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.964				
	24	Latent Heat of Vaporization (KJ/Kg)		693.3				
	25	Ratio of Specific Heats(Cp/Cv)		1.225				
	26	Density @ flowing temprature		19.56 kg/m3				
	27	Operating Viscosity		0.015 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	539.85 (VTC)				
	34	Required Area	MM²	1017(VTC)				
	35	Orifice Designation		J (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۴ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2122C			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0032C-CN05-2"-PT		-	
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0007_D06 (3 OF 3)	
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase	
	14	Required Capacity		8664.0		kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3	
	16	Oper. Pressure	Set Pressure	19 / 22		bar-g	
	17	Oper. Temperature	RelievingTemp.	124.8 / 124.8		°C	
	18	Back Pressure	Constant	-		bar-g	
	19		Variable	0.9		bar-g	
	20		Total	0.9		bar-g	
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.964			
	24	Latent Heat of Vaporization (KJ/Kg)		693.3			
	25	Ratio of Specific Heats(Cp/Cv)		1.225			
	26	Density @ flowing temprature		19.56 kg/m3			
	27	Operating Viscosity		0.015 cP			
	28	Barometric Pressure		13.26 ~ 14.37 psia			
SELECTION	29	Design Code	Sizing Basis	API 520		-	
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	539.85 (VTC)			
	34	Required Area	MM²	1017(VTC)			
	35	Orifice Designation		J (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in	
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
	44						
OPTIONS	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
	51	Compliance Standard		N/A			
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۵ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2123A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0033A-CN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0007_D06 (1 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		8664.0		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	19 /		22 bar-g		
	17	Oper. Temperature	RelievingTemp.	124.8 /		124.8 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.9		bar-g		
	20		Total	0.9		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.964				
	24	Latent Heat of Vaporization (KJ/Kg)		693.3				
	25	Ratio of Specific Heats(Cp/Cv)		1.225				
	26	Density @ flowing temprature		19.56 kg/m3				
	27	Operating Viscosity		0.015 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	539.85 (VTC)				
	34	Required Area	MM²	1017(VTC)				
	35	Orifice Designation		J (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک						 		
	DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES								
شماره پیمان:		پروژه	بسته کاری	صادرکننده	تجهیزات	رشته	نوع مدرک	سریال	نسخه
۰۵۳ - ۰۷۳ - ۹۱۸۴		BK	GCS	PEDCO	120	IN	DT	0009	D02
شماره صفحه: ۱۶ از ۳۳									

PRESSURE SAFETY VALVE									
GENERAL	1	Tag Number			PSV-2123B				
	2	Service			GAS				
	3	Line No.	Vessel No.		GAS-111-0033B-CN05-2"-PT			-	
	4	Pipe Class / C.A.	P&ID No.		CN05 / 3mm			BK-GCS-PEDCO-120-PR-PI-0007_D06 (2 OF 3)	
	5	Discharge to			To FLARE				
	6	Protect Equipment			-				
	7	Area Classification			Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance			YES				
BASIS	9	Nozzle (Full, Semi)			Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief		Safety				
	Conventional, bellows, Pilot Op.		Conventional						
	12	Bonnet Type			Closed				
PROCESS CONDITIONS	13	Fluid	State		GAS			Singel Phase	
	14	Required Capacity			8664.0			kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp		24.52 kg/kmol			0.85 kg/m3	
	16	Oper. Pressure	Set Pressure		19 / 22			bar-g	
	17	Oper. Temperature	Relieving Temp.		124.8 / 124.8			°C	
	18	Back Pressure	Constant		-			bar-g	
	Variable		0.9			bar-g			
	Total		0.9			bar-g			
	21	% Allowable Overpressure			10%				
	22	Over Pressure Factor			1.10				
	23	Compressibility Factor(Z)			0.964				
	24	Latent Heat of Vaporization (Kj/Kg)			693.3				
	25	Ratio of Specific Heats(Cp/Cv)			1.225				
	26	Density @ flowing temprature			19.56			kg/m3	
	27	Operating Viscosity			0.015			cP	
	28	Barometric Pressure			13.26 ~ 14.37			psia	
SELECTION	29	Design Code	Sizing Basis		API 520			-	
	30	Construction Code			API 520				
	31	Fire			NO				
	32	Basis of Selection			Blocked Outlet				
	33	Calculated Area	MM²		539.85 (VTC)				
	34	Required Area	MM²		1017(VTC)				
	35	Orifice Designation			J (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet		2" in			3" in	
	37	Rating & Facing :In	Outlet		#300 FLANGEDRF			#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet			ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc			SS316+RPTFE				
	40	Nozzle			316 SS				
	41	Guide and Rings			VTA				
	42	Spring			ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows			N/A				
	44								
OPTIONS	45	Cap: Screwed or Bolted			Screwed				
	46	Lever: Plain or Packed			N/A				
	47	Test Gage			Yes				
	48	With Rupture Disc			No				
	49	Hydro Test			Required				
	50	Seat Leakage Test			Required				
	51	Compliance Standard			N/A				
PURCHASE (will be finalized later)	52	Manufacturer			Will Be Finalized Later				
	53	Model			Will Be Finalized Later				
	54	Serial No.			Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage VTC : Vendor to confirm in bidding stage N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۱۷ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2123C			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0033C-CN05-2"-PT		-	
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0007_D06 (3 OF 3)	
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase	
	14	Required Capacity		8664.0		kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3	
	16	Oper. Pressure	Set Pressure	19 / 22		bar-g	
	17	Oper. Temperature	RelievingTemp.	124.8 / 124.8		°C	
	18	Back Pressure	Constant	-		bar-g	
	19		Variable	0.9		bar-g	
	20		Total	0.9		bar-g	
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.964			
	24	Latent Heat of Vaporization (KJ/Kg)		693.3			
	25	Ratio of Specific Heats(Cp/Cv)		1.225			
	26	Density @ flowing temprature		19.56 kg/m3			
	27	Operating Viscosity		0.015 cP			
	28	Barometric Pressure		13.26 ~ 14.37 psia			
SELECTION	29	Design Code	Sizing Basis	API 520		-	
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	539.85 (VTC)			
	34	Required Area	MM²	1017(VTC)			
	35	Orifice Designation		J (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in	
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
	44						
OPTIONS	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
	51	Compliance Standard		N/A			
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)

 NISOC	نگهداشت و افزایش تولید میدان نفتی بینک سطح الارضی احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک						 		
	DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES								
شماره پیمان:	پروژه	بسته کاری	صادر کننده	تهیهات	رشته	نوع مدرک	سریال	نسخه	شماره صفحه: ۱۸ از ۳۳
۰۵۳ - ۰۷۳ - ۹۱۸۴	BK	GCS	PEDCO	120	IN	DT	0009	D02	

PRESSURE SAFETY VALVE										
GENERAL	1	Tag Number			PSV-2131A					
	2	Service			GAS					
	3	Line No.	Vessel No.		GAS-111-0042A-CN05-2"-PT		-			
	4	Pipe Class / C.A.	P&ID No.		CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0009_D06 (1 OF 3)			
	5	Discharge to			To FLARE					
	6	Protect Equipment			-					
	7	Area Clacification			Zone 2, IIB T4					
	8	NACE MR0175/ISO 15156 Compliance			YES					
BASIS	9	Nozzle (Full, Semi)			Full Nozzle					
	10	Design Type	Safety, Relief, Safety-Relief		Safety					
	11		Conventional, bellows, Pilot Op.		Bellows					
	12	Bonnet Type			Closed					
PROCESS CONDITIONS	13	Fluid	State		GAS			Singel Phase		
	14	Required Capacity			982.27			kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp		24.52 kg/kmol			0.85 kg/m3		
	16	Oper. Pressure	Set Pressure		18.1 /			22 bar-g		
	17	Oper. Temperature	RelievingTemp.		60 /			208 °C		
	18	Back Pressure	Constant		-			bar-g		
	19		Variable		3.4			bar-g		
	20		Total		3.4			bar-g		
	21	% Allowable Overpressure			21%					
	22	Over Pressure Factor			1.21					
	23	Compressibility Factor(Z)			0.936					
	24	Latent Heat of Vaporization (Kj/Kg)			1807.0					
	25	Ratio of Specific Heats(Cp/Cv)			1.278					
	26	Density @ flowing temprature			17.34 kg/m3					
	27	Operating Viscosity			0.017 cP					
	28	Barometric Pressure			13.26 ~ 14.37 psia					
SELECTION	29	Design Code	Sizing Basis		API 520			-		
	30	Construction Code			API 520					
	31	Fire			YES					
	32	Basis of Selection			FIRE					
	33	Calculated Area	MM²		59.62 (VTC)					
	34	Required Area	MM²		153.93 (VTC)					
	35	Orifice Designation			D (VTC)					
CONNECTIONS	36	Size: Inlet	Outlet		1" in			2" in		
	37	Rating & Facing :In	Outlet		#300 FLANGED RF			#300 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet			ASTM A216 GR. WCB (VTC)					
	39	Seat and Disc			SS316+RPTFE					
	40	Nozzle			316 SS					
	41	Guide and Rings			VTA					
	42	Spring			ASTM A216 GR. WCB (VTC) (Note2)					
	43	Bellows			SS316+PTFE (VTC)					
	44									
OPTIONS	45	Cap: Screwed or Bolted			Screwed					
	46	Lever: Plain or Packed			N/A					
	47	Test Gage			Yes					
	48	With Rupture Disc			No					
	49	Hydro Test			Required					
	50	Seat Leakage Test			Required					
	51	Compliance Standard			N/A					
PURCHASE (will be finalized later)	52	Manufacturer			Will Be Finalized Later					
	53	Model			Will Be Finalized Later					
	54	Serial No.			Will Be Finalized Later					

Notes: ☐ VTA : Vendor to Advise in bidding stage VTC : Vendor to confirm in bidding stage N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادر کننده	بسته کاری	پروژه
D02	0009	DT	IN	120	PEDCO	GCS	BK

شماره صفحه: ۱۹ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number	PSV-2131B	
	2	Service	GAS	
	3	Line No.	Vessel No.	GAS-111-0042B-CN05-2"-PT
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm
	5	Discharge to	To FLARE	
	6	Protect Equipment	-	
	7	Area Classification	Zone 2, IIB T4	
	8	NACE MR0175/ISO 15156 Compliance	YES	
BASIS	9	Nozzle (Full, Semi)	Full Nozzle	
	10	Design Type	Safety, Relief, Safety-Relief	Safety
	11		Conventional, bellows, Pilot Op.	Bellows
	12	Bonnet Type	Closed	
PROCESS CONDITIONS	13	Fluid	State	GAS
	14	Required Capacity	982.27	kg/h
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol
	16	Oper. Pressure	Set Pressure	18.1 / 22 bar-g
	17	Oper. Temperature	Relieving Temp.	60 / 208 °C
	18	Back Pressure	Constant	- bar-g
	19		Variable	3.4 bar-g
	20		Total	3.4 bar-g
	21	% Allowable Overpressure	21%	
	22	Over Pressure Factor	1.21	
	23	Compressibility Factor(Z)	0.936	
	24	Latent Heat of Vaporization (Kj/Kg)	1807.0	
SELECTION	25	Ratio of Specific Heats(Cp/Cv)	1.278	
	26	Density @ flowing temprature	17.34	kg/m3
	27	Operating Viscosity	0.017	cP
	28	Barometric Pressure	13.26 ~ 14.37	psia
	29	Design Code	Sizing Basis	API 520
	30	Construction Code	API 520	
	31	Fire	YES	
	32	Basis of Selection	FIRE	
CONNECTIONS	33	Calculated Area	MM ²	59.62 (VTC)
	34	Required Area	MM ²	153.93 (VTC)
	35	Orifice Designation	D (VTC)	
MATERIALS (VTC)	36	Size: Inlet	Outlet	1" in 2" in
	37	Rating & Facing :In	Outlet	#300 FLANGED RF #300 FLANGED RF
MATERIALS (VTC)	38	Body and Bonnet	ASTM A216 GR. WCB (VTC)	
	39	Seat and Disc	SS316+RPTFE	
	40	Nozzle	316 SS	
	41	Guide and Rings	VTA	
	42	Spring	ASTM A216 GR. WCB (VTC) (Note2)	
	43	Bellows	SS316+PTFE (VTC)	
	44			
OPTIONS	45	Cap: Screwed or Bolted	Screwed	
	46	Lever: Plain or Packed	N/A	
	47	Test Gage	Yes	
	48	With Rupture Disc	No	
	49	Hydro Test	Required	
	50	Seat Leakage Test	Required	
	51	Compliance Standard	N/A	
PURCHASE (will be finalized later)	52	Manufacturer	Will Be Finalized Later	
	53	Model	Will Be Finalized Later	
	54	Serial No.	Will Be Finalized Later	

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۰ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2131C				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0042C-CN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	CN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0009_D06(3 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Bellows				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		982.27		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	18.1 /		22 bar-g		
	17	Oper. Temperature	RelievingTemp.	60 /		208 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	3.4		bar-g		
	20		Total	3.4		bar-g		
	21	% Allowable Overpressure		21%				
	22	Over Pressure Factor		1.21				
	23	Compressibility Factor(Z)		0.936				
	24	Latent Heat of Vaporization (KJ/Kg)		1807.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.278				
	26	Density @ flowing temprature		17.34 kg/m3				
	27	Operating Viscosity		0.017 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		YES				
	32	Basis of Selection		FIRE				
	33	Calculated Area	MM²	59.62 (VTC)				
	34	Required Area	MM²	153.93 (VTC)				
	35	Orifice Designation		D (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1" in		2" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#300 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		SS316+PTFE (VTC)				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۱ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2132A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0047A-FN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0010_D05 (1 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		8664.0		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	54.80 /		62 bar-g		
	17	Oper. Temperature	RelievingTemp.	142.3 /		142.3 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	1.0		bar-g		
	20		Total	1.0		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.923				
	24	Latent Heat of Vaporization (Kj/Kg)		566.7				
	25	Ratio of Specific Heats(Cp/Cv)		1.28				
	26	Density @ flowing temprature		54.06 kg/m3				
	27	Operating Viscosity		0.017 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	193.67 (VTC)				
	34	Required Area	MM²	397.60 (VTC)				
	35	Orifice Designation		G (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in		3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

بسته کاری

صادر کننده

تجهیزات

رشته

نوع مدرک

سریال

نسخه

BK

GCS

PEDCO

120

IN

DT

0009

D02

شماره صفحه: ۲۲ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2133A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0048A-FN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0010_D05 (1 OF 3)		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief		Safety			
	11		Conventional, bellows, Pilot Op.		Conventional			
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		8664.0		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	54.80 /		62 bar-g		
	17	Oper. Temperature	RelievingTemp.	142.3 /		142.3 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	1.0		bar-g		
	20		Total	1.0		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.923				
	24	Latent Heat of Vaporization (Kj/Kg)		566.7				
	25	Ratio of Specific Heats(Cp/Cv)		1.28				
	26	Density @ flowing temprature		54.06 kg/m3				
	27	Operating Viscosity		0.017 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	193.67 (VTC)				
	34	Required Area	MM²	397.60 (VTC)				
	35	Orifice Designation		G (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in		3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 "

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۳ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2132B			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0047B-FN05-2"-PT	-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm	BK-GCS-PEDCO-120-PR-PI-0010_D05 (2 OF 3)		
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase	
	14	Required Capacity		8664.0		kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52	kg/kmol	0.85 kg/m3	
	16	Oper. Pressure	Set Pressure	54.80	/	62 bar-g	
	17	Oper. Temperature	RelievingTemp.	142.3	/	142.3 °C	
	18	Back Pressure	Constant	-		bar-g	
	19		Variable	1.0		bar-g	
	20		Total	1.0		bar-g	
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.923			
	24	Latent Heat of Vaporization (Kj/Kg)		566.7			
	25	Ratio of Specific Heats(Cp/Cv)		1.28			
	26	Density @ flowing temprature		54.06	kg/m3		
	27	Operating Viscosity		0.017	cP		
	28	Barometric Pressure		13.26 ~ 14.37	psia		
SELECTION	29	Design Code	Sizing Basis	API 520		-	
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	193.67 (VTC)			
	34	Required Area	MM²	397.60 (VTC)			
	35	Orifice Designation		G (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in		3" in	
	37	Rating & Facing :In	Outlet	#600 FLANGED RF		#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
OPTIONS	44						
	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
PURCHASE (will be finalized later)	51	Compliance Standard		N/A			
	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۴ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2133B			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0048B-FN05-2"-PT	-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm	BK-GCS-PEDCO-120-PR-PI-0010_D05 (2 OF 3)		
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase	
	14	Required Capacity		8664.0		kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52	kg/kmol	0.85 kg/m3	
	16	Oper. Pressure	Set Pressure	54.80 / 62		bar-g	
	17	Oper. Temperature	RelievingTemp.	142.3 / 142.3		°C	
	18	Back Pressure	Constant	-		bar-g	
	19		Variable	1.0		bar-g	
	20		Total	1.0		bar-g	
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.923			
	24	Latent Heat of Vaporization (KJ/Kg)		566.7			
	25	Ratio of Specific Heats(Cp/Cv)		1.28			
	26	Density @ flowing temprature		54.06	kg/m3		
	27	Operating Viscosity		0.017	cP		
	28	Barometric Pressure		13.26 ~ 14.37	psia		
SELECTION	29	Design Code	Sizing Basis	API 520		-	
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	193.67 (VTC)			
	34	Required Area	MM²	397.60 (VTC)			
	35	Orifice Designation		G (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in		3" in	
	37	Rating & Facing :In	Outlet	#600 FLANGED RF		#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
	44						
OPTIONS	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
	51	Compliance Standard		N/A			
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره صفحه: ۲۵ از ۳۳

شماره پیمان: ۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	D02	سریال	0009	بوع مدرک	DT	رشته	IN	تجهیزات	120	صادر کننده	PEDCO	بسته کاری	GCS	پروژه	BK
------	-----	-------	------	----------	----	------	----	---------	-----	------------	-------	-----------	-----	-------	----

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2132C			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0047C-FN05-2"-PT	-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm	BK-GCS-PEDCO-120-PR-PI-0010_D05 (3 OF 3)		
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS	Singel Phase		
	14	Required Capacity		8664.0	kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52	kg/kmol	0.85 kg/m3	
	16	Oper. Pressure	Set Pressure	54.80	/	62 bar-g	
	17	Oper. Temperature	RelievingTemp.	142.3	/	142.3 °C	
	18	Back Pressure	Constant	- bar-g			
	19		Variable	1.0 bar-g			
	20		Total	1.0 bar-g			
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.923			
	24	Latent Heat of Vaporization (Kj/Kg)		566.7			
	25	Ratio of Specific Heats(Cp/Cv)		1.28			
	26	Density @ flowing temprature		54.06	kg/m3		
	27	Operating Viscosity		0.017	cP		
	28	Barometric Pressure		13.26 ~ 14.37	psia		
SELECTION	29	Design Code	Sizing Basis	API 520	-		
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	193.67 (VTC)			
	34	Required Area	MM²	397.60 (VTC)			
	35	Orifice Designation		G (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in	3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGED RF	#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
OPTIONS	44						
	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
PURCHASE (will be finalized later)	51	Compliance Standard		N/A			
	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۶ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2133C			D02
	2	Service		GAS			
	3	Line No.	Vessel No.	GAS-111-0048C-FN05-2"-PT	-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm	BK-GCS-PEDCO-120-PR-PI-0010_D05 (3 OF 3)		
	5	Discharge to		To FLARE			
	6	Protect Equipment		-			
	7	Area Clacification		Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance		YES			
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type			
	10	Design Type	Safety, Relief, Safety-Relief	Safety			
	11		Conventional, bellows, Pilot Op.	Conventional			
	12	Bonnet Type		Closed			
PROCESS CONDITIONS	13	Fluid	State	GAS	Singel Phase		
	14	Required Capacity		8664.0	kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.52	kg/kmol	0.85	
	16	Oper. Pressure	Set Pressure	54.80	/	62 bar-g	
	17	Oper. Temperature	RelievingTemp.	142.3	/	142.3 °C	
	18	Back Pressure	Constant	- bar-g			
	19		Variable	1.0 bar-g			
	20		Total	1.0 bar-g			
	21	% Allowable Overpressure		10%			
	22	Over Pressure Factor		1.10			
	23	Compressibility Factor(Z)		0.923			
	24	Latent Heat of Vaporization (Kj/Kg)		566.7			
	25	Ratio of Specific Heats(Cp/Cv)		1.28			
	26	Density @ flowing temprature		54.06	kg/m3		
	27	Operating Viscosity		0.017	cP		
	28	Barometric Pressure		13.26 ~ 14.37	psia		
SELECTION	29	Design Code	Sizing Basis	API 520	-		
	30	Construction Code		API 520			
	31	Fire		NO			
	32	Basis of Selection		Blocked Outlet			
	33	Calculated Area	MM²	193.67 (VTC)			
	34	Required Area	MM²	397.60 (VTC)			
	35	Orifice Designation		G (VTC)			
CONNECTIONS	36	Size: Inlet	Outlet	1 1/2" in	3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGED RF	#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)			
	39	Seat and Disc		SS316+RPTFE			
	40	Nozzle		316 SS			
	41	Guide and Rings		VTA			
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows		N/A			
OPTIONS	44						
	45	Cap: Screwed or Bolted		Screwed			
	46	Lever: Plain or Packed		N/A			
	47	Test Gage		Yes			
	48	With Rupture Disc		No			
	49	Hydro Test		Required			
	50	Seat Leakage Test		Required			
PURCHASE (will be finalized later)	51	Compliance Standard		N/A			
	52	Manufacturer		Will Be Finalized Later			
	53	Model		Will Be Finalized Later			
	54	Serial No.		Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۷ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2141				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0060-FN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0012 _D06		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		17252.50		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.562 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	53.9 / 62		bar-g		
	17	Oper. Temperature	RelievingTemp.	60 / 60		°C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	1.0		bar-g		
	20		Total	1.0		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.823				
	24	Latent Heat of Vaporization (KJ/Kg)		1456.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.461				
	26	Density @ flowing temprature		78.39 kg/m3				
	27	Operating Viscosity		0.015 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	311 (VTC)				
	34	Required Area	MM²	629.01 (VTC)				
	35	Orifice Designation		H (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGEDRF		#150 FLANGEDRF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۲۸ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2142				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	GAS-111-0062-FN05-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	FN05 / 3mm		BK-GCS-PEDCO-120-PR-PI-0012_D06		
	5	Discharge to		To FLARE				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		YES				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		17252.50		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	24.562 kg/kmol		0.85 kg/m3		
	16	Oper. Pressure	Set Pressure	53.9 / 62		bar-g		
	17	Oper. Temperature	RelievingTemp.	60 / 60		°C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	1.0		bar-g		
	20		Total	1.0		bar-g		
	21	% Allowable Overpressure		10%				
	22	Over Pressure Factor		1.10				
	23	Compressibility Factor(Z)		0.823				
	24	Latent Heat of Vaporization (KJ/Kg)		1456.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.461				
	26	Density @ flowing temprature		78.39 kg/m3				
27	Operating Viscosity		0.015 cP					
28	Barometric Pressure		13.26 ~ 14.37 psia					
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		NO				
	32	Basis of Selection		Blocked Outlet				
	33	Calculated Area	MM²	311 (VTC)				
	34	Required Area	MM²	629.01 (VTC)				
	35	Orifice Designation		H (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	2" in		3" in		
	37	Rating & Facing :In	Outlet	#600 FLANGEDRF		#150 FLANGEDRF		
MATERIALS (VTC)	38	Body and Bonnet		ASTM A216 GR. WCB (VTC)				
	39	Seat and Disc		SS316+RPTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
OPTIONS	44							
	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
PURCHASE (will be finalized later)	51	Compliance Standard		N/A				
	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	54	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	سریال	بوع مدرک	رشته	تجهیزات	صادر کننده	بسته کاری	پروژه
D02	0009	DT	IN	120	PEDCO	GCS	BK

شماره صفحه: ۲۹ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2201		D02
	2	Service		GAS		
	3	Line No.	Vessel No.	ISA-112-0008-AZ00-2"-NP	-	
	4	Pipe Class / C.A.	P&ID No.	AZ00 / 0mm	BK-GCS-PEDCO-120-PR-PI-0015_D06	
	5	Discharge to		To ATM		
	6	Protect Equipment		-		
	7	Area Clacification		Zone 2, IIB T4		
	8	NACE MR0175/ISO 15156 Compliance		No		
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type		
	10	Design Type	Safety, Relief, Safety-Relief	Safety		
	11		Conventional, bellows, Pilot Op.	Conventional		
	12	Bonnet Type		Closed		
PROCESS CONDITIONS	13	Fluid	State	GAS	Singel Phase	
	14	Required Capacity		1071.8	kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	28.95 kg/kmol	1.00 kg/m3	
	16	Oper. Pressure	Set Pressure	8.00	12.5 bar-g	
	17	Oper. Temperature	RelievingTemp.	65 /	323.4 °C	
	18	Back Pressure	Constant	-	bar-g	
	19		Variable	0.0	bar-g	
	20		Total	0.0	bar-g	
	21	% Allowable Overpressure		21%		
	22	Over Pressure Factor		1.21		
	23	Compressibility Factor(Z)		0.99		
	24	Latent Heat of Vaporization (KJ/Kg)		1949.0		
	25	Ratio of Specific Heats(Cp/Cv)		1.42		
	26	Density @ flowing temprature		9.37 kg/m3		
	27	Operating Viscosity		0.032 cP		
	28	Barometric Pressure		13.26 ~ 14.37 psia		
SELECTION	29	Design Code	Sizing Basis	API 520	-	
	30	Construction Code		API 520		
	31	Fire		Yes		
	32	Basis of Selection		FIRE		
	33	Calculated Area	MM²	113.24 (VTC)		
	34	Required Area	MM²	153.95 (VTC)		
	35	Orifice Designation		E (VTC)		
CONNECTIONS	36	Size: Inlet	Outlet	1" in	2" in	
	37	Rating & Facing :In	Outlet	#300 FLANGED RF	#150 FLANGED RF	
MATERIALS (VTC)	38	Body and Bonnet		ASTM B148 UNS C95800		
	39	Seat and Disc		ASTM B148 UNS C95800		
	40	Nozzle		316 SS		
	41	Guide and Rings		VTA		
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)		
	43	Bellows		N/A		
	44					
OPTIONS	45	Cap: Screwed or Bolted		Screwed		
	46	Lever: Plain or Packed		N/A		
	47	Test Gage		Yes		
	48	With Rupture Disc		No		
	49	Hydro Test		Required		
	50	Seat Leakage Test		Required		
	51	Compliance Standard		N/A		
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later		
	53	Model		Will Be Finalized Later		
	54	Serial No.		Will Be Finalized Later		

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

نوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۳۰ از ۳۳

PRESSURE SAFETY VALVE

GENERAL	1	Tag Number		PSV-2211A				D02
	2	Service		GAS				
	3	Line No.	Vessel No.	NIT-112-0022-AN01-2"-PT		-		
	4	Pipe Class / C.A.	P&ID No.	AN01 / 1mm		BK-GCS-PEDCO-120-PR-PI-0016_D06		
	5	Discharge to		To ATM				
	6	Protect Equipment		-				
	7	Area Clacification		Zone 2, IIB T4				
	8	NACE MR0175/ISO 15156 Compliance		No				
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type				
	10	Design Type	Safety, Relief, Safety-Relief	Safety				
	11		Conventional, bellows, Pilot Op.	Conventional				
	12	Bonnet Type		Closed				
PROCESS CONDITIONS	13	Fluid	State	GAS		Singel Phase		
	14	Required Capacity		500.4		kg/h		
	15	Molecular Mass	Sp. Gr.@ relief Tmp	28 kg/kmol		0.97 kg/m3		
	16	Oper. Pressure	Set Pressure	8.00		12.5 bar-g		
	17	Oper. Temperature	RelievingTemp.	60 /		323.4 °C		
	18	Back Pressure	Constant	-		bar-g		
	19		Variable	0.5		bar-g		
	20		Total	0.5		bar-g		
	21	% Allowable Overpressure		21%				
	22	Over Pressure Factor		1.21				
	23	Compressibility Factor(Z)		0.99				
	24	Latent Heat of Vaporization (KJ/Kg)		1950.0				
	25	Ratio of Specific Heats(Cp/Cv)		1.40				
	26	Density @ flowing temprature		7.60 kg/m3				
	27	Operating Viscosity		0.030 cP				
	28	Barometric Pressure		13.26 ~ 14.37 psia				
SELECTION	29	Design Code	Sizing Basis	API 520		-		
	30	Construction Code		API 520				
	31	Fire		Yes				
	32	Basis of Selection		FIRE				
	33	Calculated Area	MM²	54.241 (VTC)				
	34	Required Area	MM²	153.9 (VTC)				
	35	Orifice Designation		D (VTC)				
CONNECTIONS	36	Size: Inlet	Outlet	1" in		2" in		
	37	Rating & Facing :In	Outlet	#300 FLANGED RF		#150 FLANGED RF		
MATERIALS (VTC)	38	Body and Bonnet		A216 Gr. WCB				
	39	Seat and Disc		13Cr+PTFE				
	40	Nozzle		316 SS				
	41	Guide and Rings		VTA				
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)				
	43	Bellows		N/A				
	44							
OPTIONS	45	Cap: Screwed or Bolted		Screwed				
	46	Lever: Plain or Packed		N/A				
	47	Test Gage		Yes				
	48	With Rupture Disc		No				
	49	Hydro Test		Required				
	50	Seat Leakage Test		Required				
	51	Compliance Standard		N/A				
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later				
	53	Model		Will Be Finalized Later				
	52	Serial No.		Will Be Finalized Later				

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادر کننده

PEDCO

تجهیزات

120

رشته

IN

بوع مدرک

DT

سریال

0009

نسخه

D02

شماره صفحه: ۳۱ از ۳۳

PRESSURE SAFETY VALVE

D02

GENERAL	1	Tag Number	PSV-2271	
	2	Service	GAS	
	3	Line No.	Vessel No.	FLG-111-0011-AN07-2"-PT
	4	Pipe Class / C.A.	P&ID No.	AN07 / 6mm
	5	Discharge to	To FLARE	
	6	Protect Equipment	-	
	7	Area Clacification	Zone 2, IIB T4	
	8	NACE MR0175/ISO 15156 Compliance	Yes	
BASIS	9	Nozzle (Full, Semi)	Full Nozzle	
	10	Design Type	Safety, Relief, Safety-Relief	Safety
	11		Conventional, bellows, Pilot Op.	Bellows
	12	Bonnet Type	Closed	
PROCESS CONDITIONS	13	Fluid	State	GAS Singel Phase
	14	Required Capacity	174.5 kg/h	
	15	Molecular Mass	Sp. Gr.@ relief Tmp	18.02 kg/kmol 0.62 kg/m3
	16	Oper. Pressure	Set Pressure	4.90 9 bar-g
	17	Oper. Temperature	Relieving Temp.	36.78 / 182.6 °C
	18	Back Pressure	Constant	- bar-g
	19		Variable	3.2 bar-g
	20		Total	3.2 bar-g
	21	% Allowable Overpressure	21%	
	22	Over Pressure Factor	1.21	
	23	Compressibility Factor(Z)	0.975	
	24	Latent Heat of Vaporization (Kj/Kg)	1994.0	
	25	Ratio of Specific Heats(Cp/Cv)	1.25	
	26	Density @ flowing temprature	6.46 kg/m3	
SELECTION	27	Operating Viscosity	0.012 cP	
	28	Barometric Pressure	13.26 ~ 14.37 psia	
	29	Design Code	Sizing Basis	API 520 -
	30	Construction Code	API 520	
	31	Fire	NO	
	32	Basis of Selection	FIRE	
	33	Calculated Area	MM²	28.75(VTC)
	34	Required Area	MM²	153.9 (VTC)
CONNECTIONS	35	Orifice Designation	D (VTC)	
	36	Size: Inlet	Outlet	1" in 2" in
MATERIALS (VTC)	37	Rating & Facing :In	Outlet	#300 FLANGED RF #150 FLANGED RF
	38	Body and Bonnet	ASTM A216 GR. WCB	
	39	Seat and Disc	SS316+PTFE	
	40	Nozzle	316SS	
	41	Guide and Rings	VTA	
	42	Spring	ASTM A216 GR. WCB (VTC) (Note2)	
	43	Bellows	SS316+PTFE (VTC)	
	44			
OPTIONS	45	Cap: Screwed or Bolted	Screwed	
	46	Lever: Plain or Packed	N/A	
	47	Test Gage	Yes	
	48	With Rupture Disc	No	
	49	Hydro Test	Required	
	50	Seat Leakage Test	Required	
	51	Compliance Standard	N/A	
PURCHASE (will be finalized later)	52	Manufacturer	Will Be Finalized Later	
	53	Model	Will Be Finalized Later	
	54	Serial No.	Will Be Finalized Later	

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)

 NISOC		نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک								
DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES										
شماره پیمان: ۰۵۳ - ۰۷۳ - ۹۱۸۴		پروژه	بسته کاری	صادر کننده	تهیهات	رشته	نوع مدرک	سریال	نسخه	شماره صفحه: ۳۳ از ۳۳
		BK	GCS	PEDCO	120	IN	DT	0009	D02	

PRESSURE SAFETY VALVE										
GENERAL	1	Tag Number					PSV-2293		D02	
	2	Service					GAS			
	3	Line No.		Vessel No.		TEG-111-0113-AN04-2"-PT		-		
	4	Pipe Class / C.A.		P&ID No.		AN04 / 3mm		BK-GCS-PEDCO-120-PR-PI-0025_D06		
	5	Discharge to					To FLARE			
	6	Protect Equipment								
	7	Area Clacification					Zone 2, IIB T4			
	8	NACE MR0175/ISO 15156 Compliance					Yes			
BASIS	9	Nozzle (Full, Semi)					Full Nozzle, Spring Loaded Type			
	10	Design Type		Safety, Relief, Safety-Relief		Safety				
	Conventional, bellows, Pilot Op.			Conventional						
	12	Bonnet Type					Closed			
PROCESS CONDITIONS	13	Fluid		State		GAS		Singel Phase		
	14	Required Capacity					2098.0		kg/h	
	15	Molecular Mass		Sp. Gr.@ relief Tmp		143.6		kg/kmol	4.95	
	16	Oper. Pressure		Set Pressure		0.10		3.5	bar-g	
	17	Oper. Temperature		RelievingTemp.		AMB		/	335.9 °C	
	18	Back Pressure		Constant				bar-g		
	Variable			0.1		bar-g				
	Total			0.1		bar-g				
	21	% Allowable Overpressure					21%			
	22	Over Pressure Factor					1.21			
	23	Compressibility Factor(Z)					0.646			
	24	Latent Heat of Vaporization (Kj/Kg)					314.3			
	25	Ratio of Specific Heats(Cp/Cv)					1.08			
	26	Density @ flowing temprature					10.29		kg/m3	
	27	Operating Viscosity					0.010		cP	
	28	Barometric Pressure					13.26 - 14.37		psia	
SELECTION	29	Design Code		Sizing Basis		API 520		-		
	30	Construction Code					API 520			
	31	Fire					NO			
	32	Basis of Selection					FIRE			
	33	Calculated Area		MM²		275(VTC)				
	34	Required Area		MM²		397.6 (VTC)				
	35	Orifice Designation					G (VTC)			
	36	Size: Inlet		Outlet		1 1/2" in		3" in		
37	Rating & Facing :In		Outlet		#300 FLANGED RF		#150 FLANGED RF			
MATERIALS (VTC)	38	Body and Bonnet					ASTM A105			
	39	Seat and Disc					SS316+PTFE			
	40	Nozzle					316 SS			
	41	Guide and Rings					VTA			
	42	Spring					ASTM A216 GR. WCB (VTC) (Note2)			
	43	Bellows					N/A			
	44									
OPTIONS	45	Cap: Screwed or Bolted					Screwed			
	46	Lever: Plain or Packed					N/A			
	47	Test Gage					Yes			
	48	With Rupture Disc					No			
	49	Hydro Test					Required			
	50	Seat Leakage Test					Required			
	51	Compliance Standard					N/A			
PURCHASE (will be finalized later)	52	Manufacturer					Will Be Finalized Later			
	53	Model					Will Be Finalized Later			
	54	Serial No.					Will Be Finalized Later			

Notes: □

VTA : Vendor to Advise in bidding stage VTC : Vendor to confirm in bidding stage N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".
2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



DATA SHEETS FOR PRESSURE & SAFETY RELIEF VALVES

شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

پسته کاری

صادر کننده

تهیهات

رشته

نوع مدرک

سریال

نسخه

شماره صفحه: ۳۳ از ۳۳

BK

GCS

PEDCO

120

IN

DT

0009

D02

TEMPERATURE SAFETY VALVE

D02

GENERAL	1	Tag Number		TSV-2281	
	2	Service		LIQUID	
	3	Line No.	Vessel No.	DO-112-0005A-AN01-1"-PT	-
	4	Pipe Class / C.A.	P&ID No.	AN01 / 1mm	BK-GCS-PEDCO-120-PR-PI-0023_D06 (1 OF 3)
	5	Discharge to		To DIESEL OIL DRUM	
	6	Protect Equipment		-	
	7	Area Classification		Zone 2, IIB T4	
	8	NACE MR0175/ISO 15156 Compliance		NO	
BASIS	9	Nozzle (Full, Semi)		Full Nozzle, Spring Loaded Type	
	10	Design Type	Safety, Relief, Safety-Relief	Safety	
	11		Conventional, bellows, Pilot Op.	Conventional	
	12	Bonnet Type		Closed	
PROCESS CONDITIONS	13	Fluid	State	LIQUID	Singel Phase
	14	Required Capacity		39.537 (V.T.C)	kg/h
	15	Molecular Mass	Sp. Gr.@ relief Tmp	184.4	0.85
	16	Oper. Pressure	Set Pressure	0.10	3.5 bar-g
	17	Oper. Temperature	Relieving Temp.	AMB /	VTA °C
	18	Back Pressure	Constant	-	bar-g
	19		Variable	0.0	bar-g
	20		Total	0.0	bar-g
	21	% Allowable Overpressure		10%	
	22	Over Pressure Factor		110%	
	23	Compressibility Factor(Z)		-	
	24	Latent Heat of Vaporization (Kj/Kg)		-	
	25	Ratio of Specific Heats(Cp/Cv)		1.118	
	26	Density @ flowing temprature		850.00	
	27	Operating Viscosity (cp)		2.143	
	28	Barometric Pressure		13.26 - 14.37	psia
SELECTION	29	Design Code	Sizing Basis	-	-
	30	Construction Code		-	
	31	Fire		-	
	32	Basis of Selection		Thermal Expansion	
	33	Calculated Area	MM²	0.00003	
	34	Required Area	MM²	0.0000709676 (V.T.C)	
	35	Orifice Designation		D	
CONNECTIONS	36	Size: Inlet	Outlet	3/4" in	1" in
	37	Rating & Facing :In	Outlet	#300 FLANGED RF	#150 FLANGED RF
MATERIALS (VTC)	38	Body and Bonnet		ASTM A105	
	39	Seat and Disc		SS316+PTFE	
	40	Nozzle		316 SS	
	41	Guide and Rings		VTA	
	42	Spring		ASTM A216 GR. WCB (VTC) (Note2)	
	43	Bellows		N/A	
OPTIONS	44				
	45	Cap: Screwed or Bolted		Screwed	
	46	Lever: Plain or Packed		N/A	
	47	Test Gage		Yes	
	48	With Rupture Disc		No	
	49	Hydro Test		Required	
	50	Seat Leakage Test		Required	
	51	Compliance Standard		N/A	
PURCHASE (will be finalized later)	52	Manufacturer		Will Be Finalized Later	
	53	Model		Will Be Finalized Later	
	54	Serial No.		Will Be Finalized Later	

Notes: □

VTA : Vendor to Advise in bidding stage

VTC : Vendor to confirm in bidding stage

N/A: Not applicable

1- For material details refer to "Piping Material Specification Doc No." BK-GCS-PEDCO-120-PI-SP-0001-D02 ".

2- Suitable coating such as cadmiun plated shall be considered (vendor to advise)