

Calculation header

Identifier *BINAK*
 Tag No. *RO-2133A/B/C*

Medium selection and state

Medium  *Natural Gas (AGA8)*
 Mixture composition  *BDV-2132A/B/C*
 State  *Gaseous*
 Gas *Gas, dry (Operating conditions)*

Inlet properties

Operating temperature t_1 *60.0* °C
 Operating pressure p_1 *62.0* bar(g)
 Operating density (t_1 , p_1) ρ_1  *68.246* kg/m³
 Isentropic exponent (t_1 , p_1) κ_1  *1.2401* -

Pipeline




☒ Pipe class  *ANSI*
 Size class  *1 1/2"*
 Schedule  *Schedule 40s*

Orifice plate




Throttle *Single stage*
 Type of orifice plate *Single-hole orifice*
 Type of bore *Cylindrical bore*
☐ Flow coefficient C  *0.7851* -

Operating data

☐ Critical flow according to R. W. Miller Calculation ☒ Safety-related application *d*

Permanent pressure loss $\Delta\omega$ *55.0* bar
 Throttle orifice (20°C) d  *4.9* mm
☒ Mass flow rate q_m *1,333.0* kg/h
☐ Volume flow rate (operating conditions) q_v  *85.998* GPM(US)
 Flow type  *Non-critical*



Calculated auxiliary values

Sound pressure level (A-weighted)	LpAe 	87.0	dB(A)
Diameter ratio	β 	0.11982	-
Power loss	P 	77.956	hp(l)

Outlet properties

Operating pressure	p2 	7.0	bar(g)
Mach number	Ma2 	0.099184	-




Hint:

-  Approximate value: Dynamic viscosity (t1, p1) - η_1
-  Approximate value: Min. orifice thickness for Δp - E,min

Comments:**Mixture composition**

Methane: 63.9 %, Nitrogen: 0.298 %, Carbon dioxide: 3.16 %, Ethane: 13.8 %, Propane: 7.73 %, n-Butane: 1.86 %, i-Butane: 0.839 %, n-Pentane: 0.377 %, i-Pentane: 0.697 %, n-Hexane: 0.655 %, n-Heptane: 0.196 %, n-Octane: 0.0596 %, n-Nonane: 0.0297 %, n-Decane: 0.0099 %, Water: 1.03 %, Hydrogen sulphide: 5.41 %

Legend

-  Calculated value
-  Lookup value
-  Hint