


Calculation header

Identifier *BINAK*
 Tag No. *RO-2151*

Medium selection and state

Medium  *Natural Gas (AGA8)*
 Mixture composition  *BDV-2151*
 State  *Gaseous*
 Gas *Gas, dry (Operating conditions)*

Inlet properties

Operating temperature t_1 *59.4* °C
 Operating pressure p_1 *62.0* bar(g)
 Operating density (t_1 , p_1) ρ_1  *68.579* kg/m³
 Isentropic exponent (t_1 , p_1) κ_1  *1.2379* -

Pipeline




☒ Pipe class  *ANSI*
 Size class  *3"*
 Schedule  *Schedule 80*

Orifice plate




Throttle *Single stage*
 Type of orifice plate *Single-hole orifice*
 Type of bore *Cylindrical bore*
☐ Flow coefficient C  *0.7855* -

Operating data

☐ Critical flow according to R. W. Miller Calculation ☒ Safety-related application *d*

Permanent pressure loss $\Delta\omega$ *55.0* bar
 Throttle orifice (20°C) d  *9.0688* mm
☒ Mass flow rate q_m *4,578.0* kg/h
☐ Volume flow rate (operating conditions) q_v  *293.91* GPM(US)
 Flow type  *Non-critical*



Calculated auxiliary values

Sound pressure level (A-weighted)	LpAe 	95.9	dB(A)
Diameter ratio	β 	0.12312	-
Power loss	P 	266.79	hp(l)

Outlet properties

Operating pressure	p2 	7.0	bar(g)
Mach number	Ma2 	0.10481	-




Hint:

-  Approximate value: Dynamic viscosity (t1, p1) - η_1
-  Approximate value: Min. orifice thickness for Δp - E,min

Comments:**Mixture composition**

Methane: 64.6 %, Nitrogen: 0.302 %, Carbon dioxide: 3.19 %, Ethane: 13.9 %, Propane: 7.81 %, n-Butane: 1.88 %, i-Butane: 0.845 %, n-Pentane: 0.381 %, i-Pentane: 0.7 %, n-Hexane: 0.662 %, n-Heptane: 0.198 %, n-Octane: 0.0603 %, n-Nonane: 0.03 %, n-Decane: 0.01 %, Water: 0.0222 %, Hydrogen sulphide: 5.4 %

Legend

-  Calculated value
-  Lookup value
-  Hint