
	<div>نگهداشت و افزایش تولید میدان نفتی بینک</div> <div>سطح الارض</div> <div>احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک</div>								
شماره پیمان: ۰۵۳-۰۷۳-۹۱۸۴	MECHANICAL DATA SHEETS FOR SUMP PUMPS							شماره صفحه: ۱ از ۵	
	پروژه	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال		نسخه
	BK	GCS	PEDCO	120	ME	DT	0023		D04

طرح نگهداشت و افزایش تولید ۲۷ مخزن

MECHANICAL DATA SHEETS FOR SUMP PUMPS

نگهداشت و افزایش تولید میدان نفتی بینک

D04	AUG. 2024	IFA	V.Amjadi	M. Fakharian	M.Sadeghian	
D03	OCT. 2023	IFA	H.Ghadyani	M. Fakharian	S.Faramarzpour	
D02	DEC. 2022	IFA	H. Adineh	M. Fakharian	M.Mehrshad	
D01	JAN. 2022	IFA	H. Adineh	M. Fakharian	M.Mehrshad	
D00	DEC. 2021	IFC	H. Adineh	M. Fakharian	M.Mehrshad	
Rev.	Date	Purpose of Issue / Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

Class: 1 CLIENT Doc. Number: F0Z-708854

status:

IDC: Inter-Discipline Check

IFC: Issued For Comment

IFA: Issued For Approval

AFD: Approved For Design

AFC: Approved For Construction

AFP: Approved For Purchase

AFQ: Approved For Quotation

IFI: Issued For Information

AB-R: As-Built for CLIENT Review

AB-A: As-Built –Approved



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

۰۵۳-۰۷۳-۹۱۸۴

MECHANICAL DATA SHEETS FOR SUMP PUMPS

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادر کننده	بسته کاری	پروژه
D04	0023	DT	ME	120	PEDCO	GCS	BK

شماره صفحه: ۲ از ۵

REVISION RECORD SHEET

page	D00	D01	D02	D03	D04
1	x	x	x	x	x
2	x	x	x	x	x
3	x	x	x	x	
4	x		x	x	x
5	x		x	x	x
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
60					
61					
62					
63					
64					

page	D00	D01	D02	D03	D04
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
124					
125					
126					
127					
128					



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

۰۵۳-۰۷۳-۹۱۸۴



MECHANICAL DATA SHEETS FOR SUMP PUMPS

نسخه	سریال	نوع مدارک	رشته	تهیهات	صادر کننده	بسته کاری	پروژه
D04	0023	DT	ME	120	PEDCO	GCS	BK

شماره صفحه: ۳ از ۵

GENERAL NOTES

- Design Conditions: Min./Max Design Temp.°C Max.Design Press.(barg)
5 / 85 2.5
- For electrical motor descriptions, refer to 'Specification For LV Electro Motors' Doc. No. BK-GNRL-PEDCO-000-EL-SP-0010.
- For technical requirements of electrical LV motors refer to "Data sheets for LV induction motors" Doc.No; BK-GCS-PEDCO-120-EL-DT-0008"
Vendor shall fill in the blanks and return the completed data sheet along with his proposal.
- Vendor shall submit ITP (Inspection & Testing Plan) with his proposal.
- The motors,pump coupling and pump accessories shall be supplied from the project's approved vendor list (A.V.L.).
- Vendor is requested to confirm the material, or propose appropriate alternative.
- Mechanical seal data sheet shall fill in by vendor as per API 682. Pump Manufacturer shall supply all instrumentation for mechanical seals as per API 682 4th Edition and project requirements.
Also orifice with diameter 3mm to be considered by vendor for seal flushing.
- NPSH test shall be done & witnessed if the margin of NPSHr & NPSHa is less than 1.
- The Tie-in flanges shall conform to ASME B-16.5.
- Supplier to indicate which minimum flow pumps can achieve.
- Pumps shall be designed, fabricated, tested, and inspected in accordance with the requirements of ISO 5199 latest edition.
- Pump starts automatically with open delivery valve.
- Electrical motor shall be rated for the end of curve.
- The discharge line is 2".
- Material class of 'I-1', 'I-2', 'S-1', 'S-2', 'S-3', 'S-4', 'S-5', 'S-6', 'C-6' 'A-7' and 'A-8', which is defined in API 610 table H.1, shall be provided with full chemical analysis and mechanical test certification to BS EN 10204:2004 "3.1".
Material class of 'D-1' and 'D-2', which is defined in API 610 table H.1 and also titanium materials shall be provided with full chemical analysis and mechanical test certification to BS EN 10204:2004 "3.2".
- Based on project instrumentation specification, these equipments are classified as Type B (Connected to DCS/ESD):Centrifugal Pump Package
- Pump material shall be selected based on Annex H API 610 11th Edition. (vendor to confirm)
- Ultrasonic Test shall be performed for forged shaft.
- For pumps with vacuum suction pressure the minimum NPSH margin shall be 2 m. for other pumps the minimum NPSH margin shall be 1 m.
- Couplings shall be dry, flexible and spacer type.
- Bearing temperature shall be measured during mechanical run test.
- Max Allowable Pressure at Shut-Off is 2.5 barg.
- For site conditions refer to Process basis of design document; Doc.No: BK-GNRL-PEDCO-000-PR-DB-0001.in data sheet.
- Minimum Design Metal Tem (MDMT) = 5°C.
- Vendor to provide the pump with mentioned flow rate or minimum available flow rate at market.
- Max. allow. Sound press. Level =85 dBA.
- Allowable external forces and moments on nozzle should be conformed to Spec. No.: BK-GCS-PEDCO-120-ME-SP-0004.
- All drain and vents (If any) to be manifolded, valved and routed to the skid edge.
- Range of ambient temperature: Min. ambient temperature: 5 °C , Max. ambient temperature: 50 °C
- Hydraulic power (Kw): 0.31
- For Instrumentation, Project specification 'Specification For Instrument and Control of package Unit System (PU)' Doc. No.BK-GNRL-PEDCO-000-IN-SP-0004 and Specification For Hazardous Area Classification; BK-GNRL-PEDCO-000-SA-SP-0002 and other instrument specification which to be attached to MR shall be followed.
- The Sump pump is in pit. Sump dimentions have been considered in calculations of operating conditions. For further data refer to related P&ID; BK-GCS-PEDCO-120-PR-PI-0017. and Calculation Note For Pumps; BK-GCS-PEDCO-120-PR-CN-0001.

		<p>تنگداشت و افزایش تولید میدان نفتی بینک سطح الارض</p> <p>احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک</p>											
شماره پیمان:		MECHANICAL DATA SHEETS FOR SUMP PUMPS								شماره صفحه: ۴ از ۵			
۰۵۳-۰۷۳-۹۱۸۴		پروژه	بسته کاری	صادر کننده	تهیلات	رشته	نوع مدرک	سریال	نسخه				
		BK	GCS	PEDCO	120	ME	DT	0023	D04				
ISO Std. 5199 CENTRIFUGAL PUMP DATA SHEET (SI UNIT)													
Corporate name NISOC		Centrifugal pump Data sheet								Rev.:			
										Data:			
										Name:			
Plant:	BINAK GCS				Service:		Drain Water Pump						
					Ref. Standards:		ISO 5199, IPS-M-PM-115						
					Ref. Spec. No.:		BK-GCS-PEDCO-120-ME-SP-0004						
	No. req.	Pump type	Eq. API-610 Type		Mfr. serial No.		Kind of driver		Drive, type, size		Item No.		
Operation	1	Vertical	VS4(VTC)				Motor		LV Induction Electric Motor		P-2203 A/B		
Standby	1												
Drawings	Installation dimension					Pump weight				Pump Content			
	Assembly pump					Customer		Enquiry No.		Date			
	Assembly shaft seal							Order No.		Date			
	Piping	Auxiliary system					Supplier		Proposal No.		Date		
		Shaft seal							Contract No.		Date		
Test (4)	Material (17)	Hydrostatic	Inspection		Perform.		NPSH (8)		Sound Level		Final inspection	Approved documents	
Refer.	ISO 5199	ISO 5199	ISO 5199		ISO 5199		ISO 5199				ISO 5199	ISO 5199	
Wttn. by	Certified	Witnessed	Witnessed		Witnessed		Witnessed		NOTE 27		Certified	Certified	
Operating Condition (NOTE 12)													
Liquid	Drain Water		Flow		rated	5.50	m³/h	NPSH at rated flow		Plant- NPSHA	9.4	m	
Solids	Type				normal	5.00	m³/h			Pump- NPSH3		m	
	%of mass				min.		m³/h	Pump speed rated				rpm	
Corrosion by			Minimum flow required				Pump efficiency rated				%		
Op. Temp. (Min. / Max.)	5 / 50 °C		Inlet gauge pressure		min.	0.01	barg	Pump power input rated (NOTE 2)				kW	
pH-value at T _{op}			max.		0.10	barg	Pump power input		rated impeller dia.		kW		
Density at T _{op}	1024 kg/m³		Outlet gage pressure rated		2.00	barg	input		max. impeller dia.		kW		
Vapour press. at Max. T	0.1 bara		Differential pressure rated		2.00	bar	Electric. Driver power output rated				kW		
Kinematic vis. at T _{op}	0.5 cP		Total head rated		19.90	m	Steam turbine power output rated				kW		
Specific heat at T _{op}	J/Kg.K		Shut-off head			m	Performance curve No.						
Construction Features													
Design	barg		Max. allowable work press		barg		Cooling water condition		N.A.				
Number of Stages			Test pressure		1.5 x MAWP barg		Cooling (C) Series (s)		N.A.				
Self priming			Inlet Flange		Size/Position		Heating (H), Parallel (p)		C	H	S	P	Quantity
Impeller diameter	max	mm			Rating/facing				Bearing				
	rated	mm	Outlet Flange		Size/Position		Seal Chamber						
	min	mm			Rating/facing (14)		150# / RF		Cooler for seal flush				
Pump length vertical pumps	mm		Vent connection				Oil cooler						
Barrel dia. vertical pumps	mm		Drain connection				Flush		Liquid		Quantity		
Casing split			Shaft seal manufacture				Lantern ring						
Casing seal type			Type, size (NOTE 7)		Mech. Seal		Mechanical ring						
Impeller type			Flush plan (VTC)		11+61		Gland/Seal plate		N/A				
Casing support			Material code				Coupling (NOTE 20)		Manufacture				
Rotation(looking from driver)			Soft packing ring dimension						Type, Size				
Axial thrust reduction by			Rad. Bearing		Type				Diameter max		mm		
Total clearance	Impeller	mm	Axial. Bearing		Size		Spacer length		mm				
	Bal. Drum	mm	Line shaft bearing				Baseplate						
	Shaft bushes	mm	Bearing bracket No.				Anchor bolts supplied by		Vendor				
	Wear plate	mm	Lubrication				Driver		Supplied by	Vendor			
Wall thickness rot sheath / stat. cas			Lubrication device				Mounted by		Vendor				
Site and Utility Data (NOTES 23,24)													
Location	Partial sides		Outdoor		Unheated		Site data:		Elevation	m	Barometer	mbar	
Winterization REQ'D			Tropicalization REQ'D			Range of ambient temps: MIN/MAX			5/50		°C		
Unusual condition			Dust		Fumes		Others		Relative humidity: MIN/MAX		0/100	%	
Driver	Volt.	400	Hertz	50	Phase	3	Max Voltage Variation (NOTE 24)		± 10%				
Type of protection						Max Frequency Variation (NOTE 24)		± 5%					
Temperature rise class / Insulation class			Zone 1, IIB, T3			Max Volt. and Frequency Variation together		± 10%					



نگهداشت و افزایش تولید میدان نفتی بینک
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک



شماره پیمان:

MECHANICAL DATA SHEETS FOR SUMP PUMPS

شماره صفحه: ۵ از ۵

۰۵۳-۰۷۲-۹۱۸۴

نسخه	سریال	نوع مدرک	رشته	تهیهات	صادرکننده	پسته کاری	پروژه
D04	0023	DT	ME	120	PEDCO	GCS	BK

ISO Std. 5199 CENTRIFUGAL PUMP DATA SHEET (SI UNIT)


Material (VTC)

API class	I-2 (According to API-610)	(NOTES 6,15,17)
Casing	D04	Bearing bush
Discharge casing		Balance disc-drum
Suction casing		Bal. counter disc-drum bus.
Stage casing		Contrain.shell / Stat.casing
Suction impeller		Rotor sheath / can
Impeller		Magnet material
Diffuser		Barrel
Wear ring casing		Column pipe
Wear ring impeller		Bearing bracket
Wear plate / lining		Motor stool
Case bush		Coupling
Casing gaskets		Coupling guard
Shaft		Base plate
		Shaft sleeve
		Throat bush
	Paint	According to "Specification for Painting"; Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0006

Sump Arrangement (Note 33)

Sump Dimensions:

Grade Elevation	1		m
Low Liquid Level	2	0.1	m
C.L. Of Discharge	3		m
Sump Depth	l_1	0.65	m
Pump Length	l_2		m
Grade to Disch.	l_3		m
Grade to Low Liquid Level	l_4		m
Grade to 1st Stg Impl'r.	l_5	0.5 (VTC)	m
Submergence Req'd	l_6		m
Sump Diameter	Fd		m



Remarks

For Pump schematic and P&ID refer to BK-GCS-PEDCO-120-PR-PI-0017. and calculation note for pumps; BK-GCS-PEDCO-120-PR-CN-0001.

Customer		Supplier	
Prepared (Data / Dep/ Signature)	Checked (Data / Dep/ Sign.)	Prepared (Data / Dep/ Signature)	Checked (Data / Dep/ Sign.)