



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادرکننده

PEDCO

تسهیلات

120

رشته

ME

نوع مدرک

DT

سریال

0014

نسخه

D03

شماره صفحه: ۱ از ۸

## طرح نگهداشت و افزایش تولید ۲۷ مخزن

## MECHANICAL DATA SHEETS FOR SLUG CATCHER

## نگهداشت و افزایش تولید میدان نفتی بینک

Rev.	Date	Purpose of Issue / Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval
D03	SEP.2024	IFA	V.Amjadi	M.Fakharian	M. Sadeghian	
D02	OCT.2023	IFA	H.Ghadyani	M.Fakharian	S.Faramarzpoor	
D01	SEP.2022	IFA	H.Adineh	M.Fakharian	M.Mehrshad	
D00	DEC.2021	IFC	H.Adineh	M.Fakharian	M.Mehrshad	

Class: 1

CLIENT Doc. Number: F0Z-708845

status:

IDC: Inter-Discipline Check

IFC: Issued For Comment

IFA: Issued For Approval

AFD: Approved For Design

AFC: Approved For Construction

AFP: Approved For Purchase

AFQ: Approved For Quotation

IFI: Issued For Information

AB-R: As-Built for CLIENT Review

AB-A: As-Built -Approved



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D03	0014	DT	ME	120	PEDCO	GCS	BK

شماره صفحه: ۸ از ۲

REVISION RECORD SHEET

Page	D00	D01	D02	D03	D04
1	X	X	X	X	
2	X	X	X	X	
3	X	X		X	
4	X	X			
5	X	X	X	X	
6	X	X	X		
7	X	X	X		
8	X	X			
9					
10					
11					
12					
13					
14					
15					
16					
17					
20					
21					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					

Page	D00	D01	D02	D03	D04
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
84					
85					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
122					
123					
124					
125					
126					
127					
128					



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

BK

بسته کاری

GCS

صادرکننده

PEDCO

تسهیلات

120

رشته

ME

نوع مدرک

DT

سریال

0014

نسخه

D03

شماره صفحه: ۸ از ۳

General Notes

D03

Rev.

- The Asterisk \* denotes information and/or confirmation required from VENDOR. The Vendor shall be fully responsible for the complete mechanical design, preparing calculation book and supply of the vessel.
- Deleted
- VENDOR shall include for the services of a independent verification body for mechanical design, stage inspection, testing and stamping of the equipment (if possible).
- Painting and coating (internal & external) shall be as per project 'Specification for Painting', Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0006 and 'Specification for Lining', Doc. No. BK-GNRAL-PEDCO-000-PI-SP-0007.
- Flanges shall comply with ASME B16.5. Nozzle bolt holes shall straddle the natural centrelines for horizontal nozzles. VENDOR to confirm maximum allowable nozzle loads and moments (RF: Raised Face, WN: Welding Neck)
- All reinforcement pads shall have 1/4" (6mm) tell-tale hole and 1/8" (3mm) vent hole as per Standard Detail Drawing For Pressure Vessels and Heat Exchangers', Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001".  
proof load test c SEP.2024  
proof load test davits. Davits shall be proof load tested on the vessels to 1.5 x Safe Working Load (SWL) and shall be marked accordingly.
- All external bolts and nuts shall be hot dip galvanized. Internal bolts and nuts shall be stainless steel.
- Loads at support base, Shall be calculated and determined by vendor.
- Access Ladder & Platform to be considered .
- Stand pipe connections on equipment shall be at least 3", 150# and for instruments installation on the stand pipe at least 2", 300# flanges shall be considered (on the related piping system)
- All material, corrosion allowance and their suitability for the process fluid at design pressure and temperature to be confirmed by vendor.
- Deleted
- All nozzle locations and orientations will be finalized later.
- Instrumentation items are excluded from vendor's scope of supply.
- Any changes in material of construction, location & orientation of the nozzles shall be confirmed by client.
- All materials shall be new and unused.
- Fabrication tolerances for vessel shall be in accordance with requirement of ASME code.
- Location and number of lifting lugs on vessels shall be specified on VENDOR drawing.
- All items shall be clearly match marked against vessel drawings to facilitate erection.
- Deleted
- Vendor shall supply details of all welding connections and give general specification of used materials.
- For equipment requiring PWHT, final inspection and acceptance by the CLIENT or its nominated representative shall only be undertaken against NDE after PWHT. All weldings shall be made before vessel heat treatment (if any).
- Equipment packaging, preparation for shipment and delivery shall be in accordance with the project Packing, Marking, Transportation Procedure Doc. No. "BK-GNRAL-PEDCO-000-QC-PR-0045".
- Specified accessories and attachments shall be supplied by vendor.
- Gasket shall be spiral wound type, graphite filled with inner ring and outer ring S.S.316.
- Deleted
- Deleted
- Two M12 earthing bosses shall be provided on vessel support. Material of Earthing Bosses shall be S.S. 316



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

نسخه	سریال	نوع مدرک	رشته	تسهیلات	صادرکننده	بسته کاری	پروژه
D03	0014	DT	ME	120	PEDCO	GCS	BK

شماره صفحه: ۴ از ۸

General Notes (Cont'd)

Rev.

30. For standard detail of Earth lug execution refer to the Project "Standard Detail Drawing For Pressure Vessels and Heat Exchangers Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001".
31. Elliptical heads shall be Ultrasonic Tested for lamination after forming.
32. The projection of equipment's nozzles should be considered as per 'Standard Detail Drawing For Pressure Vessels and Heat Exchangers', Doc. No. BK-GNRAL-PEDCO-000-ME-DW-0001".
33. The elevation of equipment's nozzels should be specified as follows :  
I. For vertical vessels : from bottom T.L.  
II. For horizontal vessels : from Left T.L.
34. Nozzles and flanges shall be suitably supported and reinforced based on nozzle loads provided in project Specification for Pressure Vessels, Document No. BK-GNRAL-PEDCO-000-ME-SP-0001.
35. Prior to sealing the vessel for shipping and storage, the inside surface of the equipment shall be 100% visually inspected. Internal
36. Minimum requirement for pre-commissioning, commissioning, start up and two years operation spare parts shall be in accordance with ☐
36. Minimum requirement for pre-commissioning, commissioning, start up and two years operation spare parts shall be in accordance with ☐ document E&C-QC-SP-1.☐
- 37 Lifting Lugs / trunnions shall be provided to facilitate a single point lift. If a single point lift cannot be achieved without the use of a lifting beam, then VENDOR shall provide a suitable, certified, lifting beam.
38. Design pressure specified is at top of vessels. VENDOR design shell include static head for vessels flooded with specific gravity of the handled liquid.
39. VENDOR is to maximize shop fabrication based on the following transportation limits:☐  
- Maximum weight: 96 tonnes  
- Maximum load per axle: 12 tonnes  
- Maximum length: 50.0 m  
- Maximum width: 5.0 m  
- Maximum height: 5.2 m  
For items with dimensions and weights greater than the road capacity specified above, VENDOR may be required to split the package into several components.
40. All external attachments directly welded to the pressure part shall be the same material as vessel grade.
41. All dimensions are in "mm" unless otherwise specified.
42. The material shall be in compliance with NACE MR0175/ISO15156 and Specification For Material Requirements in Sour service Document No. BK-GNRAL-PEDCO-000-PI-SP-0008.
43. Deleted
44. DEMISTER specification will be finalized latter.
45. Welded carbon and carbon manganese steels for vessel shall comply with the following :  
Carbon content shall not exceed 0.23%.  
Based on the ladel analysis, below equation shall be satisfied.  
 $Ce_q = C + Mn/6 + (Cr + Mo + V)/5 + (Cu + Ni)/15 < 0.42 \%$
46. All carbon steel material shall be fully killed, fine grain treated and supplied in the normalized condition.
47. Sacrificial Anode is required for the equipment.



NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه

بسته کاری

صادر کننده

تسهیلات

رشته

نوع مدرک

سریال

نسخه

BK

GCS

PEDCO

120

ME

DT

0014

D03

شماره صفحه: ۸ از ۵

Mech. Data Sheet For Slug Catcher (V-2104) / sheet 1 of 4

Rev	DATA SHEET				Rev
1	Description	: <i>Inlet Gas K.O. Drum</i>			
2	Tag No.	: <i>V-2104</i>			Quantity : <i>1 Set</i>
3	Type	: <i>Pressure Vessel</i>			
<b>Process Design Data</b>					
5	Contents	<i>H2O-HC</i>	Corrosive / Erosive	<i>CO2,H2S</i>	
6	Operating Temp. (°C)	<i>15.5~32</i>	Liquid Flow (kg/h)	<i>360078</i>	
7	Operating Press. (barg)	<i>5.5</i>	Vap. Molec. Weight (kg/kmol)	<i>33.2</i>	
8	Gas Flow (kg/h)	<i>12223</i>	Liquid Sp. Gravity	<i>0.85</i>	
9	Liquid Viscosity (cP)	<i>0.4207</i>	Lethal / SOUR :	<i>SOUR</i>	
<b>Mechanical Design Data (Note 1)</b>					
10	Design Temp. (°C)	<i>85</i>	Vessel Orientation	<i>Horizontal</i>	
12	Design Press. (barg)	<i>9</i>	HHLL (mm)	<i>3900</i>	
13	Test Press. (barg)	<i>Per Code &amp; Spec Requirements.</i>	Nor. Liquid Vol. (m³)	<i>48 (Vol. from Bottom to NLL)</i>	
14	Internal Vacuum (barg)	<i>F.V.</i>	In. Dia. Of Boots (mm)	<i>-</i>	
15	In. Dia. of Shell (mm)	<i>4200</i>	Boot Length (mm)	<i>-</i>	
16	Shell Wall Thk. SEP.2024	<i>*</i>	Joint Efficiency	<i>0.85 (Shell) / 1 (Head)</i>	
17	Head Wall Thk. (mm)	<i>*(After Forming)</i>	MDMT (°C)	<i>5</i>	
18	Shell Wall Thk. OCT.2023	<i>*</i>	Joint Efficiency	<i>0.85 (Shell) / 1 (Head)</i>	
19	Head Wall Thk. (mm)	<i>*(After Forming)</i>	MDMT (°C)	<i>5</i>	
D03 20	Seismic Design	<i>Site Class: D, Code: ASCE 7-10 Fa=1,FV=1.33,S1=0.46,Ss=1.125,I=1.25</i>	Insulation Required	<i>NO</i>	
D03 21	Wind Design	<i>Speed: 232 Km/hr (Max.), Code: ASCE 7-10</i>			
<b>Materials (Note45, 46)</b>					
23	Code	<i>ASME II / ASTM</i>	Internal Welded Supports	<i>A 516 Gr. 60 N</i>	
24	Shell	<i>A 516 Gr. 60 N</i>	Nozzle Necks	<i>A 106 Gr.B N</i>	
25	Heads	<i>A 516 Gr. 60 N</i>	Pipes	<i>A 106 Gr.B N</i>	
26	Lining	<i>P3</i>	Plates	<i>A 516 Gr. 60 N</i>	
27	Saddles	<i>A 283 Gr. C</i>	Forgings	<i>A 105 N</i>	
28	Wear Plate	<i>A 516 Gr. 60 N</i>	Flanges	<i>A 105 N</i>	
29	Stiffening Rings	<i>A 516 Gr. 60 N</i>	Fittings	<i>A 234 Gr. WPB</i>	
30	Gaskets	<i>Note 26</i>	Welded Internals	<i>A 516 Gr. 60 N</i>	
31	Lifting Lugs	<i>A 516 Gr.60 N / A 283 Gr. C</i>	External Bolts	<i>A 193 Gr. B7 (8)</i>	
32	Reinforcing Pads	<i>A 516 Gr. 60N</i>	Nuts	<i>A 194 Gr. 2H (8)</i>	
33	Ladder & Platform	<i>C.S.</i>	Internal Bolts	<i>A193 Gr. B8M (8)</i>	
34	Gratings	<i>Hot Dip Galvanized C.S.</i>	Nuts	<i>A194 Gr. 8M (8)</i>	
35	External Welded Clips	<i>A 516 Gr. 60 N</i>	Name Plate	<i>S.S. 316</i>	
<b>REFERENCE STANDARDS &amp; DOCUMENTS</b>					
D03 38	Mechanical Design Code	<i>ASME SEC. VIII, DIV. 1, IPS-G-ME-150</i>			
39	Specification for Pressure Vessels	<i>BK-GNRAL-PEDCO-000-ME-SP-0001</i>			
40	Process Basis of Design	<i>BK-GNRAL-PEDCO-000-PR-DB-0001</i>			
41	Piping & Instrument Diagram (P&ID)	<i>BK-GCS-PEDCO-120-PR-PI-0004</i>			
42	Specification for Painting	<i>BK-GNRAL-PEDCO-000-PI-SP-0006</i>			
D03 43	Specification for Lining	<i>BK-GNRAL-PEDCO-000-PI-SP-0007</i>			
44	Specification for Insulation	<i>BK-GNRAL-PEDCO-000-PI-SP-0019</i>			
45	Specification For Material Requirements in Sour service	<i>BK-GNRAL-PEDCO-000-PI-SP-0008</i>			
<b>Fabrication and Inspection Requirements</b>					
47	Inspection Authority	<i>TPI &amp; Client</i>			
48	Material Certification	<i>In Accordance with BS EN 10204:2004, Type 3.1, Minimum for Pressure Containing and Attachments</i>			
49	Hydro Test Medium	<i>Water</i>	Hydro Test Procedure	<i>Yes;Per Code &amp; Spec. Requirements</i>	
50	Post Weld Heat Treatment	<i>YES(PROCESS REASON)</i>	PT	<i>100%</i>	
51	MT	<i>100 % on Lifting Lug Fillet Welds</i>	UT	<i>Yes;Per Code &amp; Spec. Requirements</i>	
52	RT	<i>100 % On T-Joints and Head Joints Butt-Welds,</i>			
53		<i>Spot On Shell Longitudinal and Circumferential Joints Butt-Welds,</i>			
54		<i>100 % On Nozzle Neck to Flange &amp; Fabricated Nozzle Neck Longitudinal Butt-Welds,</i>			
55	RT Report	<i>Yes; Per Code &amp; Spec. Requir.</i>	PT Report	<i>Yes;Per Code &amp; Spec. Requirements</i>	
56	MT Report	<i>Yes; Per Code &amp; Spec. Requir.</i>	UT Report	<i>Yes;Per Code &amp; Spec. Requirements</i>	
57	Fabrication Quality Control Plan (With Offer)	<i>Yes</i>			
58	Welding Procedure Review / Approval	<i>Yes</i>			
59	Surface Preparation & Coating	<i>Per Specification for Painting: Doc. No. "BK-GNRAL-PEDCO-PI-SP-0006"</i>			
60		<i>Per specification For Lining: Doc. No.: BK-GNRAL-PEDCO-000-PI-SP-0007</i>			
61					
62					
63					
64					





NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:





۰۵۳ - ۰۷۳ - ۹۱۸۴

پروژه	بسته کاری	صادرکننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه
BK	GCS	PEDCO	120	ME	DT	0014	D03

شماره صفحه: ۸ از ۷

Mech. Data Sheet For Slug Catcher (V-2104) / sheet 3 of 4

Sketch





NISOC

نگهداشت و افزایش تولید میدان نفتی بینک  
سطح الارض

احداث ردیف تراکم گاز در ایستگاه جمع آوری بینک

MECHANICAL DATA SHEETS FOR SLUG CATCHER



شماره پیمان:

۰۵۳ - ۰۷۳ - ۹۱۸۴

پروده	بسته کاری	صادر کننده	تسهیلات	رشته	نوع مدرک	سریال	نسخه
BK	GCS	PEDCO	120	ME	DT	0014	D03

شماره صفحه: ۸ از ۸

Mech. Data Sheet For Slug Catcher (V-2104) / sheet 4 of 4

Rev.	WEIGHT					Rev.
1	WEIGHT CONTROL DATA SHEET SI UNIT (1)			1/1		
2						
3						
4						
5						
6	Service : <i>Slug Catcher</i>			Location : <i>Bushehr (Binak Oilfield)</i>		
7	Type :			Quotation No. :		
8	No. trains :			Serial No. :		
9	No. stages :					
10	Supplier :					
11	Manufacturer :					
12	Model :					
13						
14	Note: Information to be completed by equipment vendor.					
15						
16	<b>Total weight (kg)(1,2)</b>					
17	Fabrication	Erection	Operation	Hydrostatic Test	Removable internal	Ladder & Platform
18						
19						
20						
21						
22						
23	<b>WEIGHT AND C OF G DATA REQUIRED (9)</b>					
24	CONDITION	WEIGHT ACCURACY %	WEIGHT (kg)	CENTER OF GRAVITY (mm)		
25				X	Y	Z
26	Dry					
27						
28						
29						
30	<b>SKETCH</b>					
31	<p style="text-align: center; font-size: 2em; opacity: 0.5;">Page 1</p>					
32						
33						
34						
35						
36						
37						
38						
39						
40						
41						
42						
43						
44						
45						
46						
47						
48						
49						
50						
51						
52	<b>NOTES</b>					
53	1) All lifting points to be load tested and certified.					
54	2) Any spreader beam to be load tested and certified.					
55	3) Lifting / rigging plan for skid mounted equipment to be provided by the Vendor.					
56						
57						
58						
59						
60						
61						
62						
63						