

ITEM No.	SYMBOLS	DESCRIPTION	ITEM No.	SYMBOLS	DESCRIPTION
01	\Leftrightarrow	VOLTAGE TRANSFORMER	20	Ø	THERMO SWITCH
02	\ominus	CURRENT TRANSFORMER	21	⊞	OPERATING MECHNISM
03	-	CURRENT TRANSFORMER (RING TYPE)	22	\otimes	SIGNAL LAMP
04		CORE BLANCD C.T.	23	or T	DRAW OUT UNIT
05	*	CIRCUIT BREAKER	24	A	AMMETER
06	\	NORMALLY OPEN / CLOSE CONTACT	25	V	VOLTMETER
07	0==7	LIMIT SWITCH	26	AS	AMMETER SWITCH
08	\	DISCONNECTOR (ISOLATOR)	27	VS	VOLTMETER SWITCH
09	4	CONTACTOR	28		BUS BAR
10	€	START/STOP PUSH BUTTON	29	<u></u>	OPERATING BY TURNING
11	<u></u>	EARTHING SWITCH	30	L O R	THREE POSITION LATCH TYPE SELECTOR SWITCH
12	갓	THERMAL RELAY	31	_	LATCH
13	+	COIL	32	к₩н	KILO WATT HOUR METER
14	1		33	0	RELAY (NUMBER IN THE SYMBOLS INDICATES)
15	\(\rightarrow - \rightarrow \)	TWO POLE MINIATURE CIRCUIT BREAKER	34	Ф	FUSE GENERAL SYMBOL
16	**	TWO POLE EARTH LEAKAGE MINIATURE CIRCUIT BREAKER	35		ELECTRICAL HEATER
17	A-0-M 5H1—	THREE POSITION SELECTOR SWITCH	36		CABLE NUMBER INDICATION
18	∇	CABLE GLAND	37		TESTING TERMINAL
19	□ OR O	TERMINAL	38	M—	OPERATING BY ELECTRIC MOTOR

NOTES

- 1- MAX. TWO WIRES SHOULD BE CONNECTED TO ONE TERMINAL.
- 2- PANEL HEATER SHOULD BE INSTALLED IN SUITABLE POSITION.
- 3- THE BURDEN OF C.T. & V.T. SHOULD BE FINALIZED BY PANEL MANUFACTURE.

	ABBREVIATION
Α	AMPERE
М	MOTOR
AS	AMMETER SWITCH
CT	CURRENT TRANSFORMER
Hz	HERTZ
IP	DEGREE OF PROTECTION BY ENCLOSURE
KA	KILO AMPERE
ΚV	KILO VOLT
ΚW	KILO WATT
MV	MEDIUM VOLTAGE
VS	VOLTMETER SWITCH
VI	VOLTAGE TRANSFORMER
KVA	KILOVOLT-AMPERE
K₩H	KILOWATT-HOUR
VCB	VACUUM CIRCUIT BREAKER
TCS	TRIP COIL SUPERVISION
KVAR	KILOVAR
SWGR	SWITCH GEAR

BLECTRICAL LOAD LIST BK-CCS-PEDCO-120-EL-LI-0001
EXISTENT MV SWITCHGEAR EXPANSION SINGLE LINE DIAGRAM
BK-CCS-PEDCO-120-EL-SL-0003

DRG. No. BK-dds-PEDC0-120-EL-1J-0001

REFERENCE DRAWING

D05	MAY.2023	IPI	H,SHAKIBA	V.Pakharian	A.M. MORESTEN I	**,**						
D04	DEC'5055	IPI	H,SHAKIBA	V.PAKHARIAN	W.VBHRSHAD	**,**						
D08	10F5055	IPI	H,\$HAKIBA	V.PAKHARIAN	W.VEHRSHAD	**,**						
D05	AP1.2022	IPI	H.#HÁKIBÁ	V.PAKHARIAN	W.VEHRSHAD	**,**	***	********	,	****	**,**	***
D01	MAR.2022	IPI	H,\$HAKIBA	V.PAKHARIAN	W.VEHRSHAD	**,**	REV.	DESCRIPTION	BY	DATE	BY	DATE
D00	3808.MAL	IPI	H.#HAKIBA	V.PAKHARIAN	W.WEHRSHAD	**,**	MET.	DESCRIPTION	CHECKED REV. APPR.			
REV.	DATE	P.O.I.Ø	PREP.	CHK.	APP.	AUT.		اطق نفت خيز جنوب ميباشد.	به شرکت ملی مد	ن أقلباس متعلق و	غ این نقته و حو	اصل و کلیه ت

PROJECT NAME: BINAK OILPIELD DEVELOPMENT/SURPACE PACILITIES
GAS COMPRESSOR STATION PROJECT NO.: 971020

EPC CONTRACTOR: HIRGAN ENERGY - DESIGN & INSPECTION COMPANIES

EPD/EPC CONTRACTOR (GC): PETROIRAN
DEVELOPMENT
COMPANY

DEVELOPMENT

THE ORIGINAL AND ALL COPIES OF THIS DRAWING TOGETHER WITH THE COPYRIGHT THEREIN ARE THE SOLE PROPERTY OF N.I.S.O.C./ FIELDS BINAK OILFIELD DEVELOPMENT SURFACE FACILITIES GAS COMPRESSOR STATION DATE SCALE DRAWING BY CHECKED BY PROJECT ENG.

NO CONSTRUCTION PERMITTED UNLESS DRAWING APPROVED

(VENDOR TITLE BLOCK)**

ITEM No.	SYMBOLS	DESCRIPTION	ITEM No.
39	-	LIGHTING ARRESTER OR SURGE ARRESTER	58
40	AT	AMMETER TRANSDUCER	59
41	VT	VOLT TRANSDUCER	60
42	KWT	KILO WATT TRANSDUCER	61
43	KVART	KILO VAR TRANSDUCER	62
44	CosøT	POWER FACTOR TRANSDUCER	63
45	Cos	POWER FACTOR METER	64
46	W	WATT METER	65
47	var	VAR METER	66
48	©	CLOSING COIL	67
49	©	SHUNT TRIP	68
50	RS	AUXILIARY RELAY	69
51	(XF)	AUXILIARY RELAY	70
52	27	UNDER VOLTAGE RELAY	71
53	(27M)	INDUCED VOLTAGE RELAY	72
54	33	POSITION SWITCH	73
55	38	BEARING PROTECTIVE DEVICE	74
56	46	REVERSE-PHASE OR PHASE- BALANCE CURRENT RELAY	75
57	49	MACHINE THERMAL RELAY	76

NOTES

- 1- MAX. TWO WIRES SHOULD BE CONNECTED TO ONE TERMINAL.
- 2- PANEL HEATER SHOULD BE INSTALLED IN SUITABLE POSITION.
- 3- THE BURDEN OF C.T. & V.T. SHOULD BE FINALIZED BY PANEL MANUFACTURE.

	ABBREVIATION
A	AMPERE
М	MOTOR
AS	AMMETER SWITCH
СТ	CURRENT TRANSFORMER
Hz	HERTZ
IP	DEGREE OF PROTECTION BY ENCLOSURE
KA	KILO AMPERE
ΚV	KILO VOLT
κ₩	KILO WATT
M∨	MEDIUM VOLTAGE
VS	VOLTMETER SWITCH
VI	VOLTAGE TRANSFORMER
KVA	KILOVOLT-AMPERE
к₩н	KILOWATT-HOUR
VCB	VACUUM CIRCUIT BREAKER
TCS	TRIP COIL SUPERVISION
KVAR	KILOVAR
SWGR	SWITCH GEAR
	M AS CT Hz IP KA KV KW MV VS VI KVA KWH VCB TCS KVAR

REFERENCE DRAWING

DRC. No. BK-dds-PEDC0-120-EL-LI-0001

D05	MAY.2023	IPI	H,SHAKIBA	V.PAKHARIAN	A. M. MORESENT	**,**	1					
D04	DEC'5055	IPI	H,SHAKIBA	V.Pakharian	M.Wehrshad	11,11						
D08	10F5055	IPI	H,SHAKIBA	W.PAKHARIAN	W.WEHRSHAD	**,**						
D05	AP1.2022	IPI	H,#HÁKIBÁ	V.PAKHARIAN	W.WEHRSHAD	**,**	***	*********	,	***,***	**/**	***,****
D01	MAR.2022	IPI	H,\$HÁKIBÁ	W.PAKHARIAN	W.WEHRSHAD	97,09	REV.	DESCRIPTION	BY	DATE	BY	DATE
D00	3808, MAL	IPI	H.SHAKIBA	V.PAKHARIAN	W.WEHRSHAD	**,**	REV.	DESCRIPTION	CHE	CKED	REV.	APPR.
		-										

REV. DATE P.O.I.S PREP. CHK. APP. AUT. PROJECT NAME: BINAK OILPIELD DEVELOPMENT/SURPACE PACILITIES

GAS COMPRESSOR STATION

PROJECT NO.: EPC CONTRACTOR: **ENERAN** T HIRGAN ENERGY - DESIGN & INSPECTION COMPANIES

971020 EPD/EPC CONTRACTOR (CC): PEDCO

PETROIRAN DEVELOPMENT COMPANY

THE ORIGINAL AND ALL COPIES OF THIS DRAWING TODGTHER WITH THE COPYRIGHT THEREIN ARE THE SOLE PROPERTY OF N.I.S.O.C./ FIELDS BINAK OILFIELD DEVELOPMENT SURFACE FACILITIES GAS COMPRESSOR STATION

اصل و کلیه شخ این نقشه و حق اقتباس متعلق به شرکت ملی مناطق نفت خیز جنوب میباشد.

EXISTENT MV SWITCHGBAR EXPANSION BK-CCS-PEDCO-120-BL-SL-0003

DATE SCALE DRAWING BY CHECKED BY PROJECT ENG. NO CONSTRUCTION PERMITTED UNLESS DRAWING APPROVED APPROVED FOR CONSTRUCTION BY:

(VENDOR TITLE BLOCK)**

DESCRIPTION

INSTANTANEOUS OVER CURRENT RELAY

AC TIME OVER CURRENT RELAY

SENSITIVE EARTH FAULT RELAY

TRIP COIL SUPERVISION RELAY

TOO FREQUENT START RELAY

LOCKED ROTOR RELAY

INTERTRIP RECEIVE RELAY

WINDING OVER TEMPERATURE RELAY

LOCK OUT RELAY

INSTANTANEOUS EARTH FAULT RELAY

AC INVERSE TIME EARTH FAULT RELAY

SYMBOLS

(50)

(51)

(50G)

(50N)

(51N)

(74TCS)

86)

66

(49R)

49CR

(867)

ELECTRICAL TYPICAL SCHEMATIC DIAGRAMS FOR MV PANEL SCALE SIZE DRAWING NO.

SHEET NO. REV. BUDGET REF. LOCATION SIZE CLASS SERIAL NO. SHEET REVISION N.T.S A3 BK-GCS-PEDCO-120-EL-Dd-0001 03 0F 07 D06 063-073-9184 P 2 P 709040 03 0F 07 D06







