

# نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنیه تحت الارض



## خرید پکیج های کمپرسور گاز (رفت و برگشتی) بینک (قرارداد BK-HD-GCS-CO-0008\_03)

HAVAYAR

شماره پیمان: 9184 – 073 – 053

Bare-block MRT Procedure								
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	
BK	GCS	HY	120	QC	PR	0007	V02	

6 از 1:شماره صفحه

## طرح نگهداشت و افزایش تولید 27 مخزن

## **Bare-Block MRT Procedure**

نگهداشت و افزایش تولید میدان نفتی بینک

V02	18.01.2025	AFC	Havayar Co.	M.Fakharian	S.Faramarzpour	
V01	16.04.2024	IFR	Havayar Co.	M.Fakharian	S. Faramarzpour	
V00	27.02.2024	IFR	Havayar Co.	M.Fakharian	S. Faramarzpour	
Rev.	Date	Purpose of Issue/Status	Prepared by:	Checked by:	Approved by:	CLIENT Approval

#### Status:

IFA: Issued For Approval IFR: Issued For Review IFI: Issued For Information AFC: Approved For Construction



# نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنیه تحت الارض



## خرید پکیج های کمپرسور گاز (رفت و برگشتی) بینک (قرارداد BK-HD-GCS-CO-0008\_03)

HAVAYAR

ن:	شماره پیمار
053 - 073 - 9	9184

	Bare-block MRT Procedure							
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سر يال	نسخه	
BK	GCS	HY	120	QC	PR	0007	V02	

6 از 2:شماره صفحه

### **REVISION RECORD SHEET**

PAGE	V00	V01	V02	V03	V04
1	Х	X			
2	X	X			
3	X X X				
<u>4</u> 5	Y X	X	X		
6	X	X			
7	X				
8	X				
9					
10					
11					
12					
13					
14					
15 16					
17					
18					
19					
20					
21					
22					
23					
24					
<u> 25</u>					
26 27					
28					
29					
30					
31					
32					
33					
34					
35					
36 37					
38					
39					
40					
41					
42					
43					
44	<u> </u>				
45	1			-	
<u>46</u>	1			<del>                                     </del>	
47 48				<del>                                     </del>	
49	1				
50	İ			1	
51					
52					
53	<del> </del>			ļ	
54	1				
<u>55</u>	1			-	
<u>56</u>	1			<del>                                     </del>	
57 58	1			<del>                                     </del>	
58 59	<u> </u>			t	
60	1			1	
61					
62					
63					
64					
65					l

	V00	V01	V02	V03	V04
PAGE	700	VUI	VUZ	VU3	VU4
66 67					
68					
69					
70 71					
72					
73					
74					
75 76					
77					
78					
79					
80 81					
82					
83					
84		-			
<u>85</u> 86		<del>                                     </del>			
87					
88					
89					
90 91					
92					
93					
94					
95 06					
96 97					
98					
99					
100 101					
101					
103					
104					
105 106					
107					
108					
109		-			
110 111					
112					
113					
114		-			
115 116		<del>                                     </del>			
117					
118					
119		<del>                                     </del>			
120 121					
122					
123					
124		-			
125 126		<del>                                     </del>	1		1
127					
128					
129					
130					



# نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنیه تحت الارض



## خرید پکیج های کمپرسور گاز (رفت و برگشتی) بینک (قرارداد BK-HD-GCS-CO-0008\_03 )

				AR
н	A	V A	Y	AH
IN	DUS	TRIA	LGI	ROUP

شماره پیمان:	
053 - 073 - 9184	

Bare-block MRT Procedure								
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرک	سريال	نسخه	
BK	GCS	HY	120	QC	PR	0007	V02	

6 از 3:شماره صفحه

0.0	Introduction	4
0.1	General Definition	4
1.0	Mechanical Running Test	5
2.0	Inspection and Test Item	5
3.0	Acceptance criteria	5
4.0	BAR-OVER Check	6



### نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنیه تحت الارض



6

## خرید پکیج های کمپرسور گاز (رفت و برگشتی) بینک (قرارداد BK-HD-GCS-CO-0008\_03)

شماره پیمان:		Bare-block MRT Procedure								
053 - 073 - 9184	پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	ز 4:شماره صفحه	1
000 070 0104	BK	GCS	HY	120	QC	PR	0007	V02		

#### 0.0 Introduction

Binak oilfield in Bushehr province is a part of the southern oilfields of Iran, is located 20 km northwest of Genaveh city.

With the aim of increasing production of oil from Binak oilfield, an EPC/EPD Project has been defined by NIOC/NISOC and awarded to Petro Iran Development Company (PEDCO). Also, PEDCO (as General Contractor) has assigned the EPC-packages of the Project to "Hirgan Energy - Design and Inspection" JV.

As a part of the Project, a New Gas Compressor Station (adjacent to existing Binak GCS) shall be constructed to gather of 15 MMSCFD (approx.) associated gases and compress & transfer them to Siahmakan GIS.

#### 0.1 General Definition

The following terms shall be used in this document.

CLIENT:	National Iranian South Oilfields Company (NISOC)

PROJECT: Binak Oilfield Development – Surface Facilities; New

Gas Compressor Station

EPD/EPC CONTRACTOR (GC): Petro Iran Development Company (PEDCO)

EPC CONTRACTOR: Joint Venture of: Hirgan Energy – Design & Inspection

(D&I) Companies

VENDOR: HAVAYAR

THIRD PARTY INSPECTOR (TPI): The firm appointed by EPD/EPC Contractor (GC) and

approved by Client (in writing) for the inspection of

goods.

SHALL: Is used where a provision is mandatory.

SHOULD: Is used where a provision is advisory only.

WILL: Is normally used in connection with the action by Client


rather than by an EPC/EPD Contractor, supplier or

Vendor.

MAY: Is used where a provision is completely discretionary.



#### نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنیه تحت الارض





شماره پیمان: 9184 – 073 – 053

Bare-block MRT Procedure								
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	
BK	GCS	HY	120	QC	PR	0007	V02	

6 از 5: شماره صفحه



#### 1.0 Bare-Block Mechanical Running Test

- 1.1. Mechanical Running Test:
- 1.1.1. The test shall prove mechanical operation as complete unit (only Bare Body). Shop motor shall be used.



- 1.2. The compressor does not have to be pressure loaded for mechanical running test. The compressor suction/discharge valves shall be dismantled. Voltage, current, operation speed, vibration, bearing temperature shall be checked
- 1.2. Test Condition:
  - Compressor shall be tested at the specified number of revolutions.
  - The testing may be performed at a number of revolutions within +10% and 5% of the specified number of revolutions.
  - API 618 5th is applicable for this test.

#### 2.0 Inspection and Test Item

- 2.1. The compressor will be operated at rated RPM for 4 hours without cylinder valve and it will be checking every 1 hours. Following parameters shall be check:
  - Voltage & Current
  - Operation Speed
  - Vibration
  - Bearing temperature and oil temperature

#### 3.0 Acceptance criteria

- 3.1 Number of Revolutions The measurement shall be carried out by using a preliminary calibrated hand tachometer. The measurement of the number of revolutions shall be carried out of 2 or 3 times under the same condition and the average value shall be taken.
- 3.2 The testing may be performed at a number of revolutions within +10% and -5% of specified number of revolutions.

#### 3.3 Vibration

As a rule, vibration shall be measured at the bearings or in the vicinity thereof with respect to three directions (Axial/Vertical/Horizontal)

Applicable code: ISO 20816-8



### نگهداشت و افزایش تولید میدان نفتی بینک سطح الارض و ابنيه تحت الارض



## خرید پکیج های کمپرسور گاز (رفت و برگشتی) بینک (قرارداد BK-HD-GCS-CO-0008\_03)

شماره پیمان:
053 - 073 - 9184

Bare-block MRT Procedure								
پروژه	بسته کاری	صادر کننده	تسهيلات	رشته	نوع مدرك	سريال	نسخه	
BK	GCS	HY	120	QC	PR	0007	V02	

:شماره صفحه	6	از	6	

PART	mm/s (RMS)	PART	mm/s (RMS)	
FOUNDATION BOLT	2.0	CYLINDER LATERAL	8.7	
FRAME (TOP)	5.3	CYLINDER ROD	10.7	

Note: The vibration measurement value measured by KWANDSHIN is a reference value because it is a project that supplies only the Bare Body without the compressor bed and support.

#### 3.4 Temperature

During mechanical running test, bearing temperature shall be below ambient + 40 °C.

During mechanical running test, check the lube oil temperature and record it on the check sheet.

Following bearing temperature shall be measured:

- 1- Main bearing temperature drive side
- 2- Main bearing temperature non drive side



#### 4.0 **BAR-OVER Check**

#### 4.1 Piston clearance check

Rotating coupling by hand, and the piston may be brought into contact with the cylinder cover at the top and bottom dead point. And check the clearance with lead the acceptance clearance spec is as below:

Bottom =  $1.0 \sim 4.0 \text{ mm}$